

Town of Salem

Salem, New Hampshire

09 December 22

Salem District Court Roof Replacement

ICON Job #: 222068

Project Team:

Owner

Town of Salem, NH

33 Geremonty Dr.
Salem, NH 03079

Owner's Project Manager:

Trident Project Advisors

155 N. Broadway
Salem, NH 03079

Architects:

ICON architecture, inc.

101 Summer Street
Boston, MA 02110
(617) 451-3333

MEP Engineer:

Consulting Engineering Services

811 Middle Street
Middletown, CT 06457

SECTION 00 01 10
TABLE OF CONTENTS

DIVISION 01 - GENERAL REQUIREMENTS

Section 01 11 00	Summary of Work
Section 01 32 00	Construction Progress Documentation
Section 01 33 00	Submittal Procedures
Section 01 33 00a	Substitution Request Form
Section 01 74 19	Waste Management and Disposal
Section 01 77 00	Contract Closeout

DIVISION 02 – EXISTING CONDITIONS

Section 02 41 19	Selective Demolition
------------------	----------------------

DIVISION 06 - WOOD, PLASTICS AND COMPOSITES

Section 06 10 00	Rough Carpentry
------------------	-----------------

DIVISION 07 - THERMAL AND MOISTURE PROTECTION

Section 07 53 23	EDPM Roofing
Section 07 62 00	Sheetmetal Flashing and Trim
Section 07 92 00	Caulking and Sealants

DIVISION 08 - OPENINGS

Section 08 63 00	Metal Framed Skylights
------------------	------------------------

DIVISION 22 - PLUMBING

Section 22 04 00	General Conditions for Plumbing Trades
Section 22 14 00	Facility Storm Drainage

DIVISION 23 - MECHANICAL

Section 23 04 00	General Conditions for Mechanical Trades
Section 23 23 00	Refrigerant Piping
Section 23 31 00	HVAC Ducts and Casings

DIVISION 26 - ELECTRICAL

Section 26 04 00	General Conditions for Electrical Trades
Section 26 05 01	Electrical Demolition
Section 26 05 03	Electrical Wiring Connections
Section 26 05 19	Electrical Power Conductors and Cables

END OF TABLE OF CONTENTS

TABLE OF CONTENTS
00 01 10 - 1

SECTION 01 11 00

SUMMARY OF WORK

PART 1 - GENERAL

1.01 GENERAL PROVISIONS

- A. Attention is directed to the CONTRACT AND GENERAL CONDITIONS and all Sections within DIVISION 01 - GENERAL REQUIREMENTS which are hereby made a part of this Section of the Specifications.
- B. Equality of material, article, assembly, or system other than those named or described in this Section shall be determined in accordance with the provisions of Article V of the CONTRACT AND GENERAL CONDITIONS.

1.02 REQUIREMENTS INCLUDED

- A. Work under this Contract
- B. Examination of site and documents
- C. Supervision of Work
- D. Contractor Use of premises
- E. Site Logistics and Work Restrictions
- F. Coordination
- G. Reference standards
- H. Preconstruction conference
- I. Project meetings
- J. Permits, inspection, and testing required by governing authorities
- K. Field measurements
- L. OSHA safety and health course documentation
- M. Damage responsibility
- N. Asbestos and Hazardous Materials discovery

1.03 WORK UNDER THIS CONTRACT

- A. General Information: The Salem District Courthouse is located at 35 Geremonty Dr., Salem, NH. The two-story masonry building was built in 1981 and consists of approximately 23,000 sf floor area. The roof area is approximately 11,000 sf.
- B. The work will include all operations necessary to deliver the building(s) and ancillary on and off site amenities in a fully installed and operable condition including all utility and site work and obtaining all necessary licenses, permits, and certificates.

C. The scope of work, without limiting the generality thereof, includes all labor, materials, equipment and services required to perform the work described fully in the Drawings and Specifications and includes, but is not limited to the following major work:

1. Demolition of existing ballasted roof system, down to the existing deck.
2. Disconnect and reconnect of all major roof mounted mechanical equipment.
3. Provide vertical extensions of existing HVAC duct, roof curbs, wiring connections to existing roof top equipment to facilitate the roof replacement.
4. Installation of new hi-albedo (white) roofing system including minimum R-30 base insulation.

1.04 EXAMINATION OF SITE AND DOCUMENTS

A. The bidders are expected to examine and to be thoroughly familiar with all contract documents and with the conditions under which the work is to be carried out. The Town will not be responsible for errors, omissions, and/or charges for extra work arising from the General Contractors or Subcontractors failure to familiarize themselves with the contract documents, that he is familiar with the conditions and requirements of both where they require, in any part of the work a given result to be produced, that the contract documents are adequate and he will produce the required results.

1.05 SUPERVISION OF WORK

A. The Contractor shall be held directly responsible for the correct installation of all work performed under this Contract. The Contractor must make good repair, without expense to the Owner, of any part of the new work, or existing work to remain, which may become inoperative on account of leaving the work unprotected or unsupervised during construction of the system or which may break or give out in any manner by reason of poor workmanship, defective materials or any lack of space to allow for expansion and contraction of the work during the Contractor's warranty period, from the date of final acceptance of the work by the Owner

1.06 CONTRACTOR USE OF PREMISES

A. Use of the Site: Limit use of the premises to work in areas to be established with the Town before commencement of work. Coordinate work of all trades required outside the established area. Confine operations to areas within contract limits indicated. Do not disturb portions of the site beyond the areas in which the Work is indicated.

1. Owner Occupancy: Allow for Owner occupancy and use by the public.
2. Driveways and Entrances: Keep driveways and entrances serving the premises clear and available to the Owner, the Owner's employees, and emergency vehicles at all times. Schedule deliveries to minimize space and time requirements for storage of materials and equipment on-site.
3. The Contractor can gain access to the premises during the hours specified below. In addition the Contractor and his personnel will limit themselves only within the working premises during working hours. If work needs to be scheduled during times other than

those listed below, Contractor shall inform the Owner Project Manager.

B. Damage to existing work, if caused by the Contractor's operations under this Contract, shall be repaired at the Contractor's expense.

1.08 SITE LOGISTICS AND WORK RESTRICTIONS

A. The Contractor will be responsible for the following:

1. Construction Management Plan: The Contractor shall be required to prepare a detailed Construction Management Plan (CMP) which must be approved by the owner prior to the start of construction. The CMP will include all of the measures the Contractor determines are necessary to successfully complete the project while minimizing project impacts on the building, neighbors and surrounding community. The Contractor should assume that the nearby residences are occupied. The Contractor should assume that the Building can be fully operating during events on any given day and time.

2. The CMP must include, but shall not be limited to, the Contractors proposed procedures for following items:
 - a. Work logistics plan: A description of how of the Work will be phased and sequenced to minimize disruption to individual spaces and sections of the building.

- i) Work hour limitations:

Hours of operation shall be between the hours of **7:00am** and **5:00pm** Monday thru Friday. No noise work shall commence prior to 7:00am.

Fees for the Town of Salem Staff to be present outside of these hours, to be paid by the General Contractor.

- ii) Notification procedures regarding weekend, early or late day work:

Provide 24 hour written notification to the Town of Salem for work performed during weekend hours.

- b. Conduct of the Work

- i) Safety requirements and accident prevention

- ii) Emergency contact information and procedures

- iii) Conduct of Construction personnel

The Contractor shall employ only competent, first-class workers to do the work, and whenever the Contractor shall be notified by the Town of Salem in writing that any person on the work is, in its opinion, incompetent, unfaithful, disorderly or otherwise dissatisfactory, such a person shall be discharged from the work and shall not be re-employed on it except with the written consent of the Town Administrator.

- iv) Appropriate attire, Personal Protective Equipment

- v) Appropriate language and conduct:

No Smoking allowed on Town property.

No radios allowed on the job site.

- c. Noise control
 - i) General noise control
 - ii) Notification procedures for exceptional noise
- d. Site Logistics:
 - i. Site security, temporary fencing.
 - ii. Temporary facilities site plan
 - 1. Dumpster location within staging area
 - iii. Temporary Utilities
 - 1. Water: Coordinate use with Town Facilities
 - 2. Power: Coordinate use of existing Town electrical energy, required for temporary power.
 - a. Special circuits required for electric welders or other special equipment high-amperage and/or special voltage service shall be at the cost of the contractor.
 - iv. Storage of materials on-site within staging area
 - v. Storage of materials off-site
- vi. Protecting existing utilities
- e. Site Maintenance: Maintain full operation of building and Town grounds
 - i) Dust control
 - ii) Debris control and removal of rubbish
 - iii) Cleaning during construction
 - iv) Rodent control
- f. Transportation / Circulation Management
 - i) Truck routing and delivery schedule
 - ii) Logistics for delivery / loading / unloading
 - iii) No idling of vehicles is allowed
 - iv) Logistics for construction workers parking
- g. Coordinate designated area of parking with town officials
 - v) All posted parking & traffic restrictions must be followed
 - vi) Emergency vehicle access
 - vii) Street and sidewalk occupancy and/or closures
 - viii) Municipal police services if any

3. The format of the CMP must include the following items:
 - a Name of the Project
 - b Name of the Owner
 - c Name of the General Contractor
 - d Name of all Sub-Contractors
 - e Project Address
4. General Contractor will ensure that all subcontractors and other workers on the site receive and comply fully with the approved CMP.
5. No work shall commence until the Construction Management Plan has been approved by the Owner

B Law: All construction procedures shall conform to all local, state, and federal laws (including but not limited to safety, traffic, noise, and pollution laws) governing work in Salem, NH.

1.09 COORDINATION

- A. The General Contractor shall be responsible for the proper fitting of all the work and for the coordination of the operations of all trades, subcontractors or material and men engaged upon the work. The General Contractor shall do, or cause his agents to do, all cutting, fitting, adjusting, and repair necessary in order to make the several parts of the work come together properly.
1. Examine Contract Documents in advance of start of construction and identify in writing questions, irregularities or interference to the Owner Project manager in writing. Failure to identify and address such issues in advance becomes the sole responsibility of the Contractor.
- B. The work sequence shall follow planning and schedule established by the Contractor as approved by the Designer and the Owner Project Manager. The work upon the site of the project shall commence promptly and be executed with full simultaneous progress. Work operations which require the interruption of utilities, service, and access shall be scheduled so as to involve minimum disruption and inconvenience, and to be expedited so as to insure minimum duration of any periods of disruption or inconvenience.
- C. The Contractor shall review the tolerances established in the specifications for each type of work and as established by trade organizations. The Contractor shall coordinate the various trades and resolve any conflicts that may exist between trade tolerances without additional cost to Owner. The Contractor shall provide any chipping, leveling, shoring or surveys to ensure that the various materials align as detailed by the Designer and as necessary for smooth transitions not noticeable in the finished work.

1.10 REFERENCE STANDARDS

- A. For products specified by association or trade standards, comply with requirements for the standard, except where more rigid requirements are specified or are required by codes.
- B. Where reference is made in the Contractual Documents to Publications and Standards issued by Associations or Societies, the intent shall be understood to specify the current edition of

such Publications or Standards (including tentative revision) in effect on the date of the contract advertisement notwithstanding any reference to a particular date.

1.12 PROJECT MEETINGS

- A. Project meetings shall be held on a weekly basis and | or as required subject to the discretion of the Owner Project Manager.
- B. As a prerequisite for monthly payments, ordering schedules, shop drawing submitted schedules, shall be prepared and maintained by the Contractor and shall be revised and updated on a monthly basis, and a copy shall be submitted to the Owner Project Manager and Designer.
- C. In order to expedite construction progress on this project, the Contractor shall order all materials immediately after the approval of shop drawings and shall obtain a fixed date of delivery to the project site for all materials ordered which shall not impede or otherwise interfere with construction progress. The Contractor shall present a list and written proof of all materials and equipment ordered (through purchase orders). Such list shall be presented at the meetings and shall be continuously updated.

1.13 PERMITS, INSPECTION, AND TESTING REQUIRED BY GOVERNING AUTHORITIES

- A. If the Contract Documents, laws, ordinances, rules, regulations or orders of any public authority having any jurisdiction require any portion of the Work to be inspected, tested, or approved, the Contractor shall give the Designer, the Owner Project Manager or his/her designated representative, and such Authority timely notice (5 business days minimum) of its readiness so the Designer may observe such inspecting, testing, or approval.
 - 1. Coordinate with the requirements noted in Appendix B for testing to be executed by the General Contractor, in the presence of the Commissioning Agent.
- B. Unless otherwise specified under the Sections of the Specifications, the Contractor shall pay such proper and legal fees to public officers and others as may be necessary for the due and faithful performance of the work and which may arise incidental to the fulfilling of this Contract. As such, all fees, charges, and assessments in connection with the above shall be paid by the Contractor
- C. The Contractor shall furnish and install all information required by the building official and shall secure the general building permit for the work promptly on award of the Contract. The Contractor shall conform to all conditions and requirements of the permit and code enforcement authority. The Contractor shall provide names and license numbers of its responsible representatives to complete the application for permit, and shall receive the permit and promptly distribute copies to Owner and the Designer.
 - 1. Where Inspecting Authorities require corrective work for conformance with applicable Codes and Authorities, the Contractor shall promptly comply with such requirements, except in cases where such requirements clearly exceed the requirements of the Contract Documents, in which case the Contractor shall proceed in accordance with the procedures for modifications or changes in the work established in the Contract Documents, as amended.

1.14 FIELD MEASUREMENTS

A. Although care has been taken to ensure their accuracy, the dimensions shown for existing items and structures are not guaranteed. It is the responsibility of the Contractor to verify these dimensions in the field before fabricating any construction component. No claims for extra payment due to incorrect dimensions will be considered by the Owner.

1.15 SAFETY REGULATIONS

A. This project is subject to compliance with Public Law 91-596 "Occupational Safety and Health Act" - latest edition (OSHA 29 CFR 1926), with respect to all rules and regulations pertaining to construction, including Volume 36, numbers 75 and 105, of the Federal Register, as amended, and as published by the U.S. Department of Labor. OSHA cards for all contractors on site should be on file at the site.

1.16 DAMAGE RESPONSIBILITY

A. The Contractor shall repair, at no cost to Owner, any damage to building elements, site appurtenances, landscaping, utilities, etc. caused during demolition operation and work of this Contract.

1.17 ASBESTOS AND HAZARDOUS MATERIALS DISCOVERY

A. Given the building's age, it is assumed that there are no hazardous materials present. If unanticipated asbestos-containing materials or other Hazardous Materials not included in Contract are discovered at any time during the course of work, the Contractor shall cease work in the affected areas only and continue work in other areas, at the same time notify Owner and the Designer of such discovery. Do not proceed with work in such affected areas until written instructions are received. In the absence of unit prices, costs shall be negotiated or otherwise established prior to commencement of removal, in accordance with provisions of the Contract.

PART 2 – PRODUCTS

Not Used

PART 3 – EXECUTION

Not Used

END OF SECTION

SECTION 01 32 00

CONSTRUCTION PROGRESS DOCUMENTATION

PART 1 - GENERAL

1.01 GENERAL PROVISIONS

- A. Attention is directed to the CONTRACT AND GENERAL CONDITIONS and all Sections within DIVISION 01 - GENERAL REQUIREMENTS which are hereby made a part of this Section of the Specifications.

1.02 REQUIREMENTS INCLUDED

- A. Preliminary schedule.
- B. Construction progress schedule, updated with each application for Payment with network analysis diagrams and reports.

1.03 RELATED SECTIONS

- A. CONTRACT AND GENERAL CONDITIONS
 - 1. Failure to complete the Work on Time
- B. Section 01 11 00 – SUMMARY OF WORK
 - 1. Progress meetings.

1.04 REFERENCES

- A. AGC (CPM) - The Use of CPM in Construction - A Manual for General Contractors and the Construction Industry; Associated General Contractors of America; 1976.

1.05 TIME OF COMPLETION

- A. In accordance with the General Conditions, the Work shall be commenced at the time stated in the Notice to Proceed & shall be completed within the time period(s) specified in the Owner/Contractor Agreement.

1.06 SUBMITTALS

- A. Within 10 days after date of Agreement, submit preliminary schedule defining planned operations for the first 30 days of Work, with a general outline for remainder of Work.
- B. If preliminary schedule requires revision after review, submit revised schedule within 10 days.
- C. Within 10 days after review of preliminary schedule, submit draft of proposed schedule for review.
- D. Within 10 days after joint review, submit complete schedule.

PART 2 - PRODUCTS –

NOT USED

PART 3 - EXECUTION

3.01 PRELIMINARY SCHEDULE

- A. Prepare preliminary schedule in the form of a horizontal bar chart.

3.02 CONTENT

- A. Show complete sequence of construction by activity, with dates for beginning and completion of each element of construction.
- B. Identify each item by specification section number.
- C. Identify work of separate stages and other logically grouped activities.
- D. Show accumulated percentage of completion of each item, and total percentage of Work completed, as of the first day of each month.
- E. Provide separate schedule of submittal dates for shop drawings, product data, and samples, owner-furnished products, Products identified under Allowances, and dates reviewed submittals will be required from ICON architecture, inc,. Indicate decision dates for selection of finishes.
- F. Provide legend for symbols and abbreviations used.

3.03 BAR CHARTS

- A. Include a separate bar for each major portion of Work or operation.
- B. Identify the first work day of each week.

3.04 REVIEW AND EVALUATION OF SCHEDULE

- A. Participate in joint review and evaluation of schedule with ICON architecture, inc, at each submittal.
- B. Evaluate project status to determine work behind schedule and work ahead of schedule.
- C. After review, revise as necessary as result of review, and resubmit within 10 days.

3.05 UPDATING SCHEDULE

- A. Maintain schedules with monthly updates to record actual start and finish dates of completed activities.
- B. Indicate progress of each activity to date of revision, with projected completion date of each activity.
- C. Update diagrams to graphically depict current status of Work.

3.06 DISTRIBUTION OF SCHEDULE

- A. Distribute copies of updated schedules to project site file, to Subcontractors, suppliers, ICON architecture, inc., the Owners Project Manager and the Owner.

END OF SECTION

SECTION 01 33 00

SUBMITTAL PROCEDURES

PART 1 - GENERAL

1.01 GENERAL PROVISIONS

- A. Attention is directed to the CONTRACT AND GENERAL CONDITIONS and all Sections within DIVISION 01 - GENERAL REQUIREMENTS which are hereby made a part of this Section of the Specifications.

1.02 REQUIREMENTS INCLUDED

- A. Shop drawings, products data, samples, and schedule of values.

1.03 SHOP DRAWINGS, PRODUCTS DATA, AND SAMPLES

- A. General:

1. Review and submit to the Designer, shop drawings, project data and samples required by Specifications Sections.
2. No submissions made by FAX will be accepted.
3. The Contractor, within the time frame stated in Section 01 32 00 – CONSTRUCTION PROGRESS DOCUMENTATION, shall prepare and submit for the Designer's approval, a Schedule of Shop Drawings, Product Data and Samples required to be submitted for the Work. The schedule shall indicate, by trade, the date by which final approval of each item must be obtained, and shall be revised as required by conditions of the Work. The Schedule of Shop Drawings, Product Data and Samples shall correspond with the construction schedule so that the submissions relate to the time when the products and/or systems will be required on the site. The Designer will not approve a schedule that calls for out-of-sequence submittals.

- B. Shop Drawings:

1. Original drawings shall be prepared by General Contractor, Subcontractor, Supplier or Distributor, which illustrate some portion of the Work, showing fabrication, layout, setting, or erection of details.
 - a. Shop drawings shall be prepared by a qualified detailer.
 - b. Details shall be identified by reference to sheet and detail numbers indicated on Contract Drawings.
 - c. Maximum sheet size shall be 30-inch by 42-inch.
 - d. Submit with the required number of opaque prints specified herein.
 - e. Electronic Submittals are preferred, by email or the designer's file transfer site.

- C. Product Data:

1. Manufacturers' catalog sheets, brochures, diagrams, schedules, performance charts, illustrations, and other standard descriptive data. Provide manufacturer's catalogue sheet, specification for each product and other pertinent data as required under the individual specification.
 - a. Modify product data submittals to delete information, which is not applicable to the project.
 - b. Supplement standard information to provide additional information applicable to the project.
 - c. Clearly mark each copy to identify pertinent materials, products, or models.
 - d. Show dimensions and clearances required.
 - e. Show performance characteristics and capacities.
 - f. Show wiring diagrams and controls.
2. All such data shall be specific and identification of material or equipment submitted shall be clearly made in ink. Data of general nature will not be accepted.
3. Product Data shall be accompanied by transmittal notice. The Contractor's stamp of approval shall appear on the printed information itself.

D. Samples:

1. Physical samples shall illustrate materials, or workmanship, and shall establish standards by which work is judged. After review and approval, samples may be used in construction of project if not retained for comparison
 - a. Office samples of sufficient size and quantity shall clearly illustrate:
 - 1) Functional characteristics of product or material, with integrally related parts and attachment devices.
 - 2) Full range of color samples.
 - 3) After review and approval by Designer, samples may be used in construction of project if not retained for comparison.
2. Unless otherwise specified in the individual Section, the Contractor shall submit two labeled specimens of each Sample.
3. Samples shall be of adequate size to permit proper evaluation of material. Where variations in color or in other characteristics are to be expected, samples shall show the maximum range of variation. Materials exceeding the variation of the approved samples will not be approved on the Work.
4. Samples which can be conveniently mailed shall be sent directly to the Designer, accompanied by transmittal notice. On the transmittal notice the Contractor shall stamp his approval of Samples submitted.
5. If Sample is rejected by the Designer, a new Sample shall be resubmitted in the manner specified herein above. This procedure shall be repeated until the Sample is approved in writing by the Designer.
6. Samples will not be returned unless return is requested at the time of submission. The right is reserved to require submission of Samples whether or not specified in the Specifications, at no additional cost to the Owner.

1.04 GENERAL CONTRACTOR'S RESPONSIBILITIES:

- A. Review shop drawings, Product Data and Samples prior to submission. Verify:
 - 1. Field measurements.
 - 2. Field construction criteria.
 - 3. Catalog numbers and similar data.
 - 4. Conformance with Specifications.
 - 5. Integration with adjoining work.
- B. All shop drawings prepared by subcontractors shall be processed through the General Contractor. The General Contractor shall check all the shop drawings for conformity with the Contract Documents and particularly for field measurements and proper fit with adjoining work prior to submitting same to the Designer for approval. Certification shall appear on each shop drawing stating that the General Contractor has made his/her check. Format and content of the Contractor's certification stamp shall be subject to approval by the Designer and shall include, but not be limited to:
 - 1. The Term "By Others" shall not be used on shop drawings, the General Contractor shall state by whom the related items are to be furnished and/or installed.
 - 2. The Designer reserves the right to reject and return to the General Contractor, without examination, any shop drawings which have not been previously checked and certified as outlined above, which carry the term "by other" or such vague reference, which are difficult to read, which have arrived by FAX or which in any way are obviously not in conformity with Contract Requirements.
 - 3. Shop drawings shall show materials, design, dimensions, connections and other details necessary to ensure that they accurately interpret the Contract Documents and shall also show adjoining work in such detail as required to provide proper connection with same.
 - 4. The Designer will check and approve shop drawings only for conformance with the design concept and for compliance with information given in the Contract Documents. Approval of shop drawings by the Designer will not release the General Contractor from his responsibility for furnishing same of proper dimensions, size quantity and quality to effectively perform the work and carry out the requirements and intent of Contract Documents.
 - 5. Such approval will not relieve the Contractor from responsibility for errors of any sort in the shop drawings, nor for the proper coordination of any submittal with all other work. If the shop drawings deviate, or are intended to deviate, from the Contract Documents, the General Contractor shall so advise the Designer in writing at the time the shop drawings are submitted, stating the difference in value between the Contract requirements and that denoted by said shop drawings.
 - 6. The General Contractor shall assume full liability for delay attributed to insufficient time for delivery and/or installation of material or performance of the work when approval of pertinent shop drawing is withheld due to the failure of the General Contractor to submit, revise, or resubmit shop drawings in adequate time to allow the Designer a reasonable time, not to exceed twenty-one (14) calendar days, for normal checking and processing of each submission or resubmission.

- C. Coordinate each submittal with requirements of Contract Documents.
- D. The Contractor's responsibility for errors and omissions in submittals is not relieved by the Designer's review and approval of submittals, unless Designer gives tentative written acceptance of specific deviations identified.
- E. Notify the Designer in writing at the time of submission, of deviations in submittals from requirements of Contract Documents or previous submissions.
- F. Work that requires submittals shall not commence unless submitted with Designer's stamp and initials or signature indicating review and approval.
 - 1. No work shall be started in the shop or on the job, or materials delivered to the site, until pertinent shop drawings have been approved by the Designer.
- G. After the aforesaid review and approval, distribute copies.
- H. Maintain one (1) copy of each approved submittal at the project site.

1.05 SUBMISSION REQUIREMENTS:

- A. General: All submittals shall be made to the Designer's Office. The quantity and make-up of submittals shall be as established by the Designer; however, one electronic copy of all submittals shall be transmitted to the owner's Project Manager at the same time that such submittals are transmitted to the Designer. The Designer will log and distribute submittals for review by his consultant engineers.
- B. Make submittals promptly in accordance with approved schedules, and in such sequence as to cause no delay in the work.
- C. Submit number of samples specified in each Section of the Specifications.
- D. Submittals shall include:
 - 1. Date and revision dates.
 - 2. Project title and number.
 - 3. The names of:
 - a. Designer;
 - b. General Contractor;
 - c. Subcontractor;
 - d. Supplier;
 - e. Manufacturer;
 - f. Separate detailer when pertinent.
 - 4. Identification of product or material.
 - 5. Location of work and relation to adjacent structure or materials.
 - 6. Field dimensions clearly identified as such.
 - 7. Specification Section number and specific paragraph under which item is specified.

8. Submission number.
9. Applicable standards, such as ASTM number.
10. A blank space, five-inch by four-inch, for the Designer's stamp.
11. Contractor's remarks. Identify exceptions or deviations from Contract Documents and reasons for them.
 - a. If shop drawings submitted by the Contractor indicate a departure from the Contract and the Designer deems it to be minor adjustment in the interest of the owner (subject to concurrence by the Contractor stating it does not involve a change in Contract Price or extension of time), the Designer may approve the submission.
12. Contractor's stamp, initialed or signed certifying review and approval of submittal.
13. Any other items as called for by the Designer.
14. The Designer reserves the right to ask for shop drawings for any or all items on the project, whether or not requested in individual specification sections, at no additional cost to the Owner.

1.06 RESUBMISSION REQUIREMENTS:

- A. Resubmission: Resubmission procedure shall follow the same procedures as the initial submittal with the following exceptions:
 - B. Shop Drawings:
 1. Transmittal shall contain the same information as the first transmittal except that the submission number shall change sequentially. The drawing number/description shall be identical as the first transmittal but the date shall be the revised date for that submission.
 2. No new material should be included on the same transmittal for the resubmission.
 3. Indicate on drawings any changes which may have been made other than those requested by the Designer.
 - C. Product Data and Samples:
 1. Submit any new data and samples as required from previous submittal.

1.07 THE DESIGNER'S REVIEWS AND DISTRIBUTION OF SUBMISSIONS:

- A. The time frame for the Designer's review will not exceed fourteen (14) calendar days between her/his receipt of submittal. After the Designer's (and his/her consultant engineers) review, distribution shall be as stated herein.
 1. If submittal is 'reviewed - no exceptions taken', or 'reviewed, make corrections noted', the Designer shall compose a transmittal indicating the status. The Contractor shall then distribute said submittals to appropriate subcontractors.
 2. If submittal is 'reviewed - revise and resubmit' or 'rejected', the Designer shall compose a transmittal indicating the status.
 3. The Contractor is required to anticipate review time, including time for possible

rejection and resubmission, in establishing Schedule dates.

- a. The aforementioned time provided the Designer for checking shop drawings is from the date of receipt of shop drawings by the Designer to the date of shop drawings returned to the Contractor by the Designer.
4. The Designer will process the submission and indicate the appropriate action on the submission and the transmittal. Incomplete or erroneous transmittals will be returned without action.
5. The Designer will fill out transmittal in the following sequence:
 - a. Date received from Contractor.
 - b. Date returned to Contractor.
 - c. Action taken on submission.
 - d. Distribution, including number of copies distributed and type of material distributed (i.e., print, brochure or sample, etc.).
 - e. Designer's remarks (note major deviations from the Contract Documents).

B. Designer's Review Procedure:

1. Stamped REVIEWED, "NO EXCEPTIONS TAKEN":
 - a. No corrections or resubmissions required, fabrication may proceed.
2. Stamped REVIEWED, "MAKE CORRECTIONS NOTED":
 - a. If Contractor complies with noted corrections, fabrication may proceed. Submit corrected print for final review.
 - b. If, for any reason, the Contractor cannot comply with the noted corrections, fabrication shall not proceed and Contractor shall resubmit, following procedures outlined in this Section.
3. Stamped REVIEWED, "REVISE AND RESUBMIT" OR "REJECTED":
 - a. Contractor shall revise and resubmit for review. Fabrication shall not proceed.

C. Manufacturer's Instruction

1. When required in individual Specification Section, submit manufacturer's printed instructions for delivery, storage, assembly, installation, start-up, adjusting and finishing, in quantities specified for product data.

D. Certificates of Compliance: Submit certificates of compliance with the associated Shop Drawings, Product Data, and Samples required for the product in quantities specified for certificates of compliance.

E. Field Samples: Provide field samples of finishes at the project as required by individual Specification Section. Install sample complete and finished.

F. Patterns and Colors: Submit accurate color charts and pattern charts to the Designer for review and selection whenever a choice of color or pattern is available in a specified product, unless the exact color and pattern of a product are indicated in the Contract Documents. Color and Pattern charts shall represent the manufacturer's complete standard offerings, except where Specifications limit the offerings by defining a particular series or product type which is normally limited in color and pattern availability.

1.08 SCHEDULE OF VALUES:

A. Prior to the first request for payment, the General Contractor shall submit to the Designer and the Owner's Project Manager, a Schedule of Values of the various portions of the Work in sufficient detail to reflect various major components of each trade, including quantities when requested, aggregating the total contract sum, and divided so as to facilitate payments for work under each Section. The schedule shall be prepared in such form as specified or as the Designer or the Owner's Project Manager may approve, and it shall include data to substantiate its accuracy. Each item in the Schedule of Values shall include its proper share of overhead and profit. This schedule, including breakdown and values, requires the approval of the Designer and the Owner's Project Manager and shall be used only as a basis for the Contractor's request for payment.

PART 2 – PRODUCTS

Not Used

PART 3 – EXECUTION

Not Used

END OF SECTION

SUBSTITUTION REQUEST COVER SHEET

This cover sheet is required for all proposed substitutions including "OR EQUAL"s.

Contractor: _____

Subcontractor: _____

This Request Reference Number: _____

Substitution Summary: _____

Specification Section and Paragraph Number: _____

Contract Drawing and Detail Reference: _____

Date of This Request: _____

This Request Prepared By: _____

Conditions: Indicate all conditions that apply to this proposed substitution:

- Substitution required because specified item is no longer available.
- Substitution required because Contractor believes specified item is incorrect, inappropriate, or incompatible.
- Substitution recommended because it offers the Owner substantial advantage in:
- Quality
- Time
- Cost
- This is an "OR EQUAL".

Evidence: Indicate evidence attached:

- Tabulated side by side comparison of specified item and proposed substitution directly comparing each feature, characteristic, and performance.
- Manufacturer's product data for both specified item and proposed substitution. Origin of all information included on tabulated side by side comparison is highlighted
- Details showing how the proposed substitution interfaces with adjacent work.
- Certification that warranty, if any required, will be provided as required.
- Complete cost change information.
- Higher cost to Owner as stated in cost change information
- No change in cost to Owner.
- Lower cost to Owner, credit to Owner as stated in cost change information.

Deviations from Contract Documents: Itemize all deviations from Contract Documents if this proposed substitution is approved.

The undersigned attests that the undersigned has carefully examined this entire submission and that the requirements of the Contract Documents have been met.

By: _____
Signature

date

Printed or Typed Name

Title

ARCHITECT'S REVIEW STAMP: [Stamp review stamp below and indicate action on this substitution.]

Architect's Response:

SECTION 01 74 19

WASTE MANAGEMENT AND DISPOSAL

PART 1 - GENERAL PROVISIONS

1.1 GENERAL PROVISIONS

- A. Attention is directed to the CONTRACT AND GENERAL CONDITIONS and all Sections within DIVISION 01 - GENERAL REQUIREMENTS, which are hereby made a part of this Section of the Specifications.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for disposing of demolition waste and construction waste.

1.3 RELATED SECTIONS

- A. Section 02 41 19 – SELECTIVE DEMOLITION:
 - 1. Demolition and selective demolition activities.

1.4 DEFINITIONS

- A. Demolition Waste: Building and site improvement materials resulting from demolition or selective demolition operations.
- B. Disposal: Removal off-site of demolition waste and subsequent sale, recycling, reuse, or deposit in landfill or incinerator acceptable to authorities having jurisdiction.

1.5 PERFORMANCE REQUIREMENTS

- A. In the event the Contractor encounters previously unidentified material that is reasonably believed to be hazardous, asbestos containing, coated with lead-based paint, or oily debris, the Contractor shall immediately stop work in the affected area and report the condition to the Designer and the owner. At no time shall such material be handled or disposed of by the Contractor. The Contractor agrees to cooperate with the owner and any consultants engaged by owner to perform services with respect to the analysis, detection, removal, containment, treatment, and disposal of such regulated materials.

1.6 SUBMITTALS

- A. Record Keeping for Landfill and/or Incinerator Disposal: Documentation to be submitted by the Contractor shall include the following as a condition of each payment:
 - 1. Landfill and Incinerator Disposal Records: Indicate receipt and acceptance of waste by landfills and incinerator facilities licensed to accept them. Include manifests, weight tickets, and/or receipts.
- B. Records of Donations: Indicate receipt and acceptance of salvageable waste donated to individuals and organizations. Indicate whether organization is tax exempt.
- C. Records of Sales: Indicate receipt and acceptance of salvageable waste sold to individuals and organizations. Indicate whether organization is tax exempt. All Proceeds of Sales to be returned to Owner.

1.7 QUALITY ASSURANCE

- A. Regulatory Requirements: Comply with hauling and disposal regulations of authorities having jurisdiction.

1.8 WASTE MANAGEMENT PLAN

- A. Waste Identification: Indicate anticipated types and quantities of demolition and site-clearing waste generated by the Work. Include estimated quantities and assumptions for estimates.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION

3.1 PLAN IMPLEMENTATION

- A. General: Implement Waste Management Plan as approved by the Designer. Provide containers, storage, signage, transportation, and other items as required to implement WMP for the entire duration of the Contract.
 - 1. Review WMP with each trade when they first begin work on-site. Review plan procedures and locations established for recycling and disposal.
 - 2. Review and finalize procedures for material separation and verify availability of containers and bins needed to maintain production.
 - 3. Review procedures for periodic waste collection and transportation to recycling and disposal facilities.
- B. Site Access and Temporary Controls: Conduct waste management operations to ensure minimum interference with roads, streets, walkways, and other adjacent occupied and used facilities.

1. Designate and label specific areas on Project site necessary for separating materials that are to be salvaged, recycled, reused, donated, sold, and disposed.
2. Comply with project requirements for controlling dust and dirt, environmental protection, and noise control.

3.2 DISPOSAL OF WASTE

- A. General: Remove waste materials from Project site and legally dispose of them in a landfill or incinerator acceptable to authorities having jurisdiction.
 1. Except as otherwise specified, do not allow waste materials that are to be disposed of accumulate on-site.
 2. Remove and transport debris in a manner that will prevent spillage on adjacent surfaces and areas.
- B. Burning: Do not burn waste materials.
- C. Disposal: Transport waste materials off Owner's property and legally dispose of them.

END OF SECTION

SECTION 01 77 00

CONTRACT CLOSEOUT

PART 1 - GENERAL

1.01 GENERAL PROVISIONS

- A. All of the Contract Documents, including the General and Supplementary Conditions and Division 1 General requirements, apply to the work of and are hereby made a part of this Section.
- B. Examine all drawings and all other sections of the specifications for requirements therein affecting the work of this Section whether or not such work is specifically mentioned in this Section.
- C. This section contains information that applies to all work performed under the contract and is hereby made a part of each specification section.

1.02 FINAL CLEANING

- A. Unless otherwise specified under the various Sections of the Specifications, the General Contractor shall perform final cleaning operations as herein specified prior to final inspection.
- B. Maintain project site free from accumulations of waste, debris, and rubbish, caused by operations. At completion of work, remove waste materials, rubbish, tools, equipment, machinery and surplus materials, and clean all sight-exposed surfaces; leave project clean and ready for occupancy.
- C. Broom clean exterior paved surfaces and rake clean other surfaces of the grounds
- D. Leave pipe and duct spaces, plenums, furred spaces and the like clean of debris & decayable materials.
- E. At the end of the Project, General Contractor and each Subcontractor shall remove all his tools, equipment, machinery, and surplus materials from the job site. The General Contractor shall remove waste materials and rubbish from the project at this time. All temporary structures shall be removed and the project shall be left clean.

1.03 RECORD DOCUMENTS

- A. Record Documents: Provide complete and accurate Record Documents.
 1. Maintain Record Documents up-to-date at all times.
 2. Record information immediately as the work progresses.
- B. Record Documents Required: The following Record Documents are required:
 1. Record drawings.
 2. Record specifications.
 3. Record maintenance manuals.
 4. Record warranty and maintenance agreements.
 5. Record test reports and inspections.
 6. Record submittal file.
- C. Record Document Information Required: Customize and create Record Documents which incorporate all information from:
 1. Original contract documents.

2. Addenda.
3. Change order modifications.
4. Construction change directives.
5. Field directions and instructions from the Architect.
6. All changes and deviations from the original Contract Documents.

D. Method of Information Incorporation: Provide customized Record Documents. Revise, change, and modify original Contract Documents to clearly show all Record Document information required. Transfer the Record Document information to the original Contract Documents.

E. Labeling and Identification of Record Documents: Clearly label all Record Documents.

1. Clearly label all Record Documents.
2. Date each entry of Record Document information.
3. Date final Record Documents with the final Record Document submission date.
4. Keep the Architect's and Engineer's original Contract Document title blocks, but remove all professional seals and signatures from Record Documents.
5. Add the Contractor's name, address, and telephone number.
6. Add names, addresses, and telephone numbers of subcontractors with primary Record Document responsibility for mechanical, plumbing, fire protection, and electrical disciplines.

F. Record Documents Are Tied to Progress Payments: Maintaining Record Documents up-to-date, accurate, and in excellent condition is a prerequisite for approval of Contractor's application for progress payments.

G. Cost of Preparing Record Documents: Record Documents are a "General Requirement". The cost of General Requirements including Record Documents is included in the Contract Amount.

1. Changes in the Work: Recording changes in the Work is an essential function of Record Documents. No additional, special, itemized, or line item payment will be made for Record Document work. The cost of preparing Record Documents to incorporate changes in the work is included in the Contract Amount & in the Contractor's overhead percentage. The cost of preparing Record Documents related to changes in the work shall be included in the cost of each change in the work, whether the cost increases, decreases, or does not change the Contract Amount.

1.04 RECORD DOCUMENTS BINDERS

- A. Record Documents in Binders.
- B. Record Approved Submittals.
 1. Record Document maintenance manuals.
 2. Record Document warranty and maintenance agreements.
 3. Record Document test reports and inspections.
- C. Record Document Warranty and Maintenance Agreements: As the work progresses, compile complete binders and CDs of all warranties, guarantees, certificates, and maintenance agreements required by the Contract Documents.
 1. Ensure that all documents are properly conformed and signed.
 2. Ensure that each document is in a form acceptable to the Owner.
 3. For each warranty and maintenance agreement, clearly indicate date of commencement and expiration date.

1.05 PUNCH LIST

- A. Carefully check all work as the work is being performed. Correct unsatisfactory work immediately.
- B. Make frequent inspections of work during the finishing stages of the project, progressively checking for and correcting faulty work.
- C. Before substantial completion, provide to the Architect, a list of items to be completed or corrected. The failure to include any items on such list does not alter the responsibility of the Contractor to complete all work in accordance with the Contract Documents.
- D. Upon receipt of the Contractor's list of items to be completed or corrected, the Architect will promptly make a thorough inspection and prepare a "punch list", setting forth in accurate detail any items on the Contractor's list and additional items that are not acceptable.
- E. Correct all 'punch list' items or shall cause the correction of the "punch list" items within a time frame to be established when the "punch list" is made. Do not exceed the contractual limits for completion of the punch list.

1.06 CLOSEOUT REQUIREMENTS AND SUBMITTALS

- A. Final Inspection:
 1. Submit written certification that:
 - a. Project has been inspected for compliance with Contract Documents and has satisfied the Department of Public Safety.
 - b. Equipment and systems have been tested and are operational and satisfactory.
 - c. Project is completed, and ready for final inspection.
 - d. Provide the required spare/replacement parts as specified within the particular sections.
 2. Inspectional Services Department Use and Occupancy Permit:
 - a. Arrange for a Town of Salem Inspectional Services Department final inspection and secure the signed Certificate of Inspection for Use and Occupancy.

END OF SECTION

SECTION 02 41 19

SELECTIVE DEMOLITION

PART 1 - GENERAL

1.01 GENERAL PROVISIONS

- A. All of the Contract Documents, including the General and Supplementary Conditions and Division 1 General requirements, apply to the work of and are hereby made a part of this Section.
- B. Examine all drawings and all other sections of the specifications for requirements therein affecting the work of this Section whether or not such work is specifically mentioned in this Section.
- C. This section contains information that applies to all work performed under the contract and is hereby made a part of each specification section.

1.02 DESCRIPTION OF WORK

- A. Work Included:
 1. Demolition, removal and disposal of roofing system, metal flashings, caulkings, sealants, fillers and fasters. Refer to Drawing and specifications for additional requirements.
 2. Salvage of existing items to be reused, or turned over to the facility, including but not limited to mechanical equipment and services at the roof.
 3. Removal and legal disposal of demolished materials off site. Except those items specifically designated to be relocated, reused, or turned over to the facility, all existing removed materials, items, trash and debris shall become property of the Contractor and shall be completely removed from the site and legally disposed of at her/his expense. Salvage value belongs to the Owner. On-site sale of materials is not permitted.
 4. Demolition and removal work shall properly prepare for alteration work and new construction to be provided under the Contract.
- B. Items To Be Installed Only: Not Applicable.
- C. Items to be Removed, Stored and Reinstalled Only: Not Applicable
- D. Items To Be Furnished Only: Not Applicable.
- E. Related Work: The following items are not included in this Section and will be performed under the designated Sections:
 1. Section 01 74 19 – WASTE MANAGEMENT AND DISPOSAL:
 - a) Waste management and recycling.

1.03 DEFINITIONS

- A. Remove: Detach items from existing construction and legally dispose of them off-site, unless indicated to be removed and reinstalled.

- B. Remove and Reinstall: Detach items from existing construction, prepare them for reuse, and reinstall them where indicated. Protect from weather until reinstallation.
- C. Existing to Remain: Existing items of construction that are not to be removed and that are not otherwise indicated to be removed, or removed and reinstalled.
- D. Existing to Remain to be Altered: Existing items of construction that are not to be removed but are to be altered in order to accommodate new roof installation.

1.04 SUBMITTALS

- A. Schedule of Selective Demolition Activities: Indicate the following:
 1. Detailed sequence of selective demolition and removal work, with early and late starting and finishing dates for each activity. Ensure User Agency's on-site operations are uninterrupted if applicable.
 2. Interruption of utility services, if any. Indicate how long utility services will be interrupted.
 3. Use of elevator and stairs.
 4. Locations of proposed dust- and noise-control temporary partitions and means of egress, including for other occupants affected by selective demolition operations.
 5. Coordination of User Agency's continuing occupancy of portions of existing building and of User Agency's partial occupancy of completed Work.
 6. Means of protection for items to remain and items in path of waste removal from building.
- B. Landfill Records: Provide trip tickets (receipts) indicating receipt and acceptance of hazardous wastes by a landfill facility licensed to accept hazardous wastes.
 1. Comply with submittal requirements in Section 01 74 19 - WASTE MANAGEMENT AND DISPOSAL.

1.05 QUALITY ASSURANCE

- A. Examination of Existing Conditions: The Contractor shall examine the Contract Drawings for demolition and removal requirements and provisions for new work. Verify all existing conditions and dimensions before commencing work. The Contractor shall visit the site and examine the existing conditions as he finds them and shall inform herself/himself of the character, extent and type of demolition and removal work to be performed. Submit any questions regarding the extent and character of the demolition and removal work in the manner and within the time period established for receipt of such questions during the bidding period.
- B. Pre-demolition Conference: Conduct conference at Project site to comply with requirements in Section 01 11 00 Summary of Work. Review methods and procedures related to selective demolition including, but not limited to, the following:
 1. Inspect and discuss condition of construction to be selectively demolished.
 2. Review and finalize selective demolition schedule and verify availability of materials,

demolition personnel, equipment, and facilities needed to make progress and avoid delays.

3. Review requirements of work performed by other trades that rely on substrates exposed by selective demolition operations.
4. Review areas where existing construction is to remain and requires protection.

1.06 WARRANTY

- A. Existing Warranties: Remove, replace, patch, and repair materials and surfaces cut or damaged during selective demolition, by methods and with materials so as not to void existing warranties.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION

3. 03 EXAMINATION

- A. Verify that utilities have been disconnected and capped.
- B. Survey existing conditions and correlate with requirements indicated to determine extent of selective demolition required.
- C. Inventory and record the condition of items to be removed and reinstalled and items to be removed and salvaged.
- D. When unanticipated mechanical, electrical, or structural elements that conflict with intended function or design are encountered, investigate and measure the nature and extent of conflict. Promptly submit a written report to Designer.
- E. Survey of Existing Conditions: Record existing conditions by use of preconstruction videotapes.
- F. Before selective demolition or removal of existing building elements that will be reproduced or duplicated in final Work, make permanent record of measurements, materials, and construction details required to make exact reproduction.
- G. Perform surveys as the Work progresses to detect hazards resulting from selective demolition activities.

3. 04 PREPARATION

- A. Site Access and Temporary Controls: Conduct selective demolition and debris-removal operations to ensure minimum interference with roads, streets, walks, walkways, and other adjacent occupied and used facilities.
- B. Comply with requirements for access and protection specified in Section 01 11 00 Summary of Work.
- C. Maintain adequate passage to and from all exits at all times. Before any work is done which significantly alters access or egress patterns, consult with the Designer and obtain approval of code required egress. Under no condition block or interfere with the free flow of people at

legally required exits, or in any way alter the required condition of such exits.

- D. Post warning signs and place barricades as applicable during placement and removal of temporary shoring.
- E. Conduct demolition operations to prevent injury to people and damage to adjacent buildings and facilities to remain. Ensure safe passage of people around demolition area(s).
- F. Erect temporary protection, such as walks, fences, railings, canopies, and covered passageways, where required by authorities having jurisdiction. Provide temporary barricades as required to limit access to demolition areas.
- G. Protect existing site improvements, appurtenances, and landscaping to remain.

3.05 SELECTIVE DEMOLITION, GENERAL

A. General: Demolish and remove existing construction only to the extent required by new construction and as indicated. Use methods required to complete the Work within limitations of governing regulations and as follows:

- 1. Neatly cut openings and holes plumb, square, and true to dimensions required. Use cutting methods least likely to damage construction to remain or adjoining construction. Use hand tools or small power tools designed for sawing or grinding, not hammering and chopping, to minimize disturbance of adjacent surfaces. Temporarily cover openings to remain.
- 2. Cut or drill from the exposed or finished side into concealed surfaces to avoid marring existing finished surfaces.
- 3. Maintain adequate ventilation when using cutting torches.
- 4. Remove decayed, vermin-infested, or otherwise dangerous or unsuitable materials and promptly dispose of off-site.
- 5. Locate selective demolition equipment and remove debris and materials so as not to impose excessive loads on supporting walls, floors, or framing.
- 6. Dispose of demolished items and materials promptly. Comply with requirements in Section 01 74 19 - WASTE MANAGEMENT AND DISPOSAL.

B. Removed and Reinstalled Items:

- 1. Clean and repair items to functional condition adequate for intended reuse.
- 2. Reinstall items in locations indicated. Comply with installation requirements for new materials and equipment. Provide connections, supports, and miscellaneous materials necessary to make item functional for use indicated.

C. Existing Items to Remain: Protect construction indicated to remain against damage and

soiling during selective demolition. When permitted by Designer, items may be removed to a suitable, protected storage location during selective demolition and cleaned and reinstalled in their original locations after selective demolition operations are complete.

D. Items for Re-use and Preservation of Existing Surfaces to Remain:

1. The Contractor shall inspect closely each item specifically designated to be relocated, re-used, or turned over to the Owner prior to its removal, and immediately report damages and defects to the Designer.
2. Unless special surface preparation is specified under other Specification Sections, leave existing surfaces that are to remain in a condition suitable to receive new materials and/or finishes.

3. 06 PROTECTION OF PUBLIC AND PROPERTY

- A. Ensure exposed roof, roof edges and other exposed openings or penetrations in the roof are protected from damage, weather or other potential elements that may be detrimental to the safety, security and structural integrity of the building.
- B. Provide all measures required by federal, state and municipal laws, regulations, and ordinances for the protection of surrounding property, the public, workmen, and employees during all demolition and removal operations. Measures are to be taken, but not limited to installation of sidewalks, sheds, barricades, fences, warning lights and signs, trash chutes and temporary lighting.
- C. Protect all walks, roads, streets, curbs, pavements, trees and plantings, on and off premises, and bear all costs for correcting such damage as directed by the Designer.
- D. Demolition shall be performed in such a manner that will insure the safety of adjacent property. Protect adjacent property from damage and protect persons occupying adjacent property from injuries which might occur from falling debris or other cause and so as not to cause interference with the use of other portions of the building, of adjacent buildings or the free access and safe passage to and from the same.
- E. Remove portions of structures with care by using tools and methods that will not transfer heavy shocks to existing and adjacent building structures, both internal and external of the particular work area.
- F. Provide and maintain in proper condition, suitable fire resistive dust barriers around areas where interior demolition and removal work is in progress. Dust barriers shall prevent the dust migration to adjacent areas. Remove dust barriers upon completion of major demolition and removal in the particular work area.

3. 07 DISCOVERY OF HAZARDOUS MATERIALS

- A. If hazardous materials, such as chemicals, asbestos-containing materials, or other hazardous materials are discovered during the course of the work, cease work in affected area only and immediately notify the Designer of such discovery. Do not proceed with work in such areas until instructions are issued by the Designer. Continue work in other areas.

- B. If unmarked containers are discovered during the course of the work, cease work in the affected area only and immediately notify the Designer of such discovery. Do not proceed with work in such areas until instructions are issued by the Designer. Take immediate precautions to prohibit endangering the containers integrity. Continue work in other areas.

3.08 CUTTING

- A. Perform all cutting of existing surfaces in a manner which will ensure a minimal difference between the cut area and new materials when patched.
- B. Provide a flush clean edge where concrete equipment pads, louver removals abut existing surfaces to remain undisturbed.

3.09 DISPOSAL OF DEMOLISHED MATERIALS

- A. General: Comply with requirements of Section 01 74 19 - WASTE MANAGEMENT AND DISPOSAL and the following.
 - 1. Do not allow demolished materials to accumulate on-site.
 - 2. Remove and transport debris in a manner that will prevent spillage on adjacent surfaces and areas.
 - 3. Remove debris from elevated portions of building by chute, hoist, or other device that will convey debris to grade level in a controlled descent.
- B. Burning: Do not burn demolished materials.

3.10 CLEANING

- A. Clean adjacent structures and improvements of dust, dirt, and debris caused by selective demolition operations. Premises shall be left in a clean condition and ready to accept alteration work and new construction.

END OF SECTION

SECTION 06 10 00
ROUGH CARPENTRY

PART 1 - GENERAL

1.01 GENERAL PROVISIONS

- A. All of the Contract Documents, including the General and Supplementary Conditions and Division 1 General requirements, apply to the work of and are hereby made a part of this Section.
- B. Examine all drawings and all other sections of the specifications for requirements therein affecting the work of this Section whether or not such work is specifically mentioned in this Section.
- C. This section contains information that applies to all work performed under the contract and is hereby made a part of each specification section.

1.02 DESCRIPTION OF WORK:

- A. Work Included: Provide all, labor, materials and equipment necessary to complete the work of this Section, including but not limited to the following:
 1. Wood nailers, blocking and sleepers.
 2. Wood furring.
 3. Sheathing.
 4. Concealed blocking, grounds, nailers and equipment curbs.
- B. Related Work: Other specification sections which directly relate to the work of this section include, but are not limited to, the following:
 1. Section 07 53 23 - EDPM Roofing.
 2. Section 07 92 00 – Joint Sealants

1.03 REFERENCES:

- A. The following standards and publications are applicable to the extent referenced in the text. The most recent version of these standards is implied unless otherwise stated.
- B. Lumber Standards: Comply with American Softwood Lumber Standards PS 20 and with applicable rules of the respective grading and inspecting agencies for species and products indicated certified by American Lumber Standard Committees (ALSC) Board of Review.
 1. Northeast Lumber Manufacturer's Association (NELMA): Listed Standards.
 2. Northern Softwood Lumber Bureau (NSLB): Listed Standards.
 3. National Lumber Grades Authority (NLGA): Listed Standards.
 4. American Society for Testing and Materials (ASTM): Listed Standards.
 5. American Wood Preserves Bureau Standards (AWPB): Listed Standards.

6. National Forest Products Association (NFPA), National Design Specifications for Wood Construction (NDS) and NDS Supplement, Design Values for Wood Construction.
- C. Plywood Product Standards: Comply with PS 1 (ANSI A 199.1) or, for products not manufactured under PS 1 provisions, with applicable American Plywood Association APA Performance Standard for type of panel or laminated veneer beam indicated.
- D. AITC 104, Typical Construction Details.

1.04 GRADING REQUIREMENTS:

- A. Grade and Trademark: Shall be required on plywood and each piece of framing and softwood lumber (or bundle in bundled stock). Use only the recognized official marks of the association under whose rules it is graded.
- B. Moisture Content: Moisture content shall not exceed 19% for lumber, 12% for plywood.
- C. Quality: Lumber shall be new; sound; commercially dried and seasoned; well manufactured; and free from bows, twists, crook and wanes that cannot be corrected in the process of bridging or nailing

1.05 INTENT:

- A. A major intent of the work of this section is to provide concealed blocking, grounds, and nailers for all work in this project including, but not limited to, roofing, flashings, sheet metal and the like.

1.06 SUBMITTALS

- A. Provide the following FOR REVIEW in accordance with Section 01 33 00 "SUBMITTALS PROCEDURES":
 - B. Provide the following FOR INFORMATION in accordance with Section 01330 "SUBMITTALS":
 1. Product Data: Submit manufacturer's specifications, product data, installation instructions, use limitations and recommendations for each material used, including, but not limited to, the following materials. Provide certifications stating that materials comply with requirements.
 - a. Manufacturer's data on metal connectors for wood construction.
 - b. Material Certificates: Where dimensional lumber is provided to comply with minimum allowable unit stresses, submit listing of species and grade selection for each use, and submit evidence of compliance with specified requirements. Compliance may be in form of a signed copy of applicable portion of lumber producer's grading rules showing design values for selected species and grade. Design values shall be as approved by the Board of Review of American Lumber Standards Committee.
 2. Treatment Data: For each type of treatment required provide manufacturer's certification stating chemicals and process used, quantities of chemicals retained, conformance with applicable standards, and certification that moisture content after treatment was reduced to maximum specified. Submit treatment manufacturer's

instructions for proper use of each type of treated material including, but not limited to, the following materials.

- a. Pressure Treated: For type specified, include certification by treating plant stating chemicals and process used, net amount of preservative retained and conformance with applicable standards.
- b. For water-borne preservatives, include statement that moisture content of treated materials was reduced to a maximum of 15% prior to shipment to project site.

1.07 STORAGE AND HANDLING:

- A. Store and handle in strict compliance with manufacturer's instructions and recommendations. Protect from moisture and damage. Stack materials to insure ventilation and drainage. Protect lumber from the elements and against dampness during and after delivery. Store all lumber on sleepers, laid flat, under cover in a well-ventilated area.
- B. Sequence deliveries to avoid delays, but minimize onsite storage.

1.08 PROJECT CONDITIONS:

- A. Coordinate work of this section with work of other sections to ensure proper location and attachment of other work. Scribe and trim work to provide accurate fit.

1.09 TESTING AND INSPECTION:

- A. However, such inspection, wherever conducted, shall not relieve the Contractor of his responsibility to furnish materials and workmanship in accordance with Contract requirements, nor shall inspector's acceptance of materials or workmanship prevent later rejection of same by the Owner or Architect if defects are discovered.
- B. The Contractor must set up a quality control program in the shop and in the field to ensure compliance with the Specifications.
- C. Report in writing to the Architect the results of the Contractor's inspection.

PART 2 - PRODUCTS

2.01 LUMBER:

- A. Factory-mark each piece of lumber and plywood with type, grade, mill and grading agency, except omit marking from surfaces to be exposed with transparent finish or without finish.
- B. Nominal sizes are indicated, except as shown by detail dimensions. Provide actual sizes as required by PS 20, for moisture content specified for each use.
 1. Provide dressed lumber S4S, unless otherwise indicated.
 2. Provide seasoned lumber with 15% maximum moisture content at time of dressing.
- C. Miscellaneous Lumber:

1. Provide wood for support or attachment of other work including nails, blocking, furring and similar members. Provide lumber of sizes shown or specified.
2. Provide above ground lumber in contact with roofing, flashing, sheet metal, masonry, concrete, damp proofing and waterproofing that is pressure treated with waterborne preservatives complying with AWPB LP-2 and AWPA C2. Dry lumber to maximum moisture content of 15% after treatment

2.02 PLYWOOD:

- A. OSB will not be accepted for roof, exterior wall, floor sheathing, or exposed locations.
- B. Trademark: Identify each panel with appropriate APA trademark.
- C. Concealed Performance-Rated Plywood: Where panels will be used for the following concealed types of applications, provide APA Performance-Rated Panels complying with requirements indicated for grade designation, span rating, exposure durability classification, edge detail (where applicable) and thickness.
 1. Wall Sheathing: APA-RATED SHEATHING.
 - a. Exposure Durability Classification: Exterior.
 - b. Span Rating: As required to suit stud spacing indicated.
 - c. Panel thickness: 5/8" thick minimum.
 2. Roof membrane flashing substrate: smooth-surfaced exterior grade plywood with exterior grade glue shall be used.
 - a. Minimum ½" thickness
 - b. Marine Grade A-B.

2.03 MISCELLANEOUS MATERIALS:

- A. Fasteners and Anchorages: Provide size, type, material and finish as indicated and as recommended by applicable standards, complying with applicable Federal Specifications for nails, screws, bolts, nuts, washers and anchoring devices. Provide metal hangers and framing anchors of the size and type recommended by the manufacturer for each use including recommended nails.
- B. Wood Nailer: Provide treated wood nailers at the perimeter of the entire roof and around such other roof projections and penetrations as specified on Drawings. Thickness of nailers must match the insulation thickness to achieve a smooth transition. Wood nailers shall be treated for fire and rot resistance and be #2 quality or better lumber.
 1. Wood nailers shall conform to Factory Mutual Loss Prevention Data Sheet 1-49
 2. Note: Wood nailers or wood blocking for snow protection system shall be installed prior to the installation of the roof membrane whenever possible.

2.04 WOOD TREATMENT:

- A. Preservative Treatment shall comply with applicable requirements of AWPA Standards C2 (Lumber) and C9 (Plywood) and of AWPB Standards listed below. Mark each treated item with the AWPB Quality Mark Requirements.

1. Pressure treat above-ground items with water-borne preservatives complying with AWPB Lp-2, LP-3, LP-4 and LP-5. After treatment, kiln-dry to a maximum moisture content of 15%. Treat indicated items and the following:
 - a. Nailers, curbs, blocking, stripping, and similar members in connection with roofing, flashing, vapor barriers and waterproofing.
 - b. Wood sills, blocking, furring, stripping and similar concealed members in contact with masonry or concrete.
 - c. Wood framing members less than 8" above grade.
2. Complete fabrication of treated items prior to treatment, where possible. If cut after treatment, coat cut surfaces with heavy brush coat of same chemical used for treatment. Inspect each piece of lumber or plywood after drying and discard damaged or defective pieces.

PART 3 - EXECUTION

3.01 INSPECTION:

- A. The Installer/Erector shall examine substrates, supports and conditions under which this work is to be performed and notify Contractor, in writing, of conditions detrimental to the proper completion of the work. Do not proceed with work until unsatisfactory conditions are corrected. Beginning work means installer accepts substrates and conditions.

3.02 INSTALLATION / ERECTION:

A. General:

1. Strictly comply with referenced standards, except where more restrictive requirements are specified in this section. Choose pieces carefully to eliminate split, warped and twisted members.
2. Discard units of material with defects which might impair quality of work, and units which are too small to fabricate work with minimum joints or optimum joint arrangement.
3. Securely attach carpentry work to substrate and structure by anchoring and fastening as shown and as required by state building code. Ensure that blocking is capable of supporting applied work and loadings. Countersink bolts, nail heads and other fasteners flush with face of wood on exposed carpentry work and fill holes.
4. Use common wire nails, except as otherwise indicated. Use finishing nails for finish work. Select fasteners of size that will not penetrate members where opposite side will be exposed to view or will receive finish materials. Make tight connections between members. Install fasteners without splitting of wood; pre-drill as required.
5. Saturate cut ends of treated wood with same chemicals used for original treatment.

B. Wood Grounds, Nailers and Blocking:

1. Provide wherever shown and where required for screeding or attachment of other work. Form to shapes as shown and cut as required for true line and level of work to be attached. Coordinate location with other work involved.
2. Attach to substrates as required to support applied loading. Countersink bolts and nuts flush with surfaces, unless otherwise shown. Build into masonry during installation of masonry work. Where possible, anchor to formwork before concrete placement.

Use only approved fasteners for attachment of nailers to tectum roof deck that meet or exceed pull-out data in section 075323 EDPM ROOFING.

C. Wood Furring:

1. Install plumb and level with closure strips at edges and openings. Shim with wood as required for tolerances of finished work.

D. Wood Framing, General:

1. Provide framing members of sizes and on spacings shown, and frame openings as shown, or if not shown, comply with recommendations of Manual for House Framing at the National Forest Products Association. Do not splice structural members between supports.
2. Anchor and nail as shown and to comply with Recommended Nailing Schedule as indicated.
3. Firestop concealed spaces with wood blocking not less than 2" thick, if not blocked by other framing members. Provide blocking at each building story level and at ends of joist spans.

E. Maintain premises in neat, safe and orderly condition during execution of work.

END OF SECTION

SECTION 075323

EPDM ROOFING

PART 1 - GENERAL

1.1 GENERAL PROVISIONS

A. Attention is directed to the CONTRACT AND GENERAL CONDITIONS and all Sections within DIVISION 01 - GENERAL REQUIREMENTS which are hereby made a part of this Section of the Specifications.

1.2 DESCRIPTION OF WORK

A. Work Included: Provide labor, materials and equipment necessary to complete the work of this Section, including but not limited to the following:

1. Adhered membrane-roofing system.
2. Cover board.
3. Roof insulation.
4. Vapor retarder.
5. Flashing for equipment mounted on roofing and roofing penetrations.

B. Related Work: The following items are not included in this Section and will be performed under the designated Sections:

1. Section 061000 - ROUGH CARPENTRY for wood nailers, curbs, and blocking.
2. Section 076200 - SHEET METAL FLASHING AND TRIM for metal roof penetration flashings, flashings, and counterflashings.
3. Section 079200 - JOINT SEALANTS for sealants.

1.3 DEFINITIONS

A. Roofing Terminology: Refer to ASTM D 1079 and glossary of NRCA's "The NRCA Roofing and Waterproofing Manual" for definition of terms related to roofing work in this Section.

1.4 PERFORMANCE REQUIREMENTS

A. General: Provide installed roofing membrane and base flashings that remain watertight; do not permit the passage of water; and resist specified uplift pressures, thermally induced movement, and exposure to weather without failure.

- B. Material Compatibility: Provide roofing materials that are compatible with one another under conditions of service and application required, as demonstrated by roofing manufacturer based on testing and field experience.
- C. Roofing System Design: Roofing system shall be designed to withstand Code required loads and wind speeds.
- D. Flashings: Provide base flashings, perimeter flashings, detail flashings and component materials that comply with requirements and recommendations in NRCA Roofing and Waterproofing Manual (Fourth Edition) for Construction Details and SMACNA Architectural Sheet Metal Manual (Fifth Edition) for Construction Details, as applicable.

1.5 SUBMITTALS

- A. Product Data: For each type of product indicated.
- B. Shop Drawings: For roofing system. Include plans, elevations, sections, details, and attachments to other Work.
 - 1. Base flashings and membrane terminations.
 - 2. Tapered insulation, including slopes.
 - 3. Insulation fastening patterns.
- C. Installer Certificates: Signed by roofing system manufacturer certifying that Installer is approved, authorized, or licensed by manufacturer to install roofing system.
- D. Qualification Data: For Installer and manufacturer.
- E. Design Letter: Roofing system manufacturer's Design Acceptance Letter identifying components, warranty and wind speed.
- F. Maintenance Data: For roofing system to include in maintenance manuals.
- G. Inspection Report: Copy of roofing system manufacturer's inspection report of completed roofing installation.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Deliver roofing materials to Project site in original containers with seals unbroken and labeled with manufacturer's name, product brand name and type, date of manufacture, and directions for storing and mixing with other components.
- B. Store liquid materials in their original undamaged containers in a clean, dry, protected location and within the temperature range required by roofing system manufacturer. Protect stored liquid material from direct sunlight.

1. Discard and legally dispose of liquid material that cannot be applied within its stated shelf life.
- C. Protect roof insulation materials from physical damage and from deterioration by sunlight, moisture, soiling, and other sources. Store in a dry location. Comply with insulation manufacturer's written instructions for handling, storing, and protecting during installation.
- D. Handle and store roofing materials and place equipment in a manner to avoid permanent deflection of deck.

1.7 PROJECT CONDITIONS

- A. Weather Limitations: Proceed with installation only when existing and forecasted weather conditions permit roofing system to be installed according to manufacturer's written instructions and warranty requirements.

1.8 WARRANTY

- A. Roofing Contractor's Warranty: The roofing subcontractor shall supply User Agency with a minimum two-year workmanship warranty for each roof, starting from the date of Certificate of Agency Use and Occupancy. In the event any work related to the roofing, flashing, or metalwork is found to be defective within two years from the date of Certificate of Agency Use and Occupancy, the roofing contractor shall remove and replace such at no additional cost to the Town. The roofing subcontractor's warranty obligation shall run directly to the building owner and a copy the roofing signed warranty shall be sent to the roofing system's manufacturer.
 1. The duration of the Roofing Contractor's two-year warranty shall run concurrent with the roofing system's manufacturer's 20-year warranty.
- B. Roofing Systems Manufacturer's Warranty: The roofing manufacturer shall guarantee roof areas to be in a watertight condition, for a period of 20 years, starting from the date of Certificate of Agency Use and Occupancy. Guarantees or warranties that start at the date of shipment from the factory, or from the completion date of an individual portion of the project, are not acceptable. The warranty shall be a 20-year no dollar limit (NDL), non-prorated total system labor and material warranty, for wind speeds up to (110) miles per hour. Total system warranty shall include all roofing materials, related components and accessories including, but not limited to the substrate board, vapor retarder, insulation board, cover board, roofing membrane, membrane flashings, fasteners, adhesives, metal roof copings, metal roof edges and termination metals and roof drain assemblies. The manufacturer shall repair defects in materials and workmanship as promptly after observation as weather and site conditions permit.

PART 2 - PRODUCTS

2.1 EPDM ROOFING MEMBRANE

- A. EPDM Roofing Membrane: ASTM D 4637, Type I, nonreinforced uniform, flexible sheet made from EPDM, and as follows:
 - 1. Available Products: Subject to compliance with requirements, products that may be incorporated into the Work include, but are not limited to, the following:
 - a. Carlisle Coatings & Waterproofing Inc.
 - b. Firestone Building Products Company.
 - c. Or equal.
 - 2. Thickness: 60 mils (1.5 mm) nominal.
 - 3. Exposed Face Color: White

2.2 AUXILIARY MATERIALS

- A. General: Auxiliary materials recommended by roofing system manufacturer for intended use and compatible with membrane roofing.
 - 1. Liquid-type auxiliary materials shall meet VOC limits of authorities having jurisdiction.
- B. Sheet Flashing: 60-mil-thick EPDM, partially cured or cured, according to application.
- C. Epichlorohydrin Sheet at Areas Requiring Grease Resistance: 60-mil-thick, unreinforced flexible sheet with the following typical properties as determined per ASTM test method indicated:
 - 1. Tensile Strength: 1500 psi; ASTM D 412.
 - 2. Ultimate Elongation: 200 percent; ASTM D 412.
 - 3. Tear Resistance: 150 lbf/in; ASTM D 412.
 - 4. Brittleness Temperature: Minus 20 degrees F ASTM D 746.
 - 5. Resistance to Ozone Aging: No cracks after 168 hours' exposure of 50 percent elongated sample at 104 degrees F and 100-pphm ozone; ASTM D 1149.
 - 6. Resistance to Oil Aging: 15 percent maximum mass change after 168 hours' immersion in diesel fuel No. 2 at 158 degrees F; ASTM D 471.
- D. Bonding Adhesive: Manufacturer's standard bonding adhesive.
- E. Seaming Material: Manufacturer's standard synthetic-rubber polymer primer and 3-inch-wide minimum with cover strip or 6-inch-wide, butyl splice tape with release film.
- F. Lap Sealant: Manufacturer's standard single-component sealant, color to match roofing membrane.

- G. Water Cutoff Mastic: Manufacturer's standard butyl mastic sealant.
- H. Metal Termination Bars: Manufacturer's standard predrilled stainless steel or aluminum bars, approximately 1 by 1/8 inch thick; with anchors.
- I. Fasteners: Factory-coated steel fasteners and metal or plastic plates meeting corrosion-resistance provisions in FMG 4470, designed for fastening membrane to substrate, and acceptable to membrane roofing system manufacturer.
- J. Miscellaneous Accessories: Provide pourable sealers, preformed cone and vent sheet flashings, preformed inside and outside corner sheet flashings, T-joint covers, in-seam sealants, termination reglets, cover strips, and other accessories.

2.3 VAPOR RETARDER

- A. Self-Adhering Sheet Vapor Retarder: ASTM D 1970, minimum 40-mil- thick film laminated to layer of rubberized asphalt adhesive; maximum permeance rating of 0.1 perm; cold-applied, with slip-resisting surface and release paper backing. Provide primer when recommended by vapor-retarder manufacturer.
- B. Vapor Retarder: Minimum 10 mil polyethylene sheet with maximum permeance rating of 0.10 perm.
 - 1. Tape: Pressure-sensitive tape of type recommended by vapor-retarder manufacturer for sealing joints and penetrations in vapor retarder.

2.4 ROOF INSULATION

- A. General: Provide preformed roof insulation boards that comply with requirements and referenced standards, selected from manufacturer's standard sizes and of thicknesses indicated.
 - 1. For thickness over 3 inches, install in two layers.
- B. Extruded-Polystyrene Board Insulation: ASTM C 578, Type IV, 1.6-lb/cu. ft. minimum density, square edged.
 - 1. Available Products: Subject to compliance with requirements, products that may be incorporated into the Work include, but are not limited to, the following:
 - a. DiversiFoam Products.
 - b. Dow Chemical Company.
 - c. Pactiv/Greenguard
 - d. Owens Corning.
 - e. Or equal.

- C. Polyisocyanurate Board Insulation: ASTM C 1289, Type II, Grade 2 (20 psi) or Grade 3 (25 psi) felt or glass-fiber mat facer on both major surfaces.
 - 1. Available Products: Subject to compliance with requirements, products that may be incorporated into the Work include, but are not limited to, the following:
 - a. Atlas Roofing Corporation.
 - b. Carlisle SynTec Incorporated.
 - c. Firestone Building Products Company.
 - d. GAF Materials Corp.
 - e. Johns Manville International Inc.
 - f. Or equal.
- D. Tapered Insulation: Provide factory-tapered insulation boards fabricated to slope of 1/4 inch per 12 inches unless otherwise indicated.
- E. Provide preformed saddles, crickets, tapered edge strips, and other insulation shapes where indicated for sloping to drain. Fabricate to slopes indicated.

2.5 INSULATION ACCESSORIES

- A. General: Furnish roof insulation accessories recommended by insulation manufacturer for intended use and compatible with membrane roofing.
- B. Fasteners: Factory-coated steel fasteners and metal or plastic plates meeting corrosion-resistance provisions in FMG 4470, designed for fastening roof insulation to substrate, and acceptable to roofing system manufacturer.
- C. Cold Fluid-Applied Adhesive: Manufacturer's standard cold fluid-applied adhesive formulated to adhere roof insulation to substrate.
- D. Cover Board: ASTM C 1177/C 1177M, glass-mat, water-resistant gypsum substrate, 1/2 inch thick.

2.6 WALKWAYS

- A. Flexible Walkways: Factory-formed, nonporous, heavy-duty, solid-rubber, slip-resisting, surface-textured walkway pads or rolls approximately 3/16 inch thick, and acceptable to membrane roofing system manufacturer.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, areas, and conditions, with Installer present, for compliance with the following requirements and other conditions affecting performance of roofing system:
 1. Verify that roof openings and penetrations are in place and set and braced and that roof drains are securely clamped in place.
 2. Verify that wood blocking, curbs, and nailers are securely anchored to roof deck at penetrations and terminations and that nailers match thicknesses of insulation.
 3. Verify that minimum concrete drying period recommended by roofing system manufacturer has passed.
 4. Verify that concrete substrate is visibly dry and free of moisture. Test for capillary moisture by plastic sheet method according to ASTM D 4263.
 5. Verify that concrete curing compounds that will impair adhesion of roofing components to roof deck have been removed.
 6. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Clean substrate of dust, debris, moisture, and other substances detrimental to roofing installation according to roofing system manufacturer's written instructions. Remove sharp projections.
- B. Prevent materials from entering and clogging roof drains and conductors and from spilling or migrating onto surfaces of other construction. Remove roof-drain plugs when no work is taking place or when rain is forecast.
- C. Complete terminations and base flashings and provide temporary seals to prevent water from entering completed sections of roofing system at the end of the workday or when rain is forecast. Remove and discard temporary seals before beginning work on adjoining roofing.

3.3 VAPOR-RETARDER INSTALLATION

- A. Self-Adhering Sheet Vapor Retarder: Prime substrate if required by manufacturer. Install self-adhering sheet vapor retarder over area to receive vapor retarder, side, and end lapping each sheet a minimum of 3-1/2 inches and 6 inches, respectively. Seal laps by rolling.
- B. Polyethylene Film Vapor Retarder: Loosely lay polyethylene-film vapor retarder over area to receive vapor retarder, side, and end lapping each sheet a minimum of 2 inches and 6 inches, respectively. Continuously seal side and end laps with tape.
- C. Completely seal vapor retarder at side laps, end laps, terminations, obstructions, and penetrations to prevent air movement into roofing system.

3.4 INSULATION AND COVERBOARD INSTALLATION

- A. Coordinate installing membrane roofing system components so insulation is not exposed to precipitation or left exposed at the end of the workday.
- B. Comply with membrane roofing system manufacturer's written instructions for installing roof insulation.
- C. Install tapered insulation under area of roofing to conform to slopes indicated.
- D. Install one or more layers of insulation under area of roofing to achieve required thickness. Install 2 or more layers with joints of each succeeding layer staggered from joints of previous layer a minimum of 6 inches in each direction.
- E. Trim surface of insulation where necessary at roof drains so completed surface is flush and does not restrict flow of water.
- F. Install insulation with long joints of insulation in a continuous straight line with end joints staggered between rows, abutting edges and ends between boards. Fill gaps exceeding 1/4 inch with insulation.
 - 1. Cut and fit insulation within 1/4 inch of nailers, projections, and penetrations.
- G. Mechanically Fastened Insulation and Coverboard: Install each layer of insulation and coverboard and secure to deck using mechanical fasteners specifically designed and sized for fastening specified board-type roof insulation to deck type.
 - 1. Fasten insulation to resist uplift pressure at corners, perimeter, and field of roof.

3.5 ADHERED ROOFING MEMBRANE INSTALLATION

- A. Install roofing membrane over area to receive roofing according to membrane roofing system manufacturer's written instructions. Unroll roofing membrane and allow to relax before installing.
- B. Start installation of roofing membrane in presence of membrane roofing system manufacturer's technical personnel.
- C. Accurately align roofing membrane and maintain uniform side and end laps of minimum dimensions required by manufacturer. Stagger end laps.
- D. Bonding Adhesive: Apply bonding adhesive to substrate and underside of roofing membrane at rate required by manufacturer and allow to partially dry before installing roofing membrane. Do not apply bonding adhesive to splice area of roofing membrane.

- E. Mechanically or adhesively fasten roofing membrane securely at terminations, penetrations, and perimeter of roofing.
- F. Apply roofing membrane with side laps shingled with slope of roof deck where possible.
- G. Tape Seam Installation: Clean and prime both faces of splice areas, apply splice tape, and firmly roll side and end laps of overlapping roofing membranes according to manufacturer's written instructions to ensure a watertight seam installation. Apply lap sealant and seal exposed edges of roofing membrane terminations as required by roofing manufacturer.
- H. Repair tears, voids, and lapped seams in roofing that does not meet requirements.
- I. Spread sealant or mastic bed over deck drain flange at deck drains and securely seal roofing membrane in place with clamping ring.
- J. Apply epichlorohydrin sheet over roofing membrane at locations indicated.

3.6 BASE FLASHING INSTALLATION

- A. Install sheet flashings and preformed flashing accessories and adhere to substrates according to membrane roofing system manufacturer's written instructions.
- B. Apply bonding adhesive to substrate and underside of sheet flashing at required rate and allow to partially dry. Do not apply bonding adhesive to seam area of flashing.
- C. Flash penetrations and field-formed inside and outside corners with cured or uncured sheet flashing.
- D. Clean splice areas, apply splicing cement, and firmly roll side and end laps of overlapping sheets to ensure a watertight seam installation. Apply lap sealant and seal exposed edges of sheet flashing terminations.
- E. Terminate and seal top of sheet flashings.

3.7 WALKWAY INSTALLATION

- A. Flexible Walkways: Install walkway products in locations indicated. Adhere walkway products to substrate with compatible adhesive according to roofing system manufacturer's written instructions. Provide 400 LF of walkway material, locate around mechanical equipment as directed by the Architect.

3.8 PROTECTING AND CLEANING

- A. Protect membrane-roofing system from damage and wear during remainder of construction period. When remaining construction will not affect or endanger roofing, inspect roofing for

deterioration and damage, describing its nature and extent in a written report, with copies to Designer.

- B. Correct deficiencies in or remove membrane-roofing system that does not comply with requirements, repair substrates, and repair or reinstall membrane-roofing system to a condition free of damage and deterioration at time of Substantial Completion and according to warranty requirements.
- C. Clean overspray and spillage from adjacent construction using cleaning agents and procedures recommended by manufacturer of affected construction.

END OF SECTION

SECTION 07 62 00

SHEET METAL FLASHING AND TRIM

PART 1 - GENERAL

1.1 GENERAL PROVISIONS

A. Attention is directed to the CONTRACT AND GENERAL CONDITIONS and all Sections within DIVISION 01 - GENERAL REQUIREMENTS which are hereby made a part of this Section of the Specifications.

1.2 DESCRIPTION OF WORK

A. Work Included: Provide labor, materials and equipment necessary to complete the work of this Section, including but not limited to the following:

1. Sheet metal flashing and trim for the following applications:
 - a. Through-wall flashing.
 - b. Formed wall flashing and trim.
 - c. Formed low-slope roof flashing and trim.

B. Related Work: The following items are not included in this Section and will be performed under the designated Sections:

1. Section 061000 - ROUGH CARPENTRY for wood nailers, curbs, and blocking.
2. Section 075323 - EPDM ROOFING for installing sheet metal flashing and trim integral with roofing membrane.

1.3 PERFORMANCE REQUIREMENTS

A. General: Install sheet metal flashing and trim to provide a weathertight condition and to withstand wind loads, structural movement, thermally induced movement, and exposure to weather without failing, rattling, leaking, warping, waving, buckling, fastener distortion, and fastener disengagement.

B. Fabricate and install roof edge flashing and copings capable of resisting the Wind Zone forces required by Code.

C. Thermal Movements: Provide sheet metal flashing and trim that allow for thermal movements resulting from the following maximum change (range) in ambient and surface temperatures by preventing buckling, opening of joints, hole elongation, overstressing of components, failure of joint sealants, failure of connections, and other detrimental effects. Provide clips that resist rotation and avoid shear stress as a result of sheet metal and trim thermal movements. Base

engineering calculation on surface temperatures of materials due to both solar heat gain and nighttime-sky heat loss.

1. Temperature Change (Range): 120 degrees F, ambient; 180 degrees F material surfaces.
- D. Water Infiltration: Provide sheet metal flashing and trim that do not allow water infiltration to building interior or interior side of flashing.

1.4 SUBMITTALS

- A. Product Data: For each type of product indicated. Include construction details, material descriptions, dimensions of individual components and profiles, and finishes.
- B. Shop Drawings: Show layouts of sheet metal flashing and trim, including plans and elevations. Distinguish between shop- and field-assembled work. Include the following:
 1. Identify material, thickness, weight, finish and color for each item and location in Project.
 2. Details for forming sheet metal flashing and trim, including profiles, shapes, seams, and dimensions.
 3. Details for fastening, joining, supporting, and anchoring sheet metal flashing and trim, including fasteners, clips, cleats, and attachments to adjoining work.
 4. Details of expansion joints and expansion-joint covers, including showing direction of expansion and contraction.
- C. Samples for Verification: For each type of exposed finish required, prepared on Samples of size indicated below:
 1. Sheet Metal Flashing: 12 inches long. Include fasteners, cleats, clips, closures, and other attachments.
 2. Trim: 12 inches long. Include fasteners and other exposed accessories.
 3. Accessories: Full-size Sample.

1.5 QUALITY ASSURANCE

- A. Sheet Metal Flashing and Trim Standard: Comply with SMACNA's "Architectural Sheet Metal Manual." Conform to dimensions and profiles shown unless more stringent requirements are indicated.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Deliver sheet metal flashing materials and fabrications undamaged. Protect sheet metal flashing and trim materials and fabrications during transportation and handling.
- B. Unload and inspect materials for damage, dampness, and wet-storage stains upon delivery to the site. Do not accept materials with any of these defects., Handle, store, and install sheet

metal flashing materials and fabrications in a manner to prevent bending, warping, twisting, and surface damage of the materials.

C. Stack materials on platforms or pallets, covered with suitable weathertight and ventilated covering, and sloped to shed water. Do not store sheet metal flashing and trim materials in contact with other materials that might cause corrosion, staining, denting, or other surface damage.

1.7 COORDINATION

A. Coordinate installation of sheet metal flashing and trim with interfacing and adjoining construction to provide a leakproof, secure, and noncorrosive installation. Coordinate with other trades to allow for timely progress of construction.

B. The sheet metal mechanic is responsible for cutting, fitting, drilling, and other operations in connection with sheet metal required to accommodate the work of other trades.

PART 2 - PRODUCTS

2.1 SHEET METALS

A. Aluminum Sheet: ASTM B 209, Alloy 3003, 3004, 3105, or 5005. Thickness as specified in this Section. Temper suitable for forming and structural performance required, but not less than H14, finished as follows:

1. High-Performance Organic Finish: AA-C12C42R1x (Chemical Finish: cleaned with inhibited chemicals; Chemical Finish: acid-chromate-fluoride-phosphate conversion coating; Organic Coating: as specified below). Prepare, pretreat, and apply coating to exposed metal surfaces to comply with coating and resin manufacturers' written instructions.
 - a. Fluoropolymer 3-Coat System: Manufacturer's standard 3-coat, thermocured system consisting of specially formulated inhibitive primer, fluoropolymer color coat, and clear fluoropolymer topcoat, with both color coat and clear topcoat containing not less than 70 percent polyvinylidene fluoride resin by weight, with a minimum total dry film thickness of 1.5 mil; complying with AAMA 2605.
 - 1) Color and Gloss: As selected by Designer from manufacturer's full range, including metallics.

B. Stainless-Steel Sheet: ASTM A 240/A 240M, Type 304, with No. 2D dull, cold rolled finish. Thickness as specified in this Section.

2.2 MISCELLANEOUS MATERIALS

- A. General: Provide materials and types of fasteners, solder, welding rods, protective coatings, separators, sealants, and other miscellaneous items as required for complete sheet metal flashing and trim installation.
- B. Fasteners: Wood screws, annular threaded nails, self-tapping screws, self-locking rivets and bolts, and other suitable fasteners designed to withstand design loads. Fasteners should be of the same metal or a metal compatible with the item fastened. Use stainless steel fasteners to fasten dissimilar materials.
 - 1. Exposed Fasteners: Heads matching color of sheet metal by means of plastic caps or factory-applied coating.
 - 2. Fasteners for Flashing and Trim: Blind fasteners or self-drilling screws, gasketed, with hex washer head.
 - 3. Blind Fasteners: High-strength aluminum or stainless-steel rivets.
- C. Solder for Stainless Steel: ASTM B 32, Grade Sn60, with acid flux of type recommended by stainless-steel sheet manufacturer.
- D. Sealing Tape: Pressure-sensitive, 100 percent solids, polyisobutylene compound sealing tape with release-paper backing. Provide permanently elastic, nonsag, nontoxic, nonstaining tape.
- E. Elastomeric Sealant: ASTM C 920, elastomeric polyurethane polymer sealant; of type, grade, class, and use classifications required to seal joints in sheet metal flashing and trim and remain watertight.
- F. Epoxy Seam Sealer: Two-part, noncorrosive, aluminum seam-cementing compound, recommended by aluminum manufacturer for exterior nonmoving joints, including riveted joints.
- G. Isolation Coating: ASTM D 1187, cold-applied asphalt emulsion, VOC compliant, compounded for 15-mil dry film thickness per coat. Provide inert-type noncorrosive compound free of asbestos fibers, sulfur components, and other deleterious impurities.
- H. Asphalt Roofing Cement: ASTM D 4586, asbestos free, of consistency required for application.

2.3 FABRICATION, GENERAL

- A. General: Custom fabricate sheet metal flashing and trim to comply with recommendations in SMACNA's "Architectural Sheet Metal Manual" that apply to design, dimensions, metal, and other characteristics of item indicated. Shop fabricate items where practicable. Obtain field measurements for accurate fit before shop fabrication.
- B. Fabricate sheet metal flashing and trim in thickness or weight needed to comply with performance requirements, but not less than that specified for each application and metal.

- C. Fabricate sheet metal flashing and trim without excessive oil canning, buckling, and tool marks and true to line and levels indicated, with exposed edges folded back to form hems.
 - 1. Seams for Aluminum: Fabricate nonmoving seams with flat-lock seams. Form seams and seal with epoxy seam sealer. Rivet joints for additional strength.
 - 2. Seams for Other Than Aluminum: Fabricate nonmoving seams in accessories with flat-lock seams. Tin edges to be seamed, form seams, and solder.
- D. Sealed Joints: Form nonexpansion but movable joints in metal to accommodate elastomeric sealant to comply with SMACNA recommendations.
- E. Expansion Provisions: Where lapped or bayonet-type expansion provisions in the Work cannot be used, form expansion joints of intermeshing hooked flanges, not less than 1 inch deep, filled with elastomeric sealant concealed within joints.
- F. Conceal fasteners and expansion provisions where possible on exposed-to-view sheet metal flashing and trim, unless otherwise indicated.
- G. Fabricate cleats and attachment devices from same material as accessory being anchored or from compatible, noncorrosive metal.
 - 1. Thickness: As recommended by SMACNA's "Architectural Sheet Metal Manual" for application but not less than thickness of metal being secured.

2.4 LOW-SLOPE ROOF SHEET METAL FABRICATIONS

- A. Roof Edge Flashing and Fascia Caps: Fabricate in minimum 96-inch-long, but not exceeding 10-foot-long, sections. Furnish with 6-inch-wide joint cover plates.
 - 1. Joint Style: Butt, with 12-inch-wide concealed backup plate.
 - 2. Fabricate scuppers from the following material:
 - a. Aluminum: 0.050 inch thick.
- B. Copings: Fabricate in minimum 96-inch-long, but not exceeding 10-foot-long, sections. Fabricate joint plates of same thickness as copings. Furnish with continuous cleats to support edge of external leg and drill elongated holes for fasteners on interior leg. Miter corners, seal, and solder or weld watertight.
 - 1. Joint Style: Butt, with 12-inch-wide concealed backup plate.
 - 2. Fabricate copings from the following material:
 - a. Aluminum: 0.050 inch thick.
- C. Base Flashing: Fabricate from the following material:
 - 1. Stainless Steel: 0.0187 inch thick.
- D. Counterflashing: Fabricate from the following material:

1. Stainless Steel: 0.0187 inch thick.
- E. Roof-Penetration Flashing: Fabricate from the following material:
 1. Stainless Steel: 0.0187 inch thick.
- F. Splash Pans: Fabricate from the following material:
 1. Stainless Steel: 0.0187 inch thick.
- G. Roof-Drain Flashing: Fabricate from the following material:
 1. Stainless Steel: 0.0156 inch thick.

2.5 WALL SHEET METAL FABRICATIONS

- A. Through-Wall Flashing: Fabricate continuous flashings in minimum 96-inch-long, but not exceeding 12 foot long, sections, under copings, at shelf angles, and where indicated. Fabricate discontinuous lintel, sill, and similar flashings to extend 6 inches beyond each side of wall openings. Form with 2-inch-high end dams. Fabricate from the following material:
 1. Stainless Steel: 0.0156 inch thick.

2.6 FINISHES

- A. Comply with NAAMM's "Metal Finishes Manual for Architectural and Metal Products" for recommendations for applying and designating finishes.
- B. Protect mechanical and painted finishes on exposed surfaces from damage by applying a strippable, temporary protective covering before shipping.
- C. Appearance of Finished Work: Variations in appearance of abutting or adjacent pieces are acceptable if they are within one-half of the range of approved Samples. Noticeable variations in the same piece are not acceptable. Variations in appearance of other components are acceptable if they are within the range of approved Samples and are assembled or installed to minimize contrast.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, areas, and conditions, with Installer present, to verify actual locations, dimensions and other conditions affecting performance of work.
 1. Verify that substrate is sound, dry, smooth, clean, sloped for drainage, and securely anchored.

2. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION, GENERAL

- A. General: Anchor sheet metal flashing and trim and other components of the Work securely in place, with provisions for thermal and structural movement. Use fasteners, solder, welding rods, protective coatings, separators, sealants, and other miscellaneous items as required to complete sheet metal flashing and trim system.
 1. Torch cutting of sheet metal flashing and trim is not permitted.
- B. Metal Protection: Where dissimilar metals will contact each other or corrosive substrates, protect against galvanic action by painting contact surfaces with isolation coating or by other permanent separation as recommended by fabricator or manufacturers of dissimilar metals.
 1. Coat side of stainless-steel sheet metal flashing and trim with bituminous coating where flashing and trim will contact wood, ferrous metal, or cementitious construction.
 2. Underlayment: Where installing metal flashing directly on cementitious or wood substrates, install a course of felt underlayment and cover with a slip-sheet or install a course of polyethylene underlayment.
 3. Bed flanges in thick coat of asphalt roofing cement where required for waterproof performance.
- C. Install exposed sheet metal flashing and trim without excessive oil canning, buckling, and tool marks. Fold back the exposed edges neatly to form a 1/2 inch hem on the concealed side.
- D. Install sheet metal flashing and trim true to line and levels indicated. Provide uniform, neat seams with minimum exposure of solder, welds, and elastomeric sealant. Seams shall be uniform in width and height.
- E. Install sheet metal flashing and trim to fit substrates and to result in watertight performance. Verify shapes and dimensions of surfaces to be covered before fabricating sheet metal.
 1. Space cleats not more than 12 inches apart. Anchor each cleat with two fasteners. Bend tabs over fasteners.
- F. Expansion Provisions: Provide for thermal expansion of exposed flashing and trim. Space movement joints at a maximum of 10 feet with no joints allowed within 24 inches of corner or intersection. Where lapped or bayonet-type expansion provisions cannot be used or would not be sufficiently watertight, form expansion joints of intermeshing hooked flanges, not less than 1 inch deep, filled with elastomeric sealant concealed within joints.
- G. Fasteners: Use fasteners of sizes that will penetrate substrate not less than 1-1/4 inches for nails and not less than 3/4 inch for wood screws.
 1. Galvanized or Prepainted, Metallic-Coated Steel: Use stainless-steel fasteners.
 2. Aluminum: Use aluminum or stainless steel fasteners.
 3. Stainless Steel: Use stainless-steel fasteners.

- H. Seal joints with elastomeric sealant as required for watertight construction.
 - 1. Where sealant-filled joints are used, embed hooked flanges of joint members not less than 1 inch into sealant. Form joints to completely conceal sealant. When ambient temperature at time of installation is moderate, between 40 and 70 degrees F set joint members for 50 percent movement either way. Adjust setting proportionately for installation at higher ambient temperatures. Do not install sealant-type joints at temperatures below 40 degrees F.
 - 2. Prepare joints and apply sealants to comply with requirements in Section 079200 - JOINT SEALANTS.
- I. Soldered Joints: Clean surfaces to be soldered, removing oils and foreign matter. Pretin edges of sheets to be soldered to a width of 1-1/2 inches except where pretinned surface would show in finished Work.
 - 1. Do not solder aluminum sheet.
 - 2. Stainless-Steel Soldering: Pretin edges of uncoated sheets to be soldered using solder recommended for stainless steel and phosphoric acid flux. Promptly wash off acid flux residue from metal after soldering.
 - 3. Do not use open-flame torches for soldering. Heat surfaces to receive solder and flow solder into joints. Fill joints completely. Completely remove flux and spatter from exposed surfaces.
- J. Aluminum Flashing: Rivet or weld joints in uncoated aluminum where necessary for strength. Do not allow aluminum surfaces in direct contact with other metals except stainless steel, zinc, or zinc coating. Where aluminum contacts another metal, paint the dissimilar metal with a primer followed by two coats of aluminum paint. Where drainage from a dissimilar metal passes over aluminum, paint the dissimilar metal with a non-lead pigment paint.

3.3 ROOF FLASHING INSTALLATION

- A. General: Install sheet metal roof flashing and trim to comply with performance requirements[, sheet metal manufacturer's written installation instructions,] and SMACNA's "Architectural Sheet Metal Manual." Provide concealed fasteners where possible, set units true to line, and level as indicated. Install work with laps, joints, and seams that will be permanently watertight.
- B. Pipe or Post Counterflashing: Install counterflashing umbrella with close-fitting collar with top edge flared for elastomeric sealant, extending a minimum of 4 inches over base flashing. Install stainless steel draw band and tighten.
- C. Counterflashing: Factory form counterflashing to provide spring action against the base flashing. Coordinate installation of counterflashing with installation of base flashing. Insert counterflashing in reglets or receivers and fit tightly to base flashing. Unless indicated otherwise, insert counterflashing in reglets located 9 to 10 inches above the roof surface and secure at least every 18 inches. Extend counterflashing 4 inches over base flashing. Lap

counterflashing joints a minimum of 4 inches and bed with elastomeric sealant. Fold the exposed edges of counterflashings 1/2 inch.

1. Secure in a waterproof manner by means of snap-in installation and sealant.
- D. Roof-Penetration Flashing: Coordinate installation of roof-penetration flashing with installation of roofing and other items penetrating roof. Install flashing as follows:
 1. Seal with elastomeric sealant and clamp flashing to pipes penetrating roof except for flashing on vent piping.

3.4 WALL FLASHING INSTALLATION

- A. General: Install sheet metal wall flashing to intercept and exclude penetrating moisture according to SMACNA recommendations and as indicated. Coordinate installation of wall flashing with installation of wall-opening components such as windows, doors, and louvers.

3.5 CLEANING AND PROTECTION

- A. Clean exposed metal surfaces of substances that interfere with uniform oxidation and weathering.
- B. Clean and neutralize flux materials. Clean off excess solder and sealants.
- C. Remove temporary protective coverings and strippable films as sheet metal flashing and trim are installed. On completion of installation, clean finished surfaces, including removing unused fasteners, metal filings, pop rivet stems, and pieces of flashing. Maintain in a clean condition during construction.
- D. Repair scratches, abrasions, blemishes, variations in color and texture, and minor surface defects in the finish in accordance with the manufacturer's written instructions.
- E. Replace sheet metal flashing and trim that have been damaged or discolored or that have deteriorated beyond successful repair by finish touchup or similar minor repair procedures.

END OF SECTION

SECTION 07 92 00

CAULKING AND SEALANTS

PART 1 - GENERAL

1.01 GENERAL PROVISIONS

- A. All of the Contract Documents, including the General and Supplementary Conditions and Division 1 General requirements, apply to the work of and are hereby made a part of this Section.
- B. Examine all drawings and all other sections of the specifications for requirements therein affecting the work of this Section whether or not such work is specifically mentioned in this Section.
- C. This section contains information that applies to all work performed under the contract and is hereby made a part of each specification section.

1.02 DESCRIPTION OF WORK

- A. Work Included: Provide all labor, materials and equipment necessary to complete the work of this Section, including but not limited to the following:
 1. Preparing sealant substrate surfaces.
 2. Furnishing and installing sealants and joint backing where indicated on the drawings and specified herein.
 3. Furnishing and Installing sealants at all exterior penetrations in roof.
- B. Related Work: Other specification sections which directly relate to the work of this section include, but are not limited to, the following:
 1. Section 06 10 00 – Rough Carpentry
 2. Section 07 53 23 – EDPM Roofing
 3. Section 07 62 00 – Sheet Metal Flashing and Trim.

1.03 SUBMITTALS

- A. Provide the following FOR REVIEW in accordance with Section 01 33 00 "SUBMITTALS":
 1. Product Data: For each joint-sealant product indicated, provide data indicating:
 - a. sealant chemical characteristics,
 - b. performance criteria, substrate preparation,
 - c. limitations, and
 - d. color availability.
 2. Initial Selection Samples: Manufacturer's color charts consisting of strips of cured sealants showing the full range of colors available for each product exposed to view.

3. Verification Samples: For each kind and color of joint sealant required, provide Samples with joint sealants in 1/2-inch- wide joints formed between two 6-inch-long strips of material matching the appearance of exposed surfaces adjacent to joint sealants.
4. Joint-Sealant Schedule: Include the following information:
 - a. Joint-sealant application, joint location, and designation.
 - b. Joint-sealant manufacturer and product name.
 - c. Joint-sealant formulation.
 - d. Joint-sealant color.

B. Provide the following FOR INFORMATION in accordance with Section 01 33 00 "SUBMITTALS":

1. Manufacturer's Installation Instructions: Indicate special procedures.
2. Product Certificates: For each kind of joint sealant and accessory, from manufacturer.
3. Product Test Reports: Based on evaluation of comprehensive tests performed by a qualified testing agency, indicating that sealants comply with requirements.
4. Warranties: Sample of special warranties.

C. Provide the following in accordance with Section 01 33 00

1. Health and Safety documents, including MDS sheets.

D. Provide the following FOR CLOSEOUT in accordance with Section 01 33 00

1. Warranty Documentation.

1.04 QUALITY ASSURANCE

- A. Reference Standards
 1. ASTM C 834 - Standard Specification for Latex Sealants; 1995.
 2. ASTM C 919 - Standard Practice for Use of Sealants in Acoustical Applications; 1998.
 3. ASTM C 920 - Standard Specification for Elastomeric Joint Sealants; 1998.
 4. ASTM C 1193 - Standard Guide for Use of Joint Sealants; 1991 (Re-approved 1995).
 5. ASTM D 1667 - Standard Specification for Flexible Cellular Materials--Vinyl Chloride Polymers and Copolymers (Closed-Cell Foam); 1997.
 6. ASTM D 2628 - Standard Specification for Preformed Polychloroprene Elastomeric Joint Seals for concrete Pavements; 1991 (Re-approved 1998).
 7. ASTM D 412 - Standard Test Methods for Vulcanized Rubber and Thermoplastic Elastomers- Tension; 1998a.
 8. ASTM D 903 - Standard Test Method for Peel or Stripping Strength of Adhesive Bonds; 1998.
 9. ASTM D 4060 - Standard Test Method for Abrasion Resistance of Organic Coatings by the Taber Abraser; 2001.
 10. ASTM E 84 - Standard Test Method for Surface Burning Characteristics of Building Materials; 2001.

- B. Maintain one copy of each referenced document covering installation requirements on site.
- C. Source Limitations: Obtain each kind of joint sealant from single source from single manufacturer.
- D. Manufacturer Qualifications: Company specializing in manufacturing the Products specified in this section with minimum three years documented experience.
- E. Installer Qualifications: Manufacturer's authorized representative who is trained and approved for installation of units required for this Project.
- F. Mockups: Install sealant in mockups of assemblies specified in other Sections that are indicated to receive joint sealants specified in this Section. Use materials and installation methods specified in this Section.

1.05 PROJECT CONDITIONS

- A. Delivery, Storage And Handling:
 - 1. Deliver Products in manufacturer's original unopened containers or packages with labels intact, identifying product and manufacturer, date of manufacture, lot number, shelf life, curing time, and mixing instructions, where applicable.
 - 2. Store and handle materials to prevent deterioration or damage due to moisture, temperature changes, contaminants, or other causes.
 - 3. Store products in manufacturer's unopened packaging until ready for installation.
- B. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for application and cure.
- C. Do not proceed with installation of joint sealants under the following conditions:
 - 1. When ambient and substrate temperature conditions are outside limits permitted by joint-sealant manufacturer or are below 40 degrees Fahrenheit.
 - 2. When joint substrates are wet.
 - 3. Where joint widths are less than those allowed by joint-sealant manufacturer for applications indicated.
 - 4. Where contaminants capable of interfering with adhesion have not yet been removed from joint substrates.

1.06 WARRANTY

- A. Special Installer's Warranty: Manufacturer's standard form in which Installer agrees to repair or replace joint sealants that do not comply with performance and other requirements specified in this Section within specified warranty period.
 - 1. Warranty Period: 5 years from date of Substantial Completion.
- B. Special Manufacturer's Warranty: Manufacturer's standard form in which joint-sealant manufacturer agrees to furnish joint sealants to repair or replace those that do not comply with performance and other requirements specified in this Section within specified warranty period.

1. Warranty Period: 5 years from date of Substantial Completion.
2. Include coverage for installed sealants and accessories that fail to achieve air-tightness.
- C. Special warranties specified in this article exclude deterioration or failure of joint sealants from the following:
 1. Movement of the structure caused by structural settlement or errors attributable to design or construction resulting in stresses on the sealant exceeding sealant manufacturer's written specifications for sealant elongation and compression.
 2. Disintegration of joint substrates from natural causes exceeding design specifications.
 3. Mechanical damage caused by individuals, tools, or other outside agents.
 4. Changes in sealant appearance caused by accumulation of dirt or other atmospheric contaminants.

PART 2 - PRODUCTS

2.01 MATERIALS, GENERAL

- A. Compatibility: Provide joint sealants, backings, and other related materials that are compatible with one another and with joint substrates under conditions of service and application, as demonstrated by joint-sealant manufacturer, based on testing and field experience.
- B. Liquid-Applied Joint Sealants: Comply with ASTM C 920 and other requirements indicated for each liquid-applied joint sealant specified, including those referencing ASTM C 920 classifications for type, grade, class, and uses related to exposure and joint substrates.
- C. Stain-Test-Response Characteristics: Where sealants are specified to be nonstaining to porous substrates, provide products that have undergone testing according to ASTM C 1248 and have not stained porous joint substrates indicated for Project.
- D. Colors of Exposed Joint Sealants: As selected by Architect from manufacturer's full range.

2.02 URETHANES:

- A. Two-Part Urethane: Self-Leveling, ASTM C920, Type M, Grade P, Class 25.
 1. Chem-Calk CC-550, by Bostik.
 2. Vulkem 245, by Mameco.
 3. Vulkem 255, Wide-Joint, by Mameco.
 4. NR-200 Urexpan, by Pecora Corporation.
 5. Sikaflex-2c NS/SL, by Sika Corporation.
- B. Two-Part Urethane: Non-Sag, ASTM C920, Type M, Grade NS, Class 25.
 1. Chem-Calk 500, by Bostik.

2. Vulkem 227, by Mameco.
3. Dynatrol II, by Pecora Corporation.
4. Sikaflex-2c NS/SL, by Sika Corporation.
5. Sonolastic NP 2, by Sonneborn Building Products, ChemRex Inc.

C. One-Part Urethane: Self-Leveling, ASTM C920, Type S, Grade P, Class 25.

1. Vulkem 45, by Mameco.
2. Urexpan NR-201, by Pecora Corporation.
3. Sonolastic SL1, by Sonneborn Building Products, ChemRex Inc.

D. One-Part Urethane: Non-Sag, ASTM C920, Type S, Grade NS, Class 25.

1. Chem-Calk 900, by Bostik.
2. Vulkem 116, by Mameco.
3. Sonolastic NP I, by Sonneborn Building Products, ChemRex Inc.

2.03 ACRYLICS, LATEX:

- A. One-Part Acrylic Latex, Non-Sag, ASTM-C-834-76.
 1. Chem-Calk 600, by Bostik.
 2. LC-130, by MACCO Adhesives, The Glidden Company.
 3. Easa-ply ALS, by W. R. Meadows, Inc.
 4. AC-20+Silicone Acrylic Latex, by Pecora Corporation.
 5. Sonolac, Sonneborn Building Products, ChemRex Inc.

2.04 PREFORMED COMPRESSIBLE & NON-COMPRESSIBLE FILLERS:

- A. Backer Rod - Closed cell polyethylene foam:
 1. HBR Backer Rod, by Nomaco.
 2. #92 Greenrod, by Nomaco.
 3. Sonofoam Closed-Cell Backer Rod, Sonneborn Building Products, ChemRex Inc.
- B. Backer Rod - Open cell polyurethane foam:
 1. Denver Foam, by Backer Rod Mfg Inc.
 2. Foam Pack II, by Nomaco.
- C. Neoprene compression seals:
 1. WE, WF, and WG Series, by Watson Bowman & Acme Corp.
 2. Will-Seal 150 Precompressed Expanding Foam Sealants, by Will-Seal, a Division of Illbruck.
- D. Butyl Rod: Kirkhill Rubber Co. (714)529-4901.

2.05 BOND BREAKER TAPE:

- A. Polyethylene tape of plastic as recommended by sealant manufacturer, to be applied to sealant contact surfaces where bond to substrate of joint filler must be avoided for proper performance of sealant.

2.06 COLORS

- A. Generally use sealant colors matching color of material joint is located in.
- B. Where a joint occurs between two materials of differing colors and Contractor cannot determine which material to match, contact the Architect for selection.

2.07 ACCESSORIES FOR SEALANTS

- A. Joint Cleaner: Provide type of joint cleaning compound recommended by sealant manufacturer for joint surfaces to be cleaned.
- B. Primer: As recommended by sealant manufacturer.
- C. Masking tape and similar accessories to protect surfaces from damage.

2.08 SCHEDULE FOR SEALANTS

- A. Exterior Joints:
 - 1. Coping joints, coping-to-facade joints, or horizontal surface joints not subject to foot or vehicular traffic.
 - a. Sealant No. 2.02 B
 - b. Sealant No. 2.02 D
 - c. Sealant No. 2.03 A (for prefinished materials only)
 - 2. Painted metal lap or flashing joints.
 - a. Sealant 2.02 A

PART 3 - EXECUTION

3.01 SEALANT INSPECTION

- A. Verification of Conditions: Verify that field measurements, surfaces, substrates and conditions are as required, and ready to receive Work.
 - 1. Verify that joint widths are in conformance with sealant manufacturer allowable limits.
 - 2. Verify that contaminants capable of interfering with adhesion have been cleaned from joint and joint properly prepared.
- B. Report in writing to the Architect prevailing conditions that will adversely affect satisfactory execution of the Work of this Section. Do not proceed with Work until unsatisfactory conditions have been corrected.
- C. By beginning Work, Contractor accepts conditions and assumes responsibility for correcting unsuitable conditions encountered at no additional cost to Owner.

3.02 SEALANT PREPARATION

- A. Prepare and size joints in accordance with manufacturer's instructions. Clean substrates of dirt, laitance, dust, or mortar using solvent, abrasion, or sandblasting as recommended by manufacturer. Remove loose materials and foreign matter which might impair adhesion of sealant.

- B. Verify that joint backing and release tapes are compatible with sealant. Verify sealant is suitable for substrate. Verify that sealant is paintable if painted finish is indicated.
- C. Protect materials surrounding work of this Section from damage or disfiguration.

3.03 SEALANT INSTALLATION

- A. Install sealant in accordance with manufacturer's published instructions. Perform work in accordance with ASTM C804 for solvent release sealants and ASTM C790 for latex base sealants.
- B. Prime or seal joint surfaces where recommended by sealant manufacturer. Do not allow primer or sealer to spill or migrate onto adjoining surfaces.
- C. Install backer rod and bond breaker tape where required by manufacturer.
- D. Install preformed compressible and non-compressible fillers in accordance with manufacturer's published instructions.
- E. Install sealants to depths recommended by sealant manufacturer in uniform, continuous ribbons free of air pockets, foreign embedded matter, ridges, and sags, "wetting" joint bond surfaces equally on both sides.
- F. Tool joints concave unless shown otherwise. Where horizontal joints are between a horizontal surface and a vertical surface, fill joint to form slight cove so that joint will not trap moisture and foreign matter. Dry tool joints. Do not use soap, water, or solvent to tool joints.

3.04 SEALANT CURING

- A. Cure sealants in compliance with manufacturer's published instructions.

3.05 SEALANT CLEANING

- A. Remove excess and spillage of sealants promptly as the work progresses, using materials and methods as recommended by sealant and substrate manufacturers. Clean adjoining surfaces to eliminate evidence of spillage without damage to adjoining surfaces or finishes.

END OF SECTION

(This page intentionally left blank)

SECTION 086300

METAL-FRAMED SKYLIGHTS

PART 1 - GENERAL

1.1 GENERAL PROVISIONS

A. Attention is directed to the CONTRACT AND GENERAL CONDITIONS and all Sections within DIVISION 01 - GENERAL REQUIREMENTS which are hereby made a part of this Section of the Specifications.

1.2 DESCRIPTION OF WORK

A. Work Included: Provide labor, materials and equipment necessary to complete the work of this Section, including but not limited to the following:

1. Aluminum-framed skylights with insulated glass.

B. Related Work: The following items are not included in this Section and will be performed under the designated Sections:

1. Section 061000 – ROUGH CARPENTRY for wood curbs.

2. Section 076200 - SHEET METAL FLASHING AND TRIM for metal flashings installed at perimeters of assemblies.

1.3 PERFORMANCE REQUIREMENTS

A. Provide metal-framed skylights, including anchorage, capable of withstanding, without failure, the effects of the following:

1. Structural loads.
2. Thermal movements.
3. Movements of supporting structure.
4. Dimensional tolerances of building frame and other adjacent construction.
5. Loosening or weakening of fasteners, attachments, and other components.
6. Sealant failure.

B. Structural Loads: Wind loads, snow loads, concentrated live loads and seismic loads as required by Code.

C. Thermal Movements: Allow for thermal movements from ambient and surface temperature changes. Base engineering calculation on surface temperatures of materials due to both solar heat gain and nighttime-sky heat loss.

1. Temperature Change (Range): 120 degrees F ambient; 180 degrees F material surfaces.

1.4 SUBMITTALS

- A. Product Data: Include construction details, material descriptions, dimensions of individual components and profiles, and finishes for metal-framed skylights.
- B. Shop Drawings: For metal-framed skylights. Include plans, elevations, sections, details, and attachments to other work.
- C. Samples for Verification: For each type of exposed finish required, in manufacturer's standard sizes.
- D. Fabrication Sample: Of each framing intersection of assemblies, made from 12-inch lengths of full-size components and showing details of the following:
 - 1. Joinery.
 - 2. Anchorage.
 - 3. Expansion provisions.
 - 4. Glazing.
 - 5. Flashing and drainage.
- E. Maintenance Data: For metal-framed skylights to include in maintenance manuals.
- F. Warranties: Special warranties specified in this Section.

1.5 QUALITY ASSURANCE

- A. Installer Qualifications: Entity capable of assuming engineering responsibility and performing work of this Section and who is acceptable to manufacturer.

1.6 PROJECT CONDITIONS

- A. Field Measurements: Indicate measurements on Shop Drawings.

1.7 WARRANTY

- A. Special Assembly Warranty: Manufacturer's standard form in which manufacturer agrees to repair or replace components of metal-framed skylights that fail in materials or workmanship within specified warranty period.

1. Failures include, but are not limited to, the following:
 - a. Structural failures including, but not limited to, excessive deflection.
 - b. Noise or vibration caused by thermal movements.
 - c. Deterioration of metals, metal finishes, and other materials beyond normal weathering.
 - d. Adhesive or cohesive sealant failures.
 - e. Water leakage.
2. Warranty Period: Ten years from the date of Certificate of Agency Use and Occupancy. Guarantees or warranties that start at the date of shipment from the factory, or from the completion date of an individual portion of the project, are not acceptable.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 1. Velux America, LLC.
 2. Wasco Products, Inc.
 3. Or equal.

2.2 FRAMING SYSTEMS

- A. Aluminum: Alloy and temper recommended in writing by manufacturer for type of use and finish indicated.
 1. Sheet and Plate: ASTM B 209.
 2. Extruded Bars, Rods, Profiles, and Tubes: ASTM B 221.
 3. Extruded Structural Pipe and Tubes: ASTM B 429.
- B. Pressure Caps: Manufacturer's standard aluminum components that mechanically retain glazing. Include snap-on aluminum trim that conceals fasteners.
- C. Brackets and Reinforcements: Manufacturer's standard high-strength aluminum with nonstaining, nonferrous shims for aligning skylight components.
- D. Anchors, Fasteners, and Accessories: Manufacturer's standard, corrosion-resistant, nonstaining, and nonbleeding; compatible with adjacent materials.
 1. Where fasteners are subject to loosening or turning out from thermal and structural movements, wind loads, or vibration, use self-locking devices.

METAL FRAMED SKYLIGHTS

08 63 00 - 3

2. Exposed Fasteners:
 - a. Use exposed fasteners with countersunk Phillips screw heads.
 - b. Finish exposed portions to match framing system.
3. At movement joints, use slip-joint linings, spacers, and sleeves of material and type recommended in writing by manufacturer.
- E. Anchor Bolts: ASTM A 307, Grade A hot-dip zinc coating, ASTM A 153/A 153M, Class C.
- F. Concealed Flashing: Manufacturer's standard, corrosion-resistant, nonstaining, nonbleeding flashing compatible with adjacent materials.
- G. Exposed Flashing and Closures: Manufacturer's standard aluminum components not less than 0.040 inch thick.
- H. Framing Gaskets: Manufacturer's standard
- I. Framing Sealants: As recommended in writing by manufacturer.

2.3 GLAZING SYSTEMS

- A. Glazing: Provide insulating-glass units.
- B. Spacers, Setting Blocks, and Gaskets: Manufacturer's standard elastomeric types.
- C. Glazing Sealants: As recommended in writing by manufacturer.

2.4 FABRICATION

- A. Fabricate aluminum components before finishing.
- B. Fabricate aluminum components that, when assembled, have the following characteristics:
 1. Profiles that are sharp, straight, and free of defects or deformations.
 2. Accurately fitted joints with ends coped or mitered.
 3. Internal guttering systems or other means to drain water passing joints, condensation occurring within framing members, and moisture migrating within skylight to exterior.
 4. Physical and thermal isolation of glazing from framing members.
 5. Accommodations for thermal and mechanical movements of glazing and framing to maintain required glazing edge clearances.
- C. Fabricate aluminum sill closures with weep holes and for installation as continuous component.
- D. Reinforce aluminum components as required to receive fastener threads.

2.5 ALUMINUM FINISHES

- A. General: Comply with NAAMM's "Metal Finishes Manual for Architectural and Metal Products" for recommendations for applying and designating finishes.
 - 1. Color and Gloss: As selected by Designer from manufacturer's full range, including metallics.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine areas, with Installer present, for compliance with requirements for installation tolerances and other conditions affecting performance of work.
 - 1. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION

- A. General:
 - 1. Comply with manufacturer's written instructions.
 - 2. Do not install damaged components.
 - 3. Fit joints between aluminum components to produce hairline joints free of burrs and distortion.
 - 4. Install anchors with separators and isolators to prevent metal corrosion and electrolytic deterioration and to prevent impeding movement of moving joints.
 - 5. Seal joints watertight, unless otherwise indicated.
- B. Install components to drain water passing joints, condensation occurring within framing members, and moisture migrating within skylight to exterior.
- C. Install components plumb and true in alignment with established lines and elevations.

END OF SECTION

SECTION 22 04 00

GENERAL CONDITIONS FOR PLUMBING TRADES

PART 1 GENERAL

1.1 RELATED REQUIREMENTS

- A. Drawings and general provisions of Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- B. This section applies to all sections of Division 22, "Plumbing".

1.2 DESCRIPTION

- A. The General Conditions and Supplementary General Conditions are a part of this Division and are to be considered a part of this Contract.
- B. Where items of the General Conditions and Supplementary General Conditions are repeated in other Sections of the Specifications, it is merely intended to qualify or to call particular attention to them. It is not intended that any other parts of the General Conditions and Supplementary General Conditions shall be assumed to be omitted if not repeated therein. This Section applies equally and specifically to all Contractors supplying labor and/or equipment and/or materials as required under each Section of this Division. Where conflicts exist between the drawings and the specifications or between this section of the specifications and other sections, the more stringent or higher cost option shall apply.

1.3 INTENT

- A. It is the intent of the Specifications and Drawings to call for finished work, tested and ready for operation. Provide all parts necessary for the intended use, fully complete and operational, and installed in professional manner in accordance with the design intent.
- B. Any apparatus, appliance, material or work not shown on drawings but mentioned in the specifications, or vice versa, or any incidental accessories necessary to make the work complete and ready for operation as determined by good trade practice even if not particularly specified, shall be furnished, delivered and installed under their respective Divisions without any additional expense to the Owner.
- C. Minor details not usually shown or specified but necessary for proper installation and operation shall be included in the work as though they were hereinafter shown or specified.
- D. Work under each Section shall include giving written notice to the Owner and Engineer of any materials or apparatus believed inadequate or unsuitable; in violation of laws, ordinances, rules or regulations of authorities having jurisdiction; and any necessary items of work omitted. In the absence of such written notice, it is mutually agreed that work under each Section includes the cost of all required items for the accepted, satisfactory functioning of the entire system without extra compensation.

1.4 DEFINITIONS

- A. "Approved equal" also known as "alternative" mean any product which in the opinion of the Engineer is equal in quality, arrangement, appearance, and performance to the product specified.
- B. Directed: Terms such as "directed," "requested," "authorized," "selected," "approved," "required," and "permitted" mean "directed by the Engineer," "requested by the Engineer," and similar phrases.
- C. "Finished" refers to all rooms and areas to be specified to receive architectural treatment as indicated on the drawings. All rooms and areas not covered, including underground tunnels and areas above ceilings shall be considered not finished, unless otherwise noted.
- D. "Furnish" or "supply" shall mean purchase, deliver to, and off-load at the job site, ready to be installed including where appropriate all necessary interim storage and protection.
- E. Indicated: The term "indicated" refers to graphic representations, notes, or schedules on the Drawings, other paragraphs or schedules in the Specifications, and similar requirements in the Contract Documents. Where terms such as "shown," "noted," "scheduled," and "specified" are used, it is to help the reader locate the reference; no limitation on location is intended.
- F. "Install" shall mean set in place complete with all mounting facilities and connections as necessary ready for normal use or service.
- G. No Exceptions Taken – reviewed and determined to be in general conformance with contract documents.
- H. "Product" shall mean any item of equipment, material, fixture, apparatus, appliance or accessory installed under this Division.
- I. "Provide" shall mean furnish (or supply) and install as necessary.
- J. Regulation: The term "Regulations" includes laws, ordinances, statutes, and lawful orders issued by authorities having jurisdiction, as well as rules, conventions, and agreements within the construction industry that control performance of the Work.
- K. Remove: The term "remove" means "to disconnect from its present position, remove from the premises and to dispose of in a legal manner."
- L. Special Warranties: The term "Special Warranties" are written warranties required by or incorporated in the Contract Documents, either to extend time limits provided by standard warranties or to provide greater rights for the Owner.
- M. Standard Product Warranties: The term "Standard Product Warranties" are preprinted written warranties published by individual manufacturers for particular products and are specifically endorsed by the manufacturer to the Owner.
- N. "Subcontractor" means specifically the subcontractor working under this Division. Other Contractors are specifically designated "Plumbing Subcontractor", "General Contractor" and so on. Note: Take care to ascertain limits of responsibility for connecting equipment which requires connections by two or more trades.

- O. Substitutions: Requests for changes in products, materials, equipment, and methods of construction proposed by the Contractor are considered requests for "substitutions."
- P. "Wiring" shall mean cable assembly, raceway, conductors, fittings and any other necessary accessories to make a complete wiring system.

1.5 CONTRACT DOCUMENTS

- A. The two dimensional drawings govern the construction. They show the design intent and are part of the Contract Documents. BIM models are not part of contract documents. They are developed for convenience only.
- B. Drawings are diagrammatic and indicate the general arrangement of systems and work included in the Contract. Consult the Architectural Drawings and Details for exact location of fixtures and equipment; where same are not definitely located, obtain this information from the Architect. (Do not scale the drawings)
- C. Work under each Section shall closely follow Drawings in layout of work; check Drawings of other Divisions to verify spaces in which work will be installed. Maintain maximum headroom; where space conditions appear inadequate, Owner and Engineer shall be notified before proceeding with installations.
- D. The Owner may, without extra charge, make reasonable modifications in the layout as needed to prevent conflict with work of other trades and/or for proper execution of the work.

1.6 DISCREPANCIES IN DOCUMENTS

- A. Where variances occur between the Drawings and Specifications or within either of the Documents, the item or arrangement of better quality, shall be included in the Contract price. The Owner and Engineer shall decide on the item and the manner in which the work shall be installed.
- B. Where Drawings or Specifications conflict or are unclear, submit clarification request in writing before Award of Contract. Otherwise, Architect's interpretation of Contract Documents shall be final, and no additional compensation shall be permitted due to discrepancies or un-clarities thus resolved.
- C. Where Drawings or Specifications do not coincide with manufacturers' recommendations or with applicable codes and standards, submit clarification request in form of an RFI before installation. Otherwise, make changes in installed work required for compliance with manufacturer instructions or codes and standards within Contract Price.
- D. Where insufficient information exists in the documents to precisely describe a certain component or subsystem, or the routing of a component or its coordination with other building elements, where notification required by Paragraph (B) above has not been submitted, provide the specific component or subsystem with all parts necessary for the intended use, fully complete and operational, and installed in professional manner either concealed or exposed in accordance with the design intent.
- E. Where discrepancies exist between the mechanical, plumbing, fire protection, and electrical drawings in regards to what trade owns disconnects or starters, the discrepancy shall be brought to the Architect's attention in accordance with paragraph (B) above. If the scope is not resolved prior to the Award of Contract, Division 26 shall provide such items.

1.7 SURVEYS AND MEASUREMENTS

- A. Before submitting the Bid, the Contractors shall visit the site and become thoroughly familiar with all existing conditions under which work will be installed. This Contract includes all modifications of existing systems required for the installation of new equipment. This Contract includes all necessary offsets, transitions and modifications required to install all new equipment in existing spaces. All new and existing equipment and systems shall be fully operational under this Contract before the job is considered complete. The Contractors shall be held responsible for any assumptions made, any omissions or errors made as a result of their failure to become fully familiar with the existing conditions at the site and the Contract Documents.
- B. The Contractor shall base all measurements, both horizontal and vertical, from established bench marks. All work shall agree with these established lines and levels. Verify all measurements at the site and check the correctness of same as related to the work.
- C. Should the Contractor discover any discrepancies between actual measurements and those indicated which prevent following good practice or which interfere with the intent of the Drawings and Specifications, the Engineer will be notified and work will not proceed until instructions from the Engineer are received.

1.8 CODES AND STANDARDS

- A. Reference Standard Compliance
 - 1. Where equipment or materials are specified to conform to industry and technical society reference standards of the organizations such as American National Standards Institute (ANSI), American Society for Testing and Materials (ASTM), National Electrical Manufacturers Association (NEMA), and Underwriters Laboratories Inc. (UL), submit proof of such compliance. The label or listing by the specified organization will be acceptable evidence of compliance.
 - 2. Independent Testing Organization Certificate: In lieu of the label or listing indicated above, submit a certificate from an independent testing organization, competent to perform testing, and approved by the Engineer. The certificate shall state that the item has been tested in accordance with the specified organization's test methods and that the item complies with the specified organization's reference standard.
- B. Wherever Codes and/ or standards are mentioned in these specifications, the latest applicable edition or revision of the local building or life safety code shall be followed.
- C. The following Standards shall be used where referenced by the following abbreviations:

AABC	Associated Air Balance Council
ACGIH	American Conference of Governmental Industrial Hygienists
ADC	Air Diffusion Council
AGA	American Gas Association
AIA	American Institute of Architects
AMCA	Air Moving and Conditioning Association
ANSI	American National Standards Institute
API	American Petroleum Institute
ARI	Air Conditioning and Refrigeration Institute
ASHRAE	American Society of Heating, Refrigerating and Air Conditioning Engineers
ASME	American Society of Mechanical Engineers
ASPE	American Society of Plumbing Engineers
ASSE	American Society of Sanitary Engineers

ASTM	American Society of Testing and Materials
AWS	American Welding Society
AWWA	American Water Works Association
CGA	Compressed Gas Association
CSA	Canadian Standards Association
CISPI	Cast Iron Soil Pipe Institute
EJMA	Expansion Joint Manufacturing Association
EPA	Environmental Protection Agency
FM	Factory Mutual
FSSC	Federal Specification
HIS	Hydraulic Institute Standards
IEEE	Institute of Electrical and Electronics Engineers
IRI	Industrial Risk Insurers
ISO	Insurance Services Office
MCAA	Mechanical Contractors Association of America
NBS	National Bureau of Standards
NEBB	National Environmental Balancing Bureau
NEMA	National Electrical Manufacturers Association
NFPA	National Fire Protection Association
NOFI	National Oil Fuel Institute
NSC	National Safety Council
NSF	National Sanitation Foundation
OSHA	Occupational Safety and Health Administration
PDI	Plumbing and Drainage Institute
SBI	Steel Boiler Industry (Division of Hydronics Institute)
SMACNA	Sheet Metal and Air Conditioning Contractors National Association
STI	Steel Tank Institute
UL	Underwriters' Laboratories

- D. All materials furnished and all work installed shall comply with the rules and recommendations of the NFPA, the requirements of the local utility companies, the recommendations of the fire insurance rating organization having jurisdiction and the requirements of all Governmental departments having jurisdiction.
- E. The Contractor shall include in the work, without extra cost to the Owner, any labor, materials, services, apparatus and Drawings in order to comply with all applicable laws, ordinances, rules and regulations, whether shown on Drawings and/or specified or not.

1.9 PERMITS AND FEES

- A. The Contractor shall give all necessary notices, obtain all permits; and pay all Government and State sales taxes and fees where applicable, and other costs, including utility connections or extensions in connection with the work, file all necessary Drawings, prepare all documents and obtain all necessary approvals of all Governmental and State departments having jurisdiction, obtain all required certificates of inspection for his work, and deliver a copy to the Owner and Engineer before request for acceptance and final payment for the work.

1.10 EQUIPMENT EQUIVALENTS AND SUBSTITUTIONS

- A. Certain manufacturers of material, apparatus or appliances are indicated in the drawings and specifications for this project. These items have been used as the basis of design, and as a convenience in fixing the minimum standard of quality, finish and design that is required. If the Contractors uses an "approved equal" alternative to the basis of design, and if the features of that alternative have an impact on other components of the Project, the Contractor shall include the necessary adjustments in those components, whether for

architectural, structural, mechanical, electrical, fire protection, or any other elements, plus any adjustments for difference in performance.

- B. Where no specific make of material, apparatus or appliance is mentioned, any first-class product made by a reputable manufacturer may be submitted for Architect and Engineer review.
- C. Where the Contractor proposes to use an item that is different from the basis of design in the Drawings and specifications, and that will require the redesign of the structure, partitions, foundations, piping, wiring or any other component of the mechanical, electrical, or architectural layout, the Contractor shall provide the necessary redesign of those components.
- D. Where the Contractor proposes to deviate (provide an equivalent or request for substitution) from the basis of design scheduled equipment or materials as hereinafter specified or shown on the drawings, they are required to submit a requested for substitution in writing. The Contractor shall state in their request whether it is a substitution, equivalent or a non approved equivalent to that specified and the amount of credit or extra cost involved. A copy of said request shall be included in the Base Bid with manufacturer's equipment cuts. The Base Bid shall be based on using the materials and equipment as specified with no exceptions.
- E. If an alternative or substitute item results in a difference in quantity and arrangement of structure, piping, ductwork, valves, pumps, insulation, wiring, conduit, and equipment from that specified or indicated on the Drawings, furnish and install any such additional equipment required by the system, at no additional cost to the Owner including any costs added to other trades due to the equivalent change from the basis of design detailed in the drawings or included within the specifications.

1.11 SUBMITTAL PROCEDURES

- A. Provide Submittals in accordance with the requirements of Division 01 and as indicated in the following.
- B. Coordination: Coordinate preparation and processing of submittals with performance of construction activities. Transmit each submittal sufficiently in advance of performance of related construction activities to avoid delay.
 - 1. Coordinate each submittal with fabrication, purchasing, testing, delivery, other submittals and related activities that require sequential activity.
 - 2. Coordinate transmittal of different types of submittals for related elements of the Work so processing will not be delayed by the need to review submittals concurrently for coordination. The Engineer reserves the right to withhold action on a submittal requiring coordination with other submittals until related submittals are received.
- C. Processing: Allow sufficient review time so that installation will not be delayed as a result of the time required to process submittals, including time for resubmittals.
 - 1. Allow ten business days for initial review. Allow additional time if processing must be delayed to permit coordination with subsequent submittals. The Engineer will promptly advise the Contractor when a submittal being processed must be delayed for coordination.
 - 2. If an intermediate submittal is necessary, process the same as the initial submittal.
 - 3. Allow ten business days for reprocessing each submittal.

4. No extension of Contract Time will be authorized because of failure to transmit submittals to the Engineer sufficiently in advance of the Work to permit processing.
- D. Submittal Preparation: Place a permanent label or title block on each submittal for identification. Indicate the name of the entity that prepared each submittal on the label or title block. Submittals shall be arranged in order of specification sections.
 1. Include the following information on the label for processing and recording action taken.
 - a. Project name.
 - b. Date.
 - c. Name and address of Engineer.
 - d. Name and address of Contractor.
 - e. Name and address of subcontractor.
 - f. Name and address of supplier.
 - g. Name of manufacturer.
 - h. Number, title and paragraph of appropriate Specification Section.
 - i. Drawing number and detail references, as appropriate.
- E. Submittal Transmittal: Package each submittal appropriately for transmittal and handling. Transmit each submittal from Contractor to Engineer using a transmittal form. Submittals received from sources other than the Contractor will be returned without action. On the transmittal, record relevant information and requests for data. On the form, or separate sheet, record deviations from Contract Document requirements, including minor variations and limitations. Include Contractor's certification that information complies with Contract Document requirements.
- F. Except for submittals for record, information or similar purposes, the Engineer will review each submittal, mark to indicate action taken, and return promptly. Compliance with specified characteristics is the Contractor's responsibility.
- G. Action Stamp: The Engineer will stamp each submittal with a uniform, self-explanatory action stamp. The stamp will be appropriately marked, to indicate the action taken.

1.12 COORDINATION WITH OTHER DIVISIONS

- A. All work shall be carried out in conjunction with other trades and full cooperation shall be given in order that all work may proceed with a minimum of delay and interference. Particular emphasis is placed on timely installation of major apparatus and furnishing other Contractors, especially the Contractor or Construction Manager, with information as to openings, chases, sleeves, bases, inserts, equipment locations, panels, etc., required by other trades.
- B. The Contractors are required to examine all of the Project Drawings and mutually arrange work so as to avoid interference with the work of other trades. In general, ductwork, HVAC piping, sprinkler piping and drainage lines take precedence over water, gas and electrical conduits. The Engineer shall make final decisions regarding the arrangement of work which cannot be agreed upon by the Contractors.
- C. Where the work of the Contractor will be installed in close proximity to or will interfere with work of other trades, the Contractors will cooperate in working out space conditions to make a satisfactory adjustment.
- D. If the work under a Section is installed before coordinating with other Divisions or Sections or so as to cause interference with work of other Sections, the necessary

changes to correct the condition shall be made by the Contractor causing the interference without extra charge to the Owner.

1.13 QUALITY CONTROL

- A. Service Support: The equipment items shall be supported by service organizations which are reasonably convenient to the equipment installation in order to render satisfactory service to the equipment on a regular and emergency basis during the warranty period of the contract.
- B. Modification of References: In each of the publications referred to herein, consider the advisory provisions to be mandatory, as though the word, "shall" had been substituted for "should" wherever it appears.
- C. Furnish the services of an experienced superintendent who shall be constantly in charge of the installation of the work together with all skilled tradespeople, fitters, metal workers, welders, helpers and laborers required to unload, transfer, erect, connect, adjust, start, operate and test each system.
- D. Unless otherwise specifically indicated on the Drawings or Specifications, all equipment and materials shall be installed with the acceptance of the Engineer and in accordance with the recommendations of the manufacturer. This includes the performance of such tests as the manufacturer recommends.
- E. All labor for installation of plumbing systems shall be performed by experienced, skilled tradespeople under the supervision of a licensed journeyman foreman. All work shall be of a quality consistent with good trade practice and shall be installed in a neat, professional manner. The Engineer reserves the right to reject any work which, in their opinion, has been installed in a substandard, dangerous or unserviceable manner. Replace said work in a satisfactory manner at no extra cost to the Owner.

1.14 SHUTDOWNS

- A. When installation of a new system requires the temporary shutdown of an existing operating system, the connection of the new system shall be performed at such time as designated by the Owner.
- B. The Engineer and the Owner shall be notified in writing of the estimated duration of the shutdown period at least ten (10) days in advance of the date the work is to be performed.
- C. Work shall be arranged for continuous performance whenever possible. Provide all necessary labor, including overtime if required, to assure that existing operating services will be shut down only during the time actually required to make necessary connections.

1.15 PROTECTION OF MATERIALS AND EQUIPMENT

- A. Work under each Section shall include protecting the work and material of all other Sections from damage by work or tradespeople and shall include making good all damage thus caused.
- B. The Contractor shall be responsible for work and equipment until the facility has been accepted by the Owner. Protect work against theft, injury or damage and carefully store material and equipment received on site which is not immediately installed. Close open

ends of work with temporary covers or plugs during construction to prevent entry of foreign material.

- C. Work under each Section includes receiving, unloading, uncrating, storing, protecting, setting in place and completely connecting equipment supplied under each Section. Work under each Section shall also include exercising special care in handling and protecting equipment and fixtures, and shall include the cost of replacing any of the equipment and fixtures which are missing or damaged.
- D. Equipment and material stored on the job site shall be protected from the weather, vehicles, dirt and/or damage by tradespeople or machinery. Insure that all electrical or absorbent equipment or material is protected from moisture during storage.

1.16 ADJUSTING AND TESTING

- A. After all the equipment and accessories to be furnished are in place, they shall be put in final adjustment and subjected to such operating tests so as to assure the Engineer that they are in proper adjustment and in satisfactory, permanent operating condition.
- B. Where requested by the Engineer, a factory-trained service representative shall inspect the installation and assist in the initial startup and adjustment to the equipment. The period of these services shall be for such time as necessary to secure proper installation and adjustments. After the equipment is placed in permanent operation, the service representative shall supervise the initial operation of the equipment and instruct personnel responsible for operation and maintenance of the equipment. The service representative shall notify the Contractor in writing that the equipment was installed according to manufacturer's recommendations and is operating as intended by the manufacturer.

1.17 CLEANING

- A. The Contractor shall thoroughly clean all equipment of all foreign substances, oils, dust, dirt, etc., inside and out before final acceptance by the Engineer.
- B. If any part of a system should be stopped or damaged by any foreign matter after being placed in operation, the system shall be disconnected, cleaned and reconnected wherever necessary to locate and/or remove obstructions. Any work damaged in the course of removing obstructions shall be repaired or replaced when the system is reconnected at no additional cost to the Owner.
- C. During the course of construction, all pipes shall be capped in an acceptable manner to insure adequate protection against the entrance of foreign matter.
- D. Upon completion of all work under the Contract, remove from the premises all rubbish, debris and excess materials left over from his work. Any oil or grease stains on floor areas shall be removed and floor areas left clean.
- E. Complete the following cleaning operations before requesting inspection for Certification of Substantial Completion.
 1. Remove labels that are not permanent labels.
 2. Clean transparent materials, including mirrors and glass in doors and windows. Remove glazing compound and other substances that are noticeable vision-obscuring materials. Replace chipped or broken glass and other damaged transparent materials.

3. Clean exposed exterior and interior hard-surfaced finishes to a dust-free condition, free of stains, films and similar foreign substances. Restore reflective surfaces to their original reflective condition. Leave concrete floors broom clean. Vacuum carpeted surfaces.
4. Wipe surfaces of equipment. Remove excess lubrication and other substances.

F. Comply with regulations of authorities having jurisdiction and safety standards for cleaning. Do not burn waste materials. Do not bury debris or excess materials on the Owner's property. Do not discharge volatile, harmful or dangerous materials into drainage systems. Remove and dispose of ALL waste materials, packaging material, skids etc. from the site and dispose of in a lawful manner in accordance with municipal, state and federal regulations.

G. Where extra materials of value remaining after completion of associated Work have become the Owner's property, arrange for disposition of these materials as directed.

1.18 OPERATING AND MAINTENANCE

- A. Upon completion of all work and tests, furnish the necessary skilled labor and helpers for operating his system and equipment for a period specified under each applicable Section of this Division. During this period, instruct the Owner or the Owner's representative in the operation, adjustment and maintenance of all equipment furnished. The Contractor shall give at least seven (7) days' notice to the Owner and the Engineer in advance of this period.
- B. The Contractor shall physically demonstrate procedures for all routine maintenance of all equipment furnished under each respective Section to assure accessibility to all devices.
- C. Refer to individual trade Sections for any other particular requirements related to operating instructions.

1.19 RECORD DRAWINGS

- A. General: Do not use record documents for construction purposes; protect from deterioration and loss in a secure, fire-resistive location; provide access to record documents for the Engineer's reference during normal working hours.
- B. Record Drawings: Maintain a clean, undamaged set of blue or black line white-prints of Contract Drawings and Shop Drawings. Mark the set to show the actual installation where the installation varies substantially from the Work as originally shown. Mark whichever drawing is most capable of showing conditions fully and accurately; where Shop Drawings are used, record a cross-reference at the corresponding location on the Contract Drawings.

1.20 WARRANTIES AND BONDS

- A. The following general administrative and procedural requirements for warranties and bonds required by the Contract Documents, including manufacturers' standard warranties on products and special warranties are to be included:
 1. General close-out requirements included in Division 01.
 2. Specific requirements for warranties for the Work and products and installation that are specified to be warranted, are included in the individual Sections of Divisions-02 through -50.
 3. Certifications and other commitments and agreements for continuing services to Owner are specified elsewhere in the Contract Documents.

- B. Disclaimers and Limitations: Manufacturer's disclaimers and limitations on product warranties do not relieve the Contractor of the warranty on the Work that incorporates the products, nor does it relieve suppliers, manufacturers, and subcontractors required to countersign special warranties with the Contractor.
- C. Separate Prime Contracts: Each prime Contractor is responsible for warranties related to its own Contract.

1.21 WARRANTY REQUIREMENTS

- A. Related Damages and Losses: When correcting warranted Work that has failed, remove and replace other Work that has been damaged as a result of such failure or that must be removed and replaced to provide access for correction of warranted Work.
- B. Reinstatement of Warranty: When Work covered by a warranty has failed and been corrected by replacement or rebuilding, reinstate the warranty by written endorsement. The reinstated warranty shall be equal to the original warranty with an equitable adjustment for depreciation.
- C. Replacement Cost: Upon determination that Work covered by a warranty has failed, replace or rebuild the Work to an acceptable condition complying with requirements of Contract Documents. The Contractor is responsible for the cost of replacing or rebuilding defective Work regardless of whether the Owner has benefited from use of the Work through a portion of its anticipated useful service life.
- D. Owner's Recourse: Written warranties made to the Owner are in addition to implied warranties, and shall not limit the duties, obligations, right and remedies otherwise available under the law, nor shall warranty periods be interpreted as limitations on time in which the Owner can enforce such other duties, obligations, rights, or remedies.
- E. Rejection of Warranties: The Owner reserves the right to reject warranties and to limit selections to products with warranties not in conflict with requirements of the Contract Documents.
- F. The Owner reserves the right to refuse to accept Work for the Project where a special warranty, certification, or similar commitment is required on such Work or part of the Work, until evidence is presented that entities required to countersign such commitments are willing to do so.
- G. Submit written warranties to the Engineer prior to the date certified for Substantial Completion. If the Engineer's Certificate of Substantial Completion designates a commencement date for warranties other than the date of Substantial Completion for the Work, or a designated portion of the Work, submit written warranties upon request of the Engineer.
- H. When a designated portion of the Work is completed and occupied or used by the Owner, by separate agreement with the Contractor during the construction period, submit properly executed warranties to the Engineer within fifteen days of completion of that designated portion of the Work.
- I. When a special warranty is required to be executed by the Contractor, or the Contractor and a subcontractor, supplier or manufacturer, prepare a written document that contains appropriate terms and identification, ready for execution by the required parties. Submit a draft to the Owner through the Engineer for approval prior to final execution.

1.22 GUARANTEES

- A. The Contractor shall guarantee all material and installation quality under these Specifications and the Contract for a period of one (1) year from the date of final acceptance by Owner. During this guarantee period, all defects developing through faulty equipment, materials or installation quality shall be corrected or replaced immediately by this Contractor without expense to the Owner. Such repairs or replacements shall be made to the Engineer's satisfaction.
- B. Contractor shall provide name, address, and phone number of all contractors and subcontractors and associated equipment they provided.

1.23 PROJECT CLOSE-OUT

- A. Submit specific warranties, quality bonds, maintenance agreements, final certifications and similar documents in accordance with Division 01.
- B. Deliver tools, spare parts, extra stock, and similar items.
- C. Complete start-up testing of systems, including measuring and documenting all required startup checklist requirements documented in installation and maintenance instructions by the equipment manufacturer, and instruction of the Owner's operating and maintenance personnel. Discontinue or change over and remove temporary facilities from the site, along with construction tools, mock-ups, and similar elements.
- D. Complete final clean up requirements, including touch-up painting. Touch-up and otherwise repair and restore marred exposed finishes.
- E. Field Observation Procedures: On receipt of a request for an Engineers Field Observation, the Engineer will advise the Contractor of unfulfilled requirements. The Engineer will advise the Contractor of construction that must be completed or corrected before the certificate will be issued. Contractor shall submit written response to each corrective item including specific photos prior to final Engineering inspection.
 1. The Engineer will repeat the Field Observation when requested and assured that the Work has been substantially completed.
 2. Results of the completed list of unfulfilled items will form the basis of requirements for final acceptance.

END OF SECTION

SECTION 22 14 00

FACILITY STORM DRAINAGE

PART 1 GENERAL

1.1 SUMMARY

- A. Section Includes:
 - 1. Replacement roof drains.
 - 2. Storm water piping above grade.
- B. Related Sections:
 - 1. Section 22 04 00 – General Conditions for Plumbing Trades

1.2 REFERENCES

- A. American Society of Mechanical Engineers:
 - 1. ASME A112.21.2M - Roof Drains.
 - 2. ASME B31.9 - Building Services Piping.
- B. ASTM International:
 - 1. ASTM A74 - Standard Specification for Cast Iron Soil Pipe and Fittings.
 - 2. ASTM C564 - Standard Specification for Rubber Gaskets for Cast Iron Soil Pipe and Fittings.
- C. Cast Iron Soil Pipe Institute:
 - 1. CISPI 301 - Standard Specification for Hubless Cast Iron Soil Pipe and Fittings for Sanitary and Storm Drain, Waste, and Vent Piping Applications.
 - 2. CISPI 310 - Specification for Coupling for Use in Connection with Hubless Cast Iron Soil Pipe and Fittings for Sanitary and Storm Drain, Waste, and Vent Piping Applications.
- D. Manufacturers Standardization Society of the Valve and Fittings Industry:
 - 1. MSS SP 58 - Pipe Hangers and Supports - Materials, Design and Manufacturer.
 - 2. MSS SP 69 - Pipe Hangers and Supports - Selection and Application.
 - 3. MSS SP 89 - Pipe Hangers and Supports - Fabrication and Installation Practices.

1.3 SUBMITTALS

- A. Division 01 - General Requirements.
- B. Shop Drawings: Indicate dimensions, weights, and placement of openings and holes for sump-pumps, catch basins and manholes.
- C. Product Data:
 - 1. Piping: Submit data on pipe materials, fittings, and accessories. Submit manufacturers catalog information.
 - 2. Hangers and Supports: Submit manufacturers catalog information including load capacity.
 - 3. Storm Drainage Specialties: Submit manufacturers catalog information, component sizes, rough-in requirements, service sizes, and finishes.

- D. Manufacturer's Installation Instructions: Submit installation instructions for material and equipment.
- E. Manufacturer's Certificate: Certify products meet or exceed specified requirements.

1.4 CLOSEOUT SUBMITTALS

- A. Division 01 - General Requirements.
- B. Project Record Documents: Record actual locations of equipment and clean-outs.

1.5 QUALIFICATIONS

- A. Manufacturer: Company specializing in manufacturing products specified in this section with minimum three years documented experience.
- B. Installer: Company specializing in performing Work of this section with minimum three years documented experience.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Division 01- General Requirements.
- B. Protect piping systems from entry of foreign materials by temporary covers, completing sections of the Work, and isolating parts of completed system.

1.7 FIELD MEASUREMENTS

- A. Verify field measurements prior to fabrication.

PART 2 PRODUCTS

2.1 STORM WATER PIPING, ABOVE GRADE

- A. Cast Iron Pipe: CISPI 301, hubless, service weight.
 - 1. Fittings: Cast iron, CISPI 301.
 - 2. Joints: Neoprene gaskets and stainless steel clamp-and-shield assemblies.

2.2 ROOF DRAINS

- A. Manufacturers:
 - 1. JR Smith
 - 2. Zurn
 - 3. Josam
 - 4. Substitutions: Division 01 - General Requirements.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Division 01 - General Requirements.

3.2 PREPARATION

- A. Remove scale and dirt, on inside and outside, before assembly.

3.3 INSTALLATION - ABOVE GROUND PIPING

- A. Route piping in orderly manner and maintain gradient. Route parallel and perpendicular to walls.
- B. Support cast iron drainage piping at every joint.

3.4 FIELD QUALITY CONTROL

- A. Refer to Division 01 – General Requirements.
- B. Test roof drains and new storm drain piping as applicable, in accordance with applicable code.

END OF SECTION

SECTION 23 04 00

GENERAL CONDITIONS FOR MECHANICAL TRADES

PART 1 GENERAL

1.1 RELATED REQUIREMENTS

- A. Drawings and general provisions of Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- B. This section applies to all sections of Division 23, "Mechanical".

1.2 DESCRIPTION

- A. The General Conditions and Supplementary General Conditions are a part of this Division and are to be considered a part of this Contract.
- B. Where items of the General Conditions and Supplementary General Conditions are repeated in other Sections of the Specifications, it is merely intended to qualify or to call particular attention to them. It is not intended that any other parts of the General Conditions and Supplementary General Conditions shall be assumed to be omitted if not repeated therein. This Section applies equally and specifically to all Contractors supplying labor and/or equipment and/or materials as required under each Section of this Division. Where conflicts exist between the drawings and the specifications or between this section of the specifications and other sections, the more stringent or higher cost option shall apply.

1.3 INTENT

- A. It is the intent of the Specifications and Drawings to call for finished work, tested and ready for operation. Provide all parts necessary for the intended use, fully complete and operational, and installed in professional manner in accordance with the design intent.
- B. Any apparatus, appliance, material or work not shown on drawings but mentioned in the specifications, or vice versa, or any incidental accessories necessary to make the work complete and ready for operation as determined by good trade practice even if not particularly specified, shall be furnished, delivered and installed under their respective Divisions without any additional expense to the Owner.
- C. Minor details not usually shown or specified but necessary for proper installation and operation shall be included in the work as though they were hereinafter shown or specified.
- D. Work under each Section shall include giving written notice to the Owner and Engineer of any materials or apparatus believed inadequate or unsuitable; in violation of laws, ordinances, rules or regulations of authorities having jurisdiction; and any necessary items of work omitted. In the absence of such written notice, it is mutually agreed that work under each Section includes the cost of all required items for the accepted, satisfactory functioning of the entire system without extra compensation.

1.4 DEFINITIONS

- A. "Approved equal" also known as "alternative" mean any product which in the opinion of the Engineer is equal in quality, arrangement, appearance, and performance to the product specified.
- B. Directed: Terms such as "directed," "requested," "authorized," "selected," "approved," "required," and "permitted" mean "directed by the Engineer," "requested by the Engineer," and similar phrases.
- C. "Finished" refers to all rooms and areas to be specified to receive architectural treatment as indicated on the drawings. All rooms and areas not covered, including underground tunnels and areas above ceilings shall be considered not finished, unless otherwise noted.
- D. "Furnish" or "supply" shall mean purchase, deliver to, and off-load at the job site, ready to be installed including where appropriate all necessary interim storage and protection.
- E. Indicated: The term "indicated" refers to graphic representations, notes, or schedules on the Drawings, other paragraphs or schedules in the Specifications, and similar requirements in the Contract Documents. Where terms such as "shown," "noted," "scheduled," and "specified" are used, it is to help the reader locate the reference; no limitation on location is intended.
- F. "Install" shall mean set in place complete with all mounting facilities and connections as necessary ready for normal use or service.
- G. No Exceptions Taken – reviewed and determined to be in general conformance with contract documents.
- H. "Product" shall mean any item of equipment, material, fixture, apparatus, appliance or accessory installed under this Division.
- I. "Provide" shall mean furnish (or supply) and install as necessary.
- J. Regulation: The term "Regulations" includes laws, ordinances, statutes, and lawful orders issued by authorities having jurisdiction, as well as rules, conventions, and agreements within the construction industry that control performance of the Work.
- K. Remove: The term "remove" means "to disconnect from its present position, remove from the premises and to dispose of in a legal manner."
- L. Special Warranties: The term "Special Warranties" are written warranties required by or incorporated in the Contract Documents, either to extend time limits provided by standard warranties or to provide greater rights for the Owner.
- M. Standard Product Warranties: The term "Standard Product Warranties" are preprinted written warranties published by individual manufacturers for particular products and are specifically endorsed by the manufacturer to the Owner.
- N. "Subcontractor" means specifically the subcontractor working under this Division. Other Contractors are specifically designated "Plumbing Subcontractor", "General Contractor" and so on. Note: Take care to ascertain limits of responsibility for connecting equipment which requires connections by two or more trades.

- O. Substitutions: Requests for changes in products, materials, equipment, and methods of construction proposed by the Contractor are considered requests for "substitutions."
- P. "Wiring" shall mean cable assembly, raceway, conductors, fittings and any other necessary accessories to make a complete wiring system.

1.5 CONTRACT DOCUMENTS

- A. The two dimensional drawings govern the construction. They show the design intent and are part of the Contract Documents. BIM models are not part of contract documents. They are developed for convenience only.
- B. Drawings are diagrammatic and indicate the general arrangement of systems and work included in the Contract. Consult the Architectural Drawings and Details for exact location of fixtures and equipment; where same are not definitely located, obtain this information from the Architect. (Do not scale the drawings)
- C. Work under each Section shall closely follow Drawings in layout of work; check Drawings of other Divisions to verify spaces in which work will be installed. Maintain maximum headroom; where space conditions appear inadequate, Owner and Engineer shall be notified before proceeding with installations.
- D. The Owner may, without extra charge, make reasonable modifications in the layout as needed to prevent conflict with work of other trades and/or for proper execution of the work.

1.6 DISCREPANCIES IN DOCUMENTS

- A. Where variances occur between the Drawings and Specifications or within either of the Documents, the item or arrangement of better quality, shall be included in the Contract price. The Owner and Engineer shall decide on the item and the manner in which the work shall be installed.
- B. Where Drawings or Specifications conflict or are unclear, submit clarification request in writing before Award of Contract. Otherwise, Architect's interpretation of Contract Documents shall be final, and no additional compensation shall be permitted due to discrepancies or un-clarities thus resolved.
- C. Where Drawings or Specifications do not coincide with manufacturers' recommendations or with applicable codes and standards, submit clarification request in form of an RFI before installation. Otherwise, make changes in installed work required for compliance with manufacturer instructions or codes and standards within Contract Price.
- D. Where insufficient information exists in the documents to precisely describe a certain component or subsystem, or the routing of a component or its coordination with other building elements, where notification required by Paragraph (B) above has not been submitted, provide the specific component or subsystem with all parts necessary for the intended use, fully complete and operational, and installed in professional manner either concealed or exposed in accordance with the design intent.
- E. Where discrepancies exist between the mechanical, plumbing, fire protection, and electrical drawings in regards to what trade owns disconnects or starters, the discrepancy shall be brought to the Architect's attention in accordance with paragraph (B) above. If the scope is not resolved prior to the Award of Contract, Division 26 shall provide such items.

1.7 SURVEYS AND MEASUREMENTS

- A. Before submitting the Bid, the Contractors shall visit the site and become thoroughly familiar with all existing conditions under which work will be installed. This Contract includes all modifications of existing systems required for the installation of new equipment. This Contract includes all necessary offsets, transitions and modifications required to install all new equipment in existing spaces. All new and existing equipment and systems shall be fully operational under this Contract before the job is considered complete. The Contractors shall be held responsible for any assumptions made, any omissions or errors made as a result of their failure to become fully familiar with the existing conditions at the site and the Contract Documents.
- B. The Contractor shall base all measurements, both horizontal and vertical, from established bench marks. All work shall agree with these established lines and levels. Verify all measurements at the site and check the correctness of same as related to the work.
- C. Should the Contractor discover any discrepancies between actual measurements and those indicated which prevent following good practice or which interfere with the intent of the Drawings and Specifications, the Engineer will be notified and work will not proceed until instructions from the Engineer are received.

1.8 CODES AND STANDARDS

- A. Reference Standard Compliance
 - 1. Where equipment or materials are specified to conform to industry and technical society reference standards of the organizations such as American National Standards Institute (ANSI), American Society for Testing and Materials (ASTM), National Electrical Manufacturers Association (NEMA), and Underwriters Laboratories Inc. (UL), submit proof of such compliance. The label or listing by the specified organization will be acceptable evidence of compliance.
 - 2. Independent Testing Organization Certificate: In lieu of the label or listing indicated above, submit a certificate from an independent testing organization, competent to perform testing, and approved by the Engineer. The certificate shall state that the item has been tested in accordance with the specified organization's test methods and that the item complies with the specified organization's reference standard.
- B. Wherever Codes and/ or standards are mentioned in these specifications, the latest applicable edition or revision of the local building or life safety code shall be followed.
- C. The following Standards shall be used where referenced by the following abbreviations:

AABC	Associated Air Balance Council
ACGIH	American Conference of Governmental Industrial Hygienists
ADC	Air Diffusion Council
AGA	American Gas Association
AIA	American Institute of Architects
AMCA	Air Moving and Conditioning Association
ANSI	American National Standards Institute
API	American Petroleum Institute
ARI	Air Conditioning and Refrigeration Institute
ASHRAE	American Society of Heating, Refrigerating and Air Conditioning Engineers
ASME	American Society of Mechanical Engineers
ASPE	American Society of Plumbing Engineers
ASSE	American Society of Sanitary Engineers

ASTM	American Society of Testing and Materials
AWS	American Welding Society
AWWA	American Water Works Association
CGA	Compressed Gas Association
CSA	Canadian Standards Association
CISPI	Cast Iron Soil Pipe Institute
EJMA	Expansion Joint Manufacturing Association
EPA	Environmental Protection Agency
FM	Factory Mutual
FSSC	Federal Specification
HIS	Hydraulic Institute Standards
IEEE	Institute of Electrical and Electronics Engineers
IRI	Industrial Risk Insurers
ISO	Insurance Services Office
MCAA	Mechanical Contractors Association of America
NBS	National Bureau of Standards
NEBB	National Environmental Balancing Bureau
NEMA	National Electrical Manufacturers Association
NFPA	National Fire Protection Association
NOFI	National Oil Fuel Institute
NSC	National Safety Council
NSF	National Sanitation Foundation
OSHA	Occupational Safety and Health Administration
PDI	Plumbing and Drainage Institute
SBI	Steel Boiler Industry (Division of Hydronics Institute)
SMACNA	Sheet Metal and Air Conditioning Contractors National Association
STI	Steel Tank Institute
UL	Underwriters' Laboratories

- D. All materials furnished and all work installed shall comply with the rules and recommendations of the NFPA, the requirements of the local utility companies, the recommendations of the fire insurance rating organization having jurisdiction and the requirements of all Governmental departments having jurisdiction.
- E. The Contractor shall include in the work, without extra cost to the Owner, any labor, materials, services, apparatus and Drawings in order to comply with all applicable laws, ordinances, rules and regulations, whether shown on Drawings and/or specified or not.

1.9 PERMITS AND FEES

- A. The Contractor shall give all necessary notices, obtain all permits; and pay all Government and State sales taxes and fees where applicable, and other costs, including utility connections or extensions in connection with the work, file all necessary Drawings, prepare all documents and obtain all necessary approvals of all Governmental and State departments having jurisdiction, obtain all required certificates of inspection for his work, and deliver a copy to the Owner and Engineer before request for acceptance and final payment for the work.

1.10 EQUIPMENT EQUIVALENTS AND SUBSTITUTIONS

- A. Certain manufacturers of material, apparatus or appliances are indicated in the drawings and specifications for this project. These items have been used as the basis of design, and as a convenience in fixing the minimum standard of quality, finish and design that is required. If the Contractors uses an "approved equal" alternative to the basis of design, and if the features of that alternative have an impact on other components of the Project, the Contractor shall include the necessary adjustments in those components, whether for

architectural, structural, mechanical, electrical, fire protection, or any other elements, plus any adjustments for difference in performance.

- B. Where no specific make of material, apparatus or appliance is mentioned, any first-class product made by a reputable manufacturer may be submitted for Architect and Engineer review.
- C. Where the Contractor proposes to use an item that is different from the basis of design in the Drawings and specifications, and that will require the redesign of the structure, partitions, foundations, piping, wiring or any other component of the mechanical, electrical, or architectural layout, the Contractor shall provide the necessary redesign of those components.
- D. Where the Contractor proposes to deviate (provide an equivalent or request for substitution) from the basis of design scheduled equipment or materials as hereinafter specified or shown on the drawings, they are required to submit a requested for substitution in writing. The Contractor shall state in their request whether it is a substitution, equivalent or a non approved equivalent to that specified and the amount of credit or extra cost involved. A copy of said request shall be included in the Base Bid with manufacturer's equipment cuts. The Base Bid shall be based on using the materials and equipment as specified with no exceptions.
- E. If an alternative or substitute item results in a difference in quantity and arrangement of structure, piping, ductwork, valves, pumps, insulation, wiring, conduit, and equipment from that specified or indicated on the Drawings, furnish and install any such additional equipment required by the system, at no additional cost to the Owner including any costs added to other trades due to the equivalent change from the basis of design detailed in the drawings or included within the specifications.

1.11 SUBMITTAL PROCEDURES

- A. Provide Submittals in accordance with the requirements of Division 01 and as indicated in the following.
- B. Coordination: Coordinate preparation and processing of submittals with performance of construction activities. Transmit each submittal sufficiently in advance of performance of related construction activities to avoid delay.
 - 1. Coordinate each submittal with fabrication, purchasing, testing, delivery, other submittals and related activities that require sequential activity.
 - 2. Coordinate transmittal of different types of submittals for related elements of the Work so processing will not be delayed by the need to review submittals concurrently for coordination. The Engineer reserves the right to withhold action on a submittal requiring coordination with other submittals until related submittals are received.
- C. Processing: Allow sufficient review time so that installation will not be delayed as a result of the time required to process submittals, including time for resubmittals.
 - 1. Allow ten business days for initial review. Allow additional time if processing must be delayed to permit coordination with subsequent submittals. The Engineer will promptly advise the Contractor when a submittal being processed must be delayed for coordination.
 - 2. If an intermediate submittal is necessary, process the same as the initial submittal.
 - 3. Allow ten business days for reprocessing each submittal.

4. No extension of Contract Time will be authorized because of failure to transmit submittals to the Engineer sufficiently in advance of the Work to permit processing.
- D. Submittal Preparation: Place a permanent label or title block on each submittal for identification. Indicate the name of the entity that prepared each submittal on the label or title block. Submittals shall be arranged in order of specification sections.
 1. Include the following information on the label for processing and recording action taken.
 - a. Project name.
 - b. Date.
 - c. Name and address of Engineer.
 - d. Name and address of Contractor.
 - e. Name and address of subcontractor.
 - f. Name and address of supplier.
 - g. Name of manufacturer.
 - h. Number, title and paragraph of appropriate Specification Section.
 - i. Drawing number and detail references, as appropriate.
- E. Submittal Transmittal: Package each submittal appropriately for transmittal and handling. Transmit each submittal from Contractor to Engineer using a transmittal form. Submittals received from sources other than the Contractor will be returned without action. On the transmittal, record relevant information and requests for data. On the form, or separate sheet, record deviations from Contract Document requirements, including minor variations and limitations. Include Contractor's certification that information complies with Contract Document requirements.
- F. Except for submittals for record, information or similar purposes, the Engineer will review each submittal, mark to indicate action taken, and return promptly. Compliance with specified characteristics is the Contractor's responsibility.
- G. Action Stamp: The Engineer will stamp each submittal with a uniform, self-explanatory action stamp. The stamp will be appropriately marked, to indicate the action taken.

1.12 COORDINATION WITH OTHER DIVISIONS

- A. All work shall be carried out in conjunction with other trades and full cooperation shall be given in order that all work may proceed with a minimum of delay and interference. Particular emphasis is placed on timely installation of major apparatus and furnishing other Contractors, especially the Contractor or Construction Manager, with information as to openings, chases, sleeves, bases, inserts, equipment locations, panels, etc., required by other trades.
- B. The Contractors are required to examine all of the Project Drawings and mutually arrange work so as to avoid interference with the work of other trades. In general, ductwork, HVAC piping, sprinkler piping and drainage lines take precedence over water, gas and electrical conduits. The Engineer shall make final decisions regarding the arrangement of work which cannot be agreed upon by the Contractors.
- C. Where the work of the Contractor will be installed in close proximity to or will interfere with work of other trades, the Contractors will cooperate in working out space conditions to make a satisfactory adjustment.
- D. If the work under a Section is installed before coordinating with other Divisions or Sections or so as to cause interference with work of other Sections, the necessary

changes to correct the condition shall be made by the Contractor causing the interference without extra charge to the Owner.

1.13 QUALITY CONTROL

- A. Service Support: The equipment items shall be supported by service organizations which are reasonably convenient to the equipment installation in order to render satisfactory service to the equipment on a regular and emergency basis during the warranty period of the contract.
- B. Modification of References: In each of the publications referred to herein, consider the advisory provisions to be mandatory, as though the word, "shall" had been substituted for "should" wherever it appears.
- C. Furnish the services of an experienced superintendent who shall be constantly in charge of the installation of the work together with all skilled tradespeople, fitters, metal workers, welders, helpers and laborers required to unload, transfer, erect, connect, adjust, start, operate and test each system.
- D. Unless otherwise specifically indicated on the Drawings or Specifications, all equipment and materials shall be installed with the acceptance of the Engineer and in accordance with the recommendations of the manufacturer. This includes the performance of such tests as the manufacturer recommends.
- E. All labor for installation of plumbing systems shall be performed by experienced, skilled tradespeople under the supervision of a licensed journeyman foreman. All work shall be of a quality consistent with good trade practice and shall be installed in a neat, professional manner. The Engineer reserves the right to reject any work which, in their opinion, has been installed in a substandard, dangerous or unserviceable manner. Replace said work in a satisfactory manner at no extra cost to the Owner.

1.14 SHUTDOWNS

- A. When installation of a new system requires the temporary shutdown of an existing operating system, the connection of the new system shall be performed at such time as designated by the Owner.
- B. The Engineer and the Owner shall be notified in writing of the estimated duration of the shutdown period at least ten (10) days in advance of the date the work is to be performed.
- C. Work shall be arranged for continuous performance whenever possible. Provide all necessary labor, including overtime if required, to assure that existing operating services will be shut down only during the time actually required to make necessary connections.

1.15 PROTECTION OF MATERIALS AND EQUIPMENT

- A. Work under each Section shall include protecting the work and material of all other Sections from damage by work or tradespeople and shall include making good all damage thus caused.
- B. The Contractor shall be responsible for work and equipment until the facility has been accepted by the Owner. Protect work against theft, injury or damage and carefully store material and equipment received on site which is not immediately installed. Close open

ends of work with temporary covers or plugs during construction to prevent entry of foreign material.

- C. Work under each Section includes receiving, unloading, uncrating, storing, protecting, setting in place and completely connecting equipment supplied under each Section. Work under each Section shall also include exercising special care in handling and protecting equipment and fixtures, and shall include the cost of replacing any of the equipment and fixtures which are missing or damaged.
- D. Equipment and material stored on the job site shall be protected from the weather, vehicles, dirt and/or damage by tradespeople or machinery. Insure that all electrical or absorbent equipment or material is protected from moisture during storage.

1.16 ADJUSTING AND TESTING

- A. After all the equipment and accessories to be furnished are in place, they shall be put in final adjustment and subjected to such operating tests so as to assure the Engineer that they are in proper adjustment and in satisfactory, permanent operating condition.
- B. Where requested by the Engineer, a factory-trained service representative shall inspect the installation and assist in the initial startup and adjustment to the equipment. The period of these services shall be for such time as necessary to secure proper installation and adjustments. After the equipment is placed in permanent operation, the service representative shall supervise the initial operation of the equipment and instruct personnel responsible for operation and maintenance of the equipment. The service representative shall notify the Contractor in writing that the equipment was installed according to manufacturer's recommendations and is operating as intended by the manufacturer.

1.17 CLEANING

- A. The Contractor shall thoroughly clean all equipment of all foreign substances, oils, dust, dirt, etc., inside and out before final acceptance by the Engineer.
- B. If any part of a system should be stopped or damaged by any foreign matter after being placed in operation, the system shall be disconnected, cleaned and reconnected wherever necessary to locate and/or remove obstructions. Any work damaged in the course of removing obstructions shall be repaired or replaced when the system is reconnected at no additional cost to the Owner.
- C. During the course of construction, all pipes shall be capped in an acceptable manner to insure adequate protection against the entrance of foreign matter.
- D. Upon completion of all work under the Contract, remove from the premises all rubbish, debris and excess materials left over from his work. Any oil or grease stains on floor areas shall be removed and floor areas left clean.
- E. Complete the following cleaning operations before requesting inspection for Certification of Substantial Completion.
 1. Remove labels that are not permanent labels.
 2. Clean transparent materials, including mirrors and glass in doors and windows. Remove glazing compound and other substances that are noticeable vision-obscuring materials. Replace chipped or broken glass and other damaged transparent materials.

3. Clean exposed exterior and interior hard-surfaced finishes to a dust-free condition, free of stains, films and similar foreign substances. Restore reflective surfaces to their original reflective condition. Leave concrete floors broom clean. Vacuum carpeted surfaces.
4. Wipe surfaces of equipment. Remove excess lubrication and other substances.

F. Comply with regulations of authorities having jurisdiction and safety standards for cleaning. Do not burn waste materials. Do not bury debris or excess materials on the Owner's property. Do not discharge volatile, harmful or dangerous materials into drainage systems. Remove and dispose of ALL waste materials, packaging material, skids etc. from the site and dispose of in a lawful manner in accordance with municipal, state and federal regulations.

G. Where extra materials of value remaining after completion of associated Work have become the Owner's property, arrange for disposition of these materials as directed.

1.18 OPERATING AND MAINTENANCE

- A. Upon completion of all work and tests, furnish the necessary skilled labor and helpers for operating his system and equipment for a period specified under each applicable Section of this Division. During this period, instruct the Owner or the Owner's representative in the operation, adjustment and maintenance of all equipment furnished. The Contractor shall give at least seven (7) days' notice to the Owner and the Engineer in advance of this period.
- B. The Contractor shall physically demonstrate procedures for all routine maintenance of all equipment furnished under each respective Section to assure accessibility to all devices.
- C. Refer to individual trade Sections for any other particular requirements related to operating instructions.

1.19 RECORD DRAWINGS

- A. General: Do not use record documents for construction purposes; protect from deterioration and loss in a secure, fire-resistive location; provide access to record documents for the Engineer's reference during normal working hours.
- B. Record Drawings: Maintain a clean, undamaged set of blue or black line white-prints of Contract Drawings and Shop Drawings. Mark the set to show the actual installation where the installation varies substantially from the Work as originally shown. Mark whichever drawing is most capable of showing conditions fully and accurately; where Shop Drawings are used, record a cross-reference at the corresponding location on the Contract Drawings.

1.20 WARRANTIES AND BONDS

- A. The following general administrative and procedural requirements for warranties and bonds required by the Contract Documents, including manufacturers' standard warranties on products and special warranties are to be included:
 1. General close-out requirements included in Division 01.
 2. Specific requirements for warranties for the Work and products and installation that are specified to be warranted, are included in the individual Sections of Divisions-02 through -50.
 3. Certifications and other commitments and agreements for continuing services to Owner are specified elsewhere in the Contract Documents.

- B. Disclaimers and Limitations: Manufacturer's disclaimers and limitations on product warranties do not relieve the Contractor of the warranty on the Work that incorporates the products, nor does it relieve suppliers, manufacturers, and subcontractors required to countersign special warranties with the Contractor.
- C. Separate Prime Contracts: Each prime Contractor is responsible for warranties related to its own Contract.

1.21 WARRANTY REQUIREMENTS

- A. Related Damages and Losses: When correcting warranted Work that has failed, remove and replace other Work that has been damaged as a result of such failure or that must be removed and replaced to provide access for correction of warranted Work.
- B. Reinstatement of Warranty: When Work covered by a warranty has failed and been corrected by replacement or rebuilding, reinstate the warranty by written endorsement. The reinstated warranty shall be equal to the original warranty with an equitable adjustment for depreciation.
- C. Replacement Cost: Upon determination that Work covered by a warranty has failed, replace or rebuild the Work to an acceptable condition complying with requirements of Contract Documents. The Contractor is responsible for the cost of replacing or rebuilding defective Work regardless of whether the Owner has benefited from use of the Work through a portion of its anticipated useful service life.
- D. Owner's Recourse: Written warranties made to the Owner are in addition to implied warranties, and shall not limit the duties, obligations, right and remedies otherwise available under the law, nor shall warranty periods be interpreted as limitations on time in which the Owner can enforce such other duties, obligations, rights, or remedies.
- E. Rejection of Warranties: The Owner reserves the right to reject warranties and to limit selections to products with warranties not in conflict with requirements of the Contract Documents.
- F. The Owner reserves the right to refuse to accept Work for the Project where a special warranty, certification, or similar commitment is required on such Work or part of the Work, until evidence is presented that entities required to countersign such commitments are willing to do so.
- G. Submit written warranties to the Engineer prior to the date certified for Substantial Completion. If the Engineer's Certificate of Substantial Completion designates a commencement date for warranties other than the date of Substantial Completion for the Work, or a designated portion of the Work, submit written warranties upon request of the Engineer.
- H. When a designated portion of the Work is completed and occupied or used by the Owner, by separate agreement with the Contractor during the construction period, submit properly executed warranties to the Engineer within fifteen days of completion of that designated portion of the Work.
- I. When a special warranty is required to be executed by the Contractor, or the Contractor and a subcontractor, supplier or manufacturer, prepare a written document that contains appropriate terms and identification, ready for execution by the required parties. Submit a draft to the Owner through the Engineer for approval prior to final execution.

1.22 GUARANTEES

- A. The Contractor shall guarantee all material and installation quality under these Specifications and the Contract for a period of one (1) year from the date of final acceptance by Owner. During this guarantee period, all defects developing through faulty equipment, materials or installation quality shall be corrected or replaced immediately by this Contractor without expense to the Owner. Such repairs or replacements shall be made to the Engineer's satisfaction.
- B. Contractor shall provide name, address, and phone number of all contractors and subcontractors and associated equipment they provided.

1.23 PROJECT CLOSE-OUT

- A. Submit specific warranties, quality bonds, maintenance agreements, final certifications and similar documents in accordance with Division 01.
- B. Deliver tools, spare parts, extra stock, and similar items.
- C. Complete start-up testing of systems, including measuring and documenting all required startup checklist requirements documented in installation and maintenance instructions by the equipment manufacturer, and instruction of the Owner's operating and maintenance personnel. Discontinue or change over and remove temporary facilities from the site, along with construction tools, mock-ups, and similar elements.
- D. Complete final clean up requirements, including touch-up painting. Touch-up and otherwise repair and restore marred exposed finishes.
- E. Field Observation Procedures: On receipt of a request for an Engineers Field Observation, the Engineer will advise the Contractor of unfulfilled requirements. The Engineer will advise the Contractor of construction that must be completed or corrected before the certificate will be issued. Contractor shall submit written response to each corrective item including specific photos prior to final Engineering inspection.
 1. The Engineer will repeat the Field Observation when requested and assured that the Work has been substantially completed.
 2. Results of the completed list of unfulfilled items will form the basis of requirements for final acceptance.

END OF SECTION

SECTION 23 23 00

REFRIGERANT PIPING

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Piping.
- B. Refrigerant.

1.2 REFERENCE STANDARDS (follow the most currently adopted amended version)

- A. ASHRAE Std 15 - Safety Standard for Refrigeration Systems
- B. ASME B16.22 - Wrought Copper and Copper Alloy Solder-Joint Pressure Fittings
- C. ASME B16.26 - Cast Copper Alloy Fittings for Flared Copper Tubes
- D. ASME B31.5 - Refrigeration Piping and Heat Transfer Components

1.3 SUBMITTALS

- A. See Division 01 - General Requirements.
- B. Product Data: Provide general assembly of specialties, including manufacturer's catalogue information. Provide manufacturers catalog data including load capacity.
- C. Test Reports: Indicate results of leak test, acid test.
- D. Manufacturer's Installation Instructions: Indicate support, connection requirements, and isolation for servicing.
- E. Submit welders certification of compliance with ASME BPVC-IX.
- F. Project Record Documents: Record exact locations of equipment and refrigeration accessories on record drawings.

1.4 QUALITY ASSURANCE

- A. Installer Qualifications: Company specializing in performing the type of work specified in this section, with minimum 10 years of documented experience.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Deliver and store piping and specialties in shipping containers with labeling in place.
- B. Protect piping and specialties from entry of contaminating material by leaving end caps and plugs in place until installation.

PART 2 PRODUCTS

2.1 REGULATORY REQUIREMENTS

- A. Conform to ASME B31.9 for installation of piping system.

2.2 PIPING

- A. Copper Tube: ASTM B280, H58 hard drawn or O60 soft annealed.
 - 1. Fittings: ASME B16.22 wrought copper.
 - 2. Joints: Braze, AWS A5.8M/A5.8 BCuP silver/phosphorus/copper alloy.
- B. Copper Tube to 7/8 inch OD: ASTM B88 , Type K (A), annealed.
 - 1. Fittings: ASME B16.26 cast copper.
 - 2. Joints: Flared.

2.3 REFRIGERANT

- A. Refrigerant: Provide the same refrigerants as the existing systems.

PART 3 EXECUTION

3.1 PREPARATION

- A. Ream pipe and tube ends. Remove burrs. Bevel plain end ferrous pipe.
- B. Remove scale and dirt on inside and outside before assembly.
- C. Prepare piping connections to equipment with flanges or unions.

3.2 INSTALLATION

- A. Install refrigeration specialties in accordance with manufacturer's instructions.
- B. Flood piping system with nitrogen when brazing.
- C. Follow ASHRAE Std 15 procedures for charging and purging of systems and for disposal of refrigerant.
- D. Fully charge completed system with refrigerant after testing.

3.3 FIELD QUALITY CONTROL

- A. See Division 01 - General Requirements
- B. Test refrigeration system in accordance with ASME B31.5.
- C. Pressure test system with dry nitrogen to 200 psi. Perform final tests at 27 inches vacuum and 200 psi using halide torch. Test to no leakage.

END OF SECTION

REFRIGERANT PIPING

SECTION 23 31 00
HVAC DUCTS AND CASINGS

PART 1 GENERAL

1.1 SUMMARY

- A. Section Includes:
 - 1. Duct Materials.
 - 2. Ductwork fabrication.
- B. Related Sections:
 - 1. Section 23 04 00 – General Conditions for Mechanical Trades

1.2 REFERENCES

- A. ASTM International:
 - 1. ASTM A36/A36M - Standard Specification for Carbon Structural Steel.
 - 2. ASTM A90/A90M - Standard Test Method for Weight Mass of Coating on Iron and Steel Articles with Zinc or Zinc-Alloy Coatings.
 - 3. ASTM A240/A240M - Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications.
 - 4. ASTM A666 - Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.
 - 5. ASTM A568/A568M - Standard Specification for Steel, Sheet, Carbon, and High-Strength, Low-Alloy, Hot-Rolled and Cold-Rolled, General Requirements for.
 - 6. ASTM A653/A653M - Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process.
 - 7. ASTM A1008/A1008M - Standard Specification for Steel, Sheet, Cold-Rolled, Carbon, Structural, High-Strength Low-Alloy and High-Strength Low-Alloy with Improved Formability.
 - 8. A1011/A1011M-07 Standard Specification for Steel, Sheet and Strip, Hot-Rolled, Carbon, Structural, High-Strength Low-Alloy, High-Strength Low-Alloy with Improved Formability, and Ultra-High Strength
 - 9. ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials.
- B. National Fire Protection Association:
 - 1. NFPA 90A - Standard for the Installation of Air Conditioning and Ventilating Systems.
 - 2. NFPA 90B - Standard for the Installation of Warm Air Heating and Air Conditioning Systems.
 - 3. NFPA 96 - Standard for Ventilation Control and Fire Protection of Commercial Cooking Operations.
- C. Sheet Metal and Air Conditioning Contractors:
 - 1. SMACNA - Fibrous Glass Duct Construction Standards.
 - 2. SMACNA - HVAC Air Duct Leakage Test Manual.
 - 3. SMACNA - HVAC Duct Construction Standard - Metal and Flexible.

- D. Underwriters Laboratories Inc.:
 - 1. UL 181 - Factory-Made Air Ducts and Connectors.

1.3 SUBMITTALS

- A. Section 01 33 00 - Submittal Procedures: Submittal procedures.

1.4 CLOSEOUT SUBMITTALS

- A. Section 01 70 00 - Execution and Closeout Requirements: Closeout procedures.
- B. Project Record Documents: Record actual locations of ducts and duct fittings. Record changes in fitting location and type. Show additional fittings used.

1.5 QUALITY ASSURANCE

- A. Perform Work in accordance with SMACNA - HVAC Duct Construction Standards - Metal and flexible.

1.6 QUALIFICATIONS

- A. Manufacturer: Company specializing in manufacturing products specified in this section with minimum three years experience.
- B. Installer: Company specializing in performing Work of this section with three years experience.

1.7 PRE-INSTALLATION MEETINGS

- A. Section 01 30 00 - Administrative Requirements: Pre-installation meeting.

1.8 ENVIRONMENTAL REQUIREMENTS

- A. Section 01 60 00 - Product Requirements.
- B. Do not install duct sealant when temperatures are less than those recommended by sealant manufacturers.

1.9 FIELD MEASUREMENTS

- A. Verify field measurements prior to fabrication.

1.10 WARRANTY

- A. Section 01 70 00 - Execution and Closeout Requirements: Product warranties and product bonds.

PART 2 PRODUCTS

2.1 DUCT MATERIALS

- A. Galvanized Steel Ducts: ASTM A653/A653M galvanized steel sheet, lock-forming quality, having G90 zinc coating of in conformance with ASTM A90/A90M.
- B. Fasteners: Rivets, bolts, or sheet metal screws.

2.2 TRANSVERSE DUCT CONNECTION SYSTEM

- A. Manufacturers:
 1. United McGill
 2. Semco
 3. ACME
 4. Nufab
 5. Substitutions: Section 01 60 00 - Product Requirements.
- B. Product Description: Interlocking angle and duct edge connection system with sealant, gasket, cleats, and corner clips.

2.3 DUCTWORK FABRICATION

- A. Fabricate and support rectangular ducts in accordance with SMACNA HVAC Duct Construction Standards - Metal and Flexible and [as indicated on Drawings]. Provide duct material, gages, reinforcing, and sealing for operating pressures indicated.
- B. TDC connections on all ductwork where any dimension exceeds 12 inches. Slip and drive connection acceptable on duct sizes less than 12" x 12".
- C. Construct T's, bends, and elbows with minimum radius 1-1/2 times centerline duct width. Where not possible and where rectangular elbows are used, provide turning vanes. Where acoustical lining is indicated, furnish turning vanes of perforated metal with glass fiber insulation.
- D. Seal joints between duct sections and duct seams with welds, gaskets, mastic adhesives, mastic plus embedded fabric systems.
 1. Sealants, Mastics: Conform to UL 181A. Provide products bearing appropriate UL 181A markings.
 2. Do not provide sealing products not bearing UL approval markings.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Section 01 30 00 - Administrative Requirements: Coordination and project conditions.
- B. Verify sizes of equipment connections before fabricating transitions.

3.2 INSTALLATION

- A. Install and seal ducts in accordance with SMACNA HVAC Duct Construction Standards - Metal and Flexible.
- B. During construction, install temporary closures of metal or taped polyethylene on open ductwork to prevent construction dust from entering ductwork system.
- C. For outdoor ductwork, protect ductwork, ductwork supports, linings and coverings from weather.

END OF SECTION

SECTION 26 04 00

GENERAL CONDITIONS FOR ELECTRICAL TRADES

PART 1 GENERAL

1.1 RELATED REQUIREMENTS

- A. Drawings and general provisions of Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.
- B. This section applies to all sections of Division 26, "Electrical"

1.2 DESCRIPTION

- A. The General Conditions and Supplementary General Conditions are a part of this Division and are to be considered a part of this Contract.
- B. Where items of the General Conditions and Supplementary General Conditions are repeated in other Sections of the Specifications, it is merely intended to qualify or to call particular attention to them. It is not intended that any other parts of the General Conditions and Supplementary General Conditions shall be assumed to be omitted if not repeated therein. This Section applies equally and specifically to all Contractors supplying labor and/or equipment and/or materials as required under each Section of this Division, (Division 27 and Division 28). Where conflicts exist between the drawings and the specifications or between this section of the specifications and other sections, the more stringent or higher cost option shall apply.

1.3 INTENT

- A. It is the intent of this Section of the Specifications to establish a standard of quality and performance characteristics for basic materials and installation methods used in building electrical (communications and electronic safety and security) systems.
- B. This contract is for all labor, materials and equipment required for installation. The system shall be complete and finished in all respects, tested and ready for operation. Work shall include calibration of equipment with factory settings. All materials, equipment and apparatus shall be new and of first class quality.
- C. Minor details not usually shown or specified but necessary for proper installation and operation shall be included in the work as though they were hereinafter shown or specified.
- D. Work under each Section shall include giving written notice to the Owner and Engineer of any materials or apparatus believed inadequate or unsuitable; in violation of laws, ordinances, rules or regulations of authorities having jurisdiction; and any necessary items of work omitted. In the absence of such written notice, it is mutually agreed that work under each Section has included the cost of all required items for the accepted, satisfactory functioning of the entire system without extra compensation.

1.4 DEFINITIONS

- A. "Approved equal" also known as "alternative" mean any product which in the opinion of the Engineer is equal in quality, arrangement, appearance, and performance to the product specified.
- B. Directed: Terms such as "directed," "requested," "authorized," "selected," "approved," "required," and "permitted" mean "directed by the Engineer," "requested by the Engineer," and similar phrases.
- C. "Finished" refers to all rooms and areas to be specified to receive architectural treatment as indicated on the drawings. All rooms and areas not covered, including underground tunnels and areas above ceilings shall be considered not finished, unless otherwise noted.
- D. "Furnish" or "supply" shall mean purchase, deliver to, and off-load at the job site, ready to be installed including where appropriate all necessary interim storage and protection.
- E. Indicated: The term "indicated" refers to graphic representations, notes, or schedules on the Drawings, other paragraphs or schedules in the Specifications, and similar requirements in the Contract Documents. Where terms such as "shown," "noted," "scheduled," and "specified" are used, it is to help the reader locate the reference; no limitation on location is intended.
- F. "Install" shall mean set in place complete with all mounting facilities and connections as necessary ready for normal use or service.
- G. No Exceptions Taken – reviewed and determined to be in general conformance with contract documents.
- H. "Product" shall mean any item of equipment, material, fixture, apparatus, appliance or accessory installed under this Division.
- I. "Provide" shall mean furnish (or supply) and install as necessary.
- J. Regulation: The term "Regulations" includes laws, ordinances, statutes, and lawful orders issued by authorities having jurisdiction, as well as rules, conventions, and agreements within the construction industry that control performance of the Work.
- K. Remove: The term "remove" means "to disconnect from its present position, remove from the premises and to dispose of in a legal manner."
- L. Special Warranties: The term "Special Warranties" are written warranties required by or incorporated in the Contract Documents, either to extend time limits provided by standard warranties or to provide greater rights for the Owner.
- M. Standard Product Warranties: The term "Standard Product Warranties" are preprinted written warranties published by individual manufacturers for particular products and are specifically endorsed by the manufacturer to the Owner.
- N. "Subcontractor" means specifically the subcontractor working under this Division. Other Contractors are specifically designated "Plumbing Subcontractor", "General Contractor" and so on. Note: Take care to ascertain limits of responsibility for connecting equipment which requires connections by two or more trades.

- O. Substitutions: Requests for changes in products, materials, equipment, and methods of construction proposed by the Contractor are considered requests for "substitutions."
- P. "Wiring" shall mean cable assembly, raceway, conductors, fittings and any other necessary accessories to make a complete wiring system.

1.5 CONTRACT DOCUMENTS

- A. The two dimensional drawings govern the construction. They show the design intent and are part of the Contract Documents. BIM models are not part of contract documents. They are developed for convenience only.
- B. Drawings are diagrammatic and indicate the general arrangement of systems and work included in the Contract. Consult the Architectural Drawings and Details for exact location of fixtures and equipment; where same are not definitely located, obtain this information from the Architect. (Do not scale the drawings)
- C. Work under each Section shall closely follow Drawings in layout of work; check Drawings of other Divisions to verify spaces in which work will be installed. Maintain maximum headroom; where space conditions appear inadequate, Owner and Engineer shall be notified before proceeding with installations.
- D. The Owner may, without extra charge, make reasonable modifications in the layout as needed to prevent conflict with work of other trades and/or for proper execution of the work.

1.6 DISCREPANCIES IN DOCUMENTS

- A. Where variances occur between the Drawings and Specifications or within either of the Documents, the item or arrangement of better quality, shall be included in the Contract price. The Owner and Engineer shall decide on the item and the manner in which the work shall be installed.
- B. Where Drawings or Specifications conflict or are unclear, submit clarification request in writing before Award of Contract. Otherwise, Architect's interpretation of Contract Documents shall be final, and no additional compensation shall be permitted due to discrepancies or un-clarities thus resolved.
- C. Where Drawings or Specifications do not coincide with manufacturers' recommendations or with applicable codes and standards, submit clarification request in form of an RFI before installation. Otherwise, make changes in installed work required for compliance with manufacturer instructions or codes and standards within Contract Price.
- D. Where insufficient information exists in the documents to precisely describe a certain component or subsystem, or the routing of a component or its coordination with other building elements, where notification required by Paragraph (B) above has not been submitted, provide the specific component or subsystem with all parts necessary for the intended use, fully complete and operational, and installed in professional manner either concealed or exposed in accordance with the design intent.
- E. Where discrepancies exist between the mechanical, plumbing, fire protection, and electrical drawings in regards to what trade owns disconnects or starters, the discrepancy shall be brought to the Architect's attention in accordance with paragraph (B) above. If the scope is not resolved prior to the Award of Contract, Division 26 shall provide such items.

1.7 SURVEYS AND MEASUREMENTS

- A. Before submitting his Bid, the Contractors shall visit the site and become thoroughly familiar with all existing conditions under which his work will be installed. This Contract includes all modifications of existing systems required for the installation of new equipment. This Contract includes all necessary offsets, transitions and modifications required to install all new equipment in existing spaces. All new and existing equipment and systems shall be fully operational under this Contract before the job is considered complete. The Contractors shall be held responsible for any assumptions he makes, any omissions or errors he makes as a result of his failure to become fully familiar with the existing conditions at the site and the Contract Documents.
- B. The Contractor shall base all measurements, both horizontal and vertical, from established bench marks. All work shall agree with these established lines and levels. Verify all measurements at the site and check the correctness of same as related to the work.
- C. Should the Contractor discover any discrepancies between actual measurements and those indicated which prevent following good practice or which interfere with the intent of the Drawings and Specifications, the Engineer will be notified and work will not proceed until instructions from the Engineer are received.

1.8 CODES AND STANDARDS

- A. Reference Standard Compliance
 - 1. Where equipment or materials are specified to conform to industry and technical society reference standards of the organizations such as American National Standards Institute (ANSI), American Society for Testing and Materials (ASTM), National Electrical Manufacturers Association (NEMA), and Underwriters Laboratories Inc. (UL), submit proof of such compliance. The label or listing by the specified organization will be acceptable evidence of compliance.
 - 2. Independent Testing Organization Certificate: In lieu of the label or listing, indicated above submit a certificate from an independent testing organization, competent to perform testing, and approved by the engineer. The certificate shall state that the item has been tested in accordance with the specified organization's test methods and that the item complies with the specified organization's reference standard.
- B. Wherever Codes and/or Standards are mentioned in these Specifications, the latest applicable edition or revision of the local building or life safety code shall be followed.
- C. The following Standards shall be used where referenced by the following abbreviations:

AABC	Associated Air Balance Council
ACGIH	American Conference of Governmental Industrial Hygienists
ADC	Air Diffusion Council
AGA	American Gas Association
AIA	American Institute of Architects
AMCA	Air Moving and Conditioning Association
ANSI	American National Standards Institute
API	American Petroleum Institute
ARI	Air Conditioning and Refrigeration Institute
ASHRAE	American Society of Heating, Refrigerating and Air Conditioning Engineers
ASME	American Society of Mechanical Engineers
ASPE	American Society of Plumbing Engineers
ASSE	American Society of Sanitary Engineers

ASTM	American Society of Testing and Materials
AWS	American Welding Society
AWWA	American Water Works Association
CGA	Compressed Gas Association
CSA	Canadian Standards Association
CISPI	Cast Iron Soil Pipe Institute
EJMA	Expansion Joint Manufacturing Association
EPA	Environmental Protection Agency
FM	Factory Mutual
FSSC	Federal Specification
HIS	Hydraulic Institute Standards
IEEE	Institute of Electrical and Electronics Engineers
IRI	Industrial Risk Insurers
ISO	Insurance Services Office
MCAA	Mechanical Contractors Association of America
NBS	National Bureau of Standards
NEBB	National Environmental Balancing Bureau
NEMA	National Electrical Manufacturers Association
NFPA	National Fire Protection Association
NOFI	National Oil Fuel Institute
NSC	National Safety Council
NSF	National Sanitation Foundation
OSHA	Occupational Safety and Health Administration
PDI	Plumbing and Drainage Institute
SBI	Steel Boiler Industry (Division of Hydronics Institute)
SMACNA	Sheet Metal and Air Conditioning Contractors National Association
STI	Steel Tank Institute
UL	Underwriters' Laboratories

- D. All materials furnished and all work installed shall comply with the rules and recommendations of the NFPA, the requirements of the local utility companies, the recommendations of the fire insurance rating organization having jurisdiction and the requirements of all Governmental departments having jurisdiction.
- E. The Contractor shall include in the work, without extra cost to the Owner, any labor, materials, services, apparatus and Drawings in order to comply with all applicable laws, ordinances, rules and regulations, whether shown on Drawings and/or specified or not.

1.9 PERMITS AND FEES

- A. The Contractor shall give all necessary notices, obtain all permits; and pay all Government and State sales taxes and fees where applicable, and other costs, including utility connections or extensions in connection with the work, file all necessary Drawings, prepare all documents and obtain all necessary approvals of all Governmental and State departments having jurisdiction, obtain all required certificates of inspection for his work, and deliver a copy to the Owner and Engineer before request for acceptance and final payment for the work.

1.10 EQUIPMENT EQUIVALENTS AND SUBSTITUTIONS

- A. Certain manufacturers of material, apparatus or appliances are indicated in the drawings and specifications for this project. These items have been used as the basis of design, and as a convenience in fixing the minimum standard of quality, finish and design that is required. If the Contractors uses an "approved equal" alternative to the basis of design, and if the features of that alternative have an impact on other components of the Project, the Contractor shall include the necessary adjustments in those components, whether for

architectural, structural, mechanical, electrical, fire protection, or any other elements, plus any adjustments for difference in performance.

- B. Where no specific make of material, apparatus or appliance is mentioned, any first-class product made by a reputable manufacturer may be submitted for Architect and Engineer review.
- C. Where the Contractor proposes to use an item that is different from the basis of design in the Drawings and specifications, and that will require the redesign of the structure, partitions, foundations, piping, wiring or any other component of the mechanical, electrical, or architectural layout, the Contractor shall provide the necessary redesign of those components.
- D. Where the Contractor proposes to deviate (provide an equivalent or request for substitution) from the basis of design scheduled equipment or materials as hereinafter specified or shown on the drawings, they are required to submit a requested for substitution in writing. The Contractor shall state in their request whether it is a substitution, equivalent or a non approved equivalent to that specified and the amount of credit or extra cost involved. A copy of said request shall be included in the Base Bid with manufacturer's equipment cuts. The Base Bid shall be based on using the materials and equipment as specified with no exceptions.
- E. If an alternative or substitute item results in a difference in quantity and arrangement of piping, ductwork, valves, pumps, insulation, wiring, conduit, and equipment from that specified or indicated on the Drawings, the Contractor shall furnish and install any such additional equipment required by the system, at no additional cost to the Owner including any costs added to other trades due to the equivalent change from the basis of design detailed in the drawings or included within the specifications.

1.11 SUBMITTAL PROCEDURES

- A. Provide Submittals in accordance with the requirements of Division 1 and as indicated in the following.
- B. Coordination: Coordinate preparation and processing of submittals with performance of construction activities. Transmit each submittal sufficiently in advance of performance of related construction activities to avoid delay.
 - 1. Coordinate each submittal with fabrication, purchasing, testing, delivery, other submittals and related activities that require sequential activity.
 - 2. Coordinate transmittal of different types of submittals for related elements of the Work so processing will not be delayed by the need to review submittals concurrently for coordination. The Engineer reserves the right to withhold action on a submittal requiring coordination with other submittals until related submittals are received.
- C. Processing: Allow sufficient review time so that installation will not be delayed as a result of the time required to process submittals, including time for resubmittals.
 - 1. Allow two weeks for initial review. Allow additional time if processing must be delayed to permit coordination with subsequent submittals. The Engineer will promptly advise the Contractor when a submittal being processed must be delayed for coordination.
 - 2. If an intermediate submittal is necessary, process the same as the initial submittal.
 - 3. Allow two weeks for reprocessing each submittal.

4. No extension of Contract Time will be authorized because of failure to transmit submittals to the Engineer sufficiently in advance of the Work to permit processing.
- D. Submittal Preparation: Place a permanent label or title block on each submittal for identification. Indicate the name of the entity that prepared each submittal on the label or title block.
 1. Include the following information on the label for processing and recording action taken.
 - a. Project name.
 - b. Date.
 - c. Name and address of Engineer.
 - d. Name and address of Contractor.
 - e. Name and address of subcontractor.
 - f. Name and address of supplier.
 - g. Name of manufacturer.
 - h. Number and title of appropriate Specification Section.
 - i. Drawing number and detail references, as appropriate.
- E. Submittal Transmittal: Package each submittal appropriately for transmittal and handling. Transmit each submittal from Contractor to Engineer using a transmittal form. Submittals received from sources other than the Contractor will be returned without action. On the transmittal, record relevant information and requests for data. On the form, or separate sheet, record deviations from Contract Document requirements, including minor variations and limitations. Include Contractor's certification that information complies with Contract Document requirements.
- F. Except for submittals for record, information or similar purposes, the Engineer will review each submittal, mark to indicate action taken, and return promptly. Compliance with specified characteristics is the Contractor's responsibility.
- G. Action Stamp: The Engineer will stamp each submittal with a uniform, self-explanatory action stamp. The stamp will be appropriately marked, to indicate the action taken.

1.12 COORDINATION WITH OTHER DIVISIONS

- A. All work shall be carried out in conjunction with other trades and full cooperation shall be given in order that all work may proceed with a minimum of delay and interference. Particular emphasis is placed on timely installation of major apparatus and furnishing other Contractors, especially the Contractor or Construction Manager, with information as to openings, chases, sleeves, bases, inserts, equipment locations, panels, etc., required by other trades.
- B. The Contractors are required to examine all of the Project Drawings and mutually arrange work so as to avoid interference with the work of other trades. In general, ductwork, HVAC piping, sprinkler piping and drainage lines take precedence over water, gas and electrical conduits. The Engineer shall make final decisions regarding the arrangement of work which cannot be agreed upon by the Contractors.
- C. Where the work of the Contractor will be installed in close proximity to or will interfere with work of other trades, the Contractors will cooperate in working out space conditions to make a satisfactory adjustment.
- D. If the work under a Section is installed before coordinating with other Divisions or Sections or so as to cause interference with work of other Sections, the necessary

changes to correct the condition shall be made by the Contractor causing the interference without extra charge to the Owner.

1.13 QUALITY CONTROL

- A. Service Support: The equipment items shall be supported by service organizations which are reasonably convenient to the equipment installation in order to render satisfactory service to the equipment on a regular and emergency basis during the warranty period of the contract.
- B. Modification of References: In each of the publications referred to herein, consider the advisory provisions to be mandatory, as though the word, "shall" had been substituted for "should" wherever it appears.
- C. The Contractor shall furnish the services of an experienced superintendent who shall be constantly in charge of the installation of the work together with all skilled workmen, journeymen, electricians, helpers and laborers required to unload, transfer, erect, connect, adjust, start, operate and test each system.
- D. Unless otherwise specifically indicated on the Drawings or Specifications, all equipment and materials shall be installed with the acceptance of the Engineer and in accordance with the recommendations of the manufacturer. This includes the performance of such tests as the manufacturer recommends.
- E. All labor for installation of electrical systems shall be performed by experienced, skilled tradesmen under the supervision of a licensed journeyman foreman. All work shall be of a quality consistent with good trade practice and shall be installed in a neat, workmanlike manner. The Engineer reserves the right to reject any work which, in his opinion, has been installed in a substandard, dangerous or unserviceable manner. The Contractor shall replace said work in a satisfactory manner at no extra cost to the Owner.

1.14 SHUTDOWNS

- A. When installation of a new system requires the temporary shutdown of an existing operating system, the connection of the new system shall be performed at such time as designated by the Owner.
- B. The Engineer and the Owner shall be notified in writing of the estimated duration of the shutdown period at least ten (10) days in advance of the date the work is to be performed.
- C. Work shall be arranged for continuous performance whenever possible. The Contractor shall provide all necessary labor, including overtime if required, to assure that existing operating services will be shut down only during the time actually required to make necessary connections.

1.15 PROTECTION OF MATERIALS AND EQUIPMENT

- A. Work under each Section shall include protecting the work and material of all other Sections from damage by work or workmen and shall include making good all damage thus caused.
- B. The Contractor shall be responsible for work and equipment until the facility has been accepted by the Owner. Protect work against theft, injury or damage and carefully store material and equipment received on site which is not immediately installed. Close open

ends of work with temporary covers or plugs during construction to prevent entry of foreign material.

- C. Work under each Section includes receiving, unloading, uncrating, storing, protecting, setting in place and completely connecting equipment supplied under each Section. Work under each Section shall also include exercising special care in handling and protecting equipment and fixtures, and shall include the cost of replacing any of the equipment and fixtures which are missing or damaged.
- D. Equipment and material stored on the job site shall be protected from the weather, vehicles, dirt and/or damage by workmen or machinery. Insure that all electrical or absorbent equipment or material is protected from moisture during storage.

1.16 ADJUSTING AND TESTING

- A. After all the equipment and accessories to be furnished are in place, they shall be put in final adjustment and subjected to such operating tests so as to assure the Engineer that they are in proper adjustment and in satisfactory, permanent operating condition.
- B. Where requested by the Engineer, a factory-trained service representative shall inspect the installation and assist in the initial startup and adjustment to the equipment. The period of these services shall be for such time as necessary to secure proper installation and adjustments. After the equipment is placed in permanent operation, the service representative shall supervise the initial operation of the equipment and instruct personnel responsible for operation and maintenance of the equipment. The service representative shall notify the Contractor in writing that the equipment was installed according to manufacturer's recommendations and is operating as intended by the manufacturer.

1.17 CLEANING

- A. The Contractor shall thoroughly clean all equipment of all foreign substances, oils, dust, dirt, etc., inside and out before final acceptance by the Engineer.
- B. If any part of a system should be stopped or damaged by any foreign matter after being placed in operation, the system shall be disconnected, cleaned and reconnected wherever necessary to locate and/or remove obstructions. Any work damaged in the course of removing obstructions shall be repaired or replaced when the system is reconnected at no additional cost to the Owner.
- C. During the course of construction, all conduits shall be capped in an acceptable manner to insure adequate protection against the entrance of foreign matter.
- D. Upon completion of all work under the Contract, remove from the premises all rubbish, debris and excess materials left over from his work. Any oil or grease stains on floor areas shall be removed and floor areas left clean.
- E. Complete the following cleaning operations before requesting inspection for Certification of Substantial Completion.
 1. Remove labels that are not permanent labels.
 2. Clean transparent materials, including mirrors and glass in doors and windows. Remove glazing compound and other substances that are noticeable vision-obscuring materials. Replace chipped or broken glass and other damaged transparent materials.

3. Clean exposed exterior and interior hard-surfaced finishes to a dust-free condition, free of stains, films and similar foreign substances. Restore reflective surfaces to their original reflective condition. Leave concrete floors broom clean. Vacuum carpeted surfaces and panelboard interiors.
4. Wipe surfaces of equipment. Remove excess lubrication and other substances.

F. Comply with regulations of authorities having jurisdiction and safety standards for cleaning. Do not burn waste materials. Do not bury debris or excess materials on the Owner's property. Do not discharge volatile, harmful or dangerous materials into drainage systems. Remove and dispose of ALL waste materials, packaging material, skids etc. from the site and dispose of in a lawful manner in accordance with municipal, state and federal regulations.

G. Where extra materials of value remaining after completion of associated Work have become the Owner's property, arrange for disposition of these materials as directed.

1.18 OPERATING AND MAINTENANCE

- A. Upon completion of all work and tests, the Contractor shall furnish the necessary skilled labor and helpers for operating his system and equipment for a period specified under each applicable Section of this Division. During this period, he shall fully instruct the Owner or the Owner's representative in the operation, adjustment and maintenance of all equipment furnished. The Contractor shall give at least seven (7) day notice to the Owner and the Engineer in advance of this period.
- B. The Contractor shall physically demonstrate procedures for all routine maintenance of all equipment furnished under each respective Section to assure accessibility to all devices.
- C. Refer to individual trade Sections for any other particular requirements related to operating instructions.

1.19 RECORD DRAWINGS

- A. General: Do not use record documents for construction purposes; protect from deterioration and loss in a secure, fire-resistive location; provide access to record documents for the Engineer's reference during normal working hours.
- B. Record Drawings: Maintain a clean, undamaged set of blue or black line white-prints of Contract Drawings and Shop Drawings. Mark the set to show the actual installation where the installation varies substantially from the Work as originally shown. Mark whichever drawing is most capable of showing conditions fully and accurately; where Shop Drawings are used, record a cross-reference at the corresponding location on the Contract Drawings.

1.20 WARRANTIES AND BONDS

- A. The following general administrative and procedural requirements for warranties and bonds required by the Contract Documents, including manufacturers standard warranties on products and special warranties are to be included:
 1. General close-out requirements included in Section "Project Close-out."
 2. Specific requirements for warranties for the Work and products and installation that are specified to be warranted, are included in the individual Sections of Divisions 02 through [50].
 3. Certifications and other commitments and agreements for continuing services to Owner are specified elsewhere in the Contract Documents.

- B. Disclaimers and Limitations: Manufacturer's disclaimers and limitations on product warranties do not relieve the Contractor of the warranty on the Work that incorporates the products, nor does it relieve suppliers, manufacturers, and subcontractors required to countersign special warranties with the Contractor.
- C. Separate Prime Contracts: Each prime Contractor is responsible for warranties related to its own Contract.

1.21 WARRANTY REQUIREMENTS

- A. Related Damages and Losses: When correcting warranted Work that has failed, remove and replace other Work that has been damaged as a result of such failure or that must be removed and replaced to provide access for correction of warranted Work.
- B. Reinstatement of Warranty: When Work covered by a warranty has failed and been corrected by replacement or rebuilding, reinstate the warranty by written endorsement. The reinstated warranty shall be equal to the original warranty with an equitable adjustment for depreciation.
- C. Replacement Cost: Upon determination that Work covered by a warranty has failed, replace or rebuild the Work to an acceptable condition complying with requirements of Contract Documents. The Contractor is responsible for the cost of replacing or rebuilding defective Work regardless of whether the Owner has benefited from use of the Work through a portion of its anticipated useful service life.
- D. Owner's Recourse: Written warranties made to the Owner are in addition to implied warranties, and shall not limit the duties, obligations, right and remedies otherwise available under the law, nor shall warranty periods be interpreted as limitations on time in which the Owner can enforce such other duties, obligations, rights, or remedies.
- E. Rejection of Warranties: The Owner reserves the right to reject warranties and to limit selections to products with warranties not in conflict with requirements of the Contract Documents.
- F. The Owner reserves the right to refuse to accept Work for the Project where a special warranty, certification, or similar commitment is required on such Work or part of the Work, until evidence is presented that entities required to countersign such commitments are willing to do so.
- G. Submit written warranties to the Engineer prior to the date certified for Substantial Completion. If the Engineer's Certificate of Substantial Completion designates a commencement date for warranties other than the date of Substantial Completion for the Work, or a designated portion of the Work, submit written warranties upon request of the Engineer.
- H. When a designated portion of the Work is completed and occupied or used by the Owner, by separate agreement with the Contractor during the construction period, submit properly executed warranties to the Engineer within fifteen days of completion of that designated portion of the Work.
- I. When a special warranty is required to be executed by the Contractor, or the Contractor and a subcontractor, supplier or manufacturer, prepare a written document that contains appropriate terms and identification, ready for execution by the required parties. Submit a draft to the Owner through the Engineer for approval prior to final execution.

1.22 GUARANTEES

- A. The Contractor shall guarantee all material and installation quality under these Specifications and the Contract for a period of one (1) year from the date of final acceptance by Owner. During this guarantee period, all defects developing through faulty equipment, materials or installation quality shall be corrected or replaced immediately by this Contractor without expense to the Owner. Such repairs or replacements shall be made to the Engineer's satisfaction..
- B. Contractor shall provide name, address, and phone number of all contractors and subcontractors and associated equipment they provided

1.23 PROJECT CLOSE-OUT

- A. Contractor shall submit annual maintenance proposal to the Architect/Engineer for review and approval as part of the close out documents.
- B. Submit specific warranties, workmanship bonds, maintenance agreements, final certifications and similar documents.
- C. Deliver tools, spare parts, extra stock, and similar items.
- D. Complete start-up testing of systems, and instruction of the Owner's operating and maintenance personnel. Discontinue or change over and remove temporary facilities from the site, along with construction tools, mock-ups, and similar elements.
- E. Complete final clean up requirements, including touch-up painting. Touch-up and otherwise repair and restore marred exposed finishes.
- F. Inspection Procedures: On receipt of a request for inspection, the Engineer will either proceed with inspection or advise the Contractor of unfilled requirements. The Engineer will prepare the Certificate of Substantial Completion following inspection, or advise the Contractor of construction that must be completed or corrected before the certificate will be issued.
 - 1. The Engineer will repeat inspection when requested and assured that the Work has been substantially completed.
 - 2. Results of the completed list of unfulfilled items will form the basis of requirements for final acceptance.

END OF SECTION

SECTION 26 05 01

ELECTRICAL DEMOLITION

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Prior to beginning work, test the existing systems as appropriate and document all deficiencies affecting the work under this contract to the architect and owner. Provide a cost proposal for recommended solutions. Do not proceed with the corrective work until authorized by the owner or their appointed representatives.
- B. Electrical demolition.

1.2 RELATED REQUIREMENTS

- A. Division 01 – General Requirements.
- B. Section 26 04 00 – General Conditions for Electrical Trades.
- C. Division 02 - Existing Conditions

1.3 SUBMITTALS

- A. Division 01 – General Requirements.
- B. Section 26 04 00 – General Conditions for Electrical Trades.

PART 2 PRODUCTS

2.1 MATERIALS AND EQUIPMENT

- A. Materials and equipment for patching and extending work: As specified in individual sections.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Demolition drawings are based on limited field observation and existing record documents where available.
- B. Report discrepancies to Architect/Engineer before disturbing existing installation.
- C. Beginning of demolition means installer accepts existing conditions.
- D. Contractor shall modify existing circuits, when existing devices are removed, as required to maintain circuit continuity.

3.2 PREPARATION

- A. Disconnect electrical systems in walls, floors, and ceilings to be removed.
- B. Provide temporary wiring and connections to maintain existing systems in service during construction. When work must be performed on energized equipment or circuits, use personnel experienced in such operations.
- C. Phased Construction: Provide temporary equipment, wiring, conduit, labor and materials as required to maintain operation of existing systems during all phases of construction.

3.3 DEMOLITION AND EXTENSION OF EXISTING ELECTRICAL WORK

- A. Remove, relocate, and extend existing installations to accommodate relocated/reinstalled equipment as indicated.
- B. Remove abandoned wiring to source of supply.
- C. Remove exposed abandoned conduit, including abandoned conduit above accessible ceiling finishes. Cut conduit flush with walls and floors, and patch surfaces.
- D. Repair adjacent construction and finishes damaged during demolition and extension work.
- E. Maintain access to existing electrical installations that remain active. Modify installation or provide access panel as appropriate.
- F. Extend existing installations using materials and methods compatible with existing electrical installations, or as specified.

3.4 CLEANING AND REPAIR

- A. Division 01 - General Requirements.
- B. Clean and repair existing materials and equipment that remain or that are to be reused.

END OF SECTION

SECTION 26 05 03

EQUIPMENT WIRING CONNECTIONS

PART 1 GENERAL

1.1 SUMMARY

- A. Section includes electrical connections to equipment.

1.2 RELATED SECTIONS

- A. Division 01 – General Requirements
- B. Section 26 04 00 – General Conditions for Electrical Trades.

1.3 REFERENCE STANDARDS

- A. National Electrical Manufacturers Association:
 - 1. NEMA WD 1 - General Requirements for Wiring Devices.
 - 2. NEMA WD 6 - Wiring Devices-Dimensional Requirements.

1.4 SUBMITTALS

- A. See Division 01 - General Requirements
- B. Product Data: Submit device manufacturer's catalog information showing dimensions, configurations, and construction.
- C. Provide manufacturer's installation instructions.

1.5 QUALITY ASSURANCE

- A. Comply with NFPA 70.
- B. Comply with latest adopted version of applicable building code, including any addendum or supplements.

1.6 CLOSEOUT SUBMITTALS

- A. See Division 01- General Requirements
- B. Project Record Documents: Record actual locations, sizes, and configurations of equipment connections.

1.7 COORDINATION

- A. See Division 01 - General Requirements
- B. Obtain and review shop drawings, product data, manufacturer's wiring diagrams, and manufacturer's instructions for equipment furnished under other sections.
- C. Determine connection locations and requirements.

- D. Sequence rough-in of electrical connections to coordinate with installation of equipment.
- E. Sequence electrical connections to coordinate with start-up of equipment.

PART 2 PRODUCTS

2.1 ATTACHMENT PLUGS

- A. Manufacturers:
 - 1. Hubbell.
 - 2. Leviton.
 - 3. Legrand / Pass & Seymour
 - 4. Substitutions: Division 01 - General Requirements.
- B. Attachment Plug Construction: Conform to NEMA WD 1.
- C. Configuration: NEMA WD 6; match receptacle configuration to outlet furnished for equipment.
- D. Rating: Suitable for connected load of equipment, length of cord, and rating of branch circuit overcurrent protection.

2.2 FLEXIBLE CORD

- A. Manufacturers:
 - 1. General Cable.
 - 2. Southwire Company.
 - 3. Hubbell Incorporated.
 - 4. Substitutions: Division 01 - General Requirements.
- B. Cord Construction:
 - 1. Type multi-conductor flexible cord with identified neutral and equipment grounding conductor.
 - 2. Rating: 600V, amperage to match full load or MCA rating of equipment being served, sized per NFPA 70, Article 400.5.
 - 3. Conductor Identification:
- C. Neutral:
 - 1. White or gray colored braid.
 - 2. Colored tracer in the braid.
 - 3. White, gray, or light blue insulation.
 - 4. Ridges, grooves, or white stripes on the exterior of the cord.
- D. Equipment Grounding Conductor:
 - 1. Continuous green color.
 - 2. Continuous identifying marker distinguishing it from the other conductors.
- E. Connectors:
 - 1. Type: All steel fitting with gland nut, seal, and bushing for securing cable.
 - 2. Suitable for use for passing cord thru enclosure or bulkhead.
 - 3. Provide with suitable NEMA rating for application.
- F. Strain Relief:
 - 1. Type: Aluminum fitting with galvanized steel mesh, duct-tight

2. Suitable for size and type of flexible cord being used.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Division 01 - Administrative Requirements: Coordination and project conditions.
- B. Verify equipment is ready for electrical connection, for wiring, and to be energized.

3.2 EXISTING WORK

- A. Remove exposed abandoned equipment wiring connections.
- B. Disconnect abandoned utilization equipment and remove wiring connections. Remove abandoned components when connected raceway is abandoned and removed. Install blank cover for abandoned boxes and enclosures not removed.
- C. Extend existing equipment connections using materials and methods as specified.

3.3 INSTALLATION

- A. Make conduit connections to equipment using flexible metal conduit. Use liquidtight flexible metal conduit with watertight connectors in damp or wet locations.
- B. Connect heat producing equipment using wire and cable with insulation suitable for temperatures encountered.
- C. Provide receptacle outlet and plate to accommodate connection to attachment plug.
- D. Provide flexible cord and cord-cap for field-supplied attachment plug. Coordinate exact requirements with equipment supplier.
- E. Install suitable strain-relief clamps and fittings for cord connections at outlet boxes and equipment connection boxes.
- F. Install disconnect switches, controllers, control stations, and control devices to complete equipment wiring requirements.
- G. Install terminal block jumpers to complete equipment wiring requirements.
- H. Install interconnecting conduit and wiring between devices and equipment to complete equipment wiring requirements.

END OF SECTION

SECTION 26 05 19

ELECTRICAL POWER CONDUCTORS AND CABLES

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Single conductor building wire.
- B. Power and control tray cable.
- C. Electrical tape.
- D. Heat shrink tubing.
- E. Oxide inhibiting compound.
- F. Wire pulling lubricant.
- G. Cable ties.

1.2 RELATED REQUIREMENTS

- A. Division 01 – General Requirements.
- B. Division 07 – Thermal and Moisture Protection.
- C. Section 26 05 01 – Electrical Demolition : Disconnection, removal, and/or extension of existing electrical conductors and cables.
- D. Section 26 05 26 - Grounding and Bonding for Electrical Systems: Additional requirements for grounding conductors and grounding connectors.
- E. Section 26 05 53 - Identification for Electrical Systems: Identification products and requirements.

1.3 REFERENCE STANDARDS

- A. ASTM B3 - Standard Specification for Soft or Annealed Copper Wire; 2013.
- B. ASTM B8 - Standard Specification for Concentric-Lay-Stranded Copper Conductors, Hard, Medium-Hard, or Soft; 2011.
- C. ASTM B33 - Standard Specification for Tin-Coated Soft or Annealed Copper Wire for Electrical Purposes; 2010 (Reapproved 2014).
- D. ASTM B800 - Standard Specification for 8000 Series Aluminum Alloy Wire for Electrical Purposes - Annealed and Intermediate Tempers; 2005 (Reapproved 2015).
- E. ASTM B801 - Standard Specification for Concentric-Lay-Stranded Conductors of 8000 Series Aluminum Alloy Wire for Subsequent Covering of Insulation; 2016.

- F. ASTM D3005 - Standard Specification for Low-Temperature Resistant Vinyl Chloride Plastic Pressure-Sensitive Electrical Insulating Tape; 2010.
- G. ASTM D4388 - Standard Specification for Nonmetallic Semi-Conducting and Electrically Insulating Rubber Tapes; 2013.
- H. FS A-A-59544 - Cable and Wire, Electrical (Power, Fixed Installation); Federal Specification; Revision A, 2008.
- I. NECA 1 - Standard for Good Workmanship in Electrical Construction; 2015.
- J. NECA 104 - Recommended Practice for Installing Aluminum Building Wire and Cable; 2012.
- K. NECA 120 - Standard for Installing Armored Cable (AC) and Metal-Clad Cable (MC); 2012.
- L. NECA 121 - Standard for Installing Nonmetallic-Sheathed Cable (Type NM-B) and Underground Feeder and Branch-Circuit Cable (Type UF); 2007.
- M. NEMA WC 70 - Power Cables Rated 2000 Volts or Less for the Distribution of Electrical Energy; 2009.
- N. NETA ATS - Acceptance Testing Specifications for Electrical Power Equipment and Systems; 2013.
- O. NFPA 70 - National Electrical Code; Most Recent Edition Adopted by Authority Having Jurisdiction, Including All Applicable Amendments and Supplements.
- P. UL 44 - Thermoset-Insulated Wires and Cables; Current Edition, Including All Revisions.
- Q. UL 83 - Thermoplastic-Insulated Wires and Cables; Current Edition, Including All Revisions.
- R. UL 183 - Manufactured Wiring Systems; Current Edition, Including All Revisions.
- S. UL 486A-486B - Wire Connectors; Current Edition, Including All Revisions.
- T. UL 486C - Splicing Wire Connectors; Current Edition, Including All Revisions.
- U. UL 486D - Sealed Wire Connector Systems; Current Edition, Including All Revisions.
- V. UL 510 - Polyvinyl Chloride, Polyethylene, and Rubber Insulating Tape; Current Edition, Including All Revisions.
- W. UL 719 – Nonmetallic-Sheathed Cables; Current Edition, Including All Revisions.
- X. UL 1277 - Electrical Power and Control Tray Cables with Optional Optical-Fiber Members; Current Edition, Including All Revisions.
- Y. UL 1569 - Metal-Clad Cables; Current Edition, Including All Revisions.

1.4 ADMINISTRATIVE REQUIREMENTS

- A. Coordination:

1. Coordinate sizes of raceways, boxes, and equipment enclosures installed under other sections with the actual conductors to be installed, including adjustments for conductor sizes increased for voltage drop.
2. Coordinate with electrical equipment installed under other sections to provide terminations suitable for use with the conductors to be installed.
3. Notify Architect of any conflicts with or deviations from the contract documents. Obtain direction before proceeding with work.

1.5 SUBMITTALS

- A. See Division 01 – General Requirements.
- B. Product Data: Provide manufacturer's standard catalog pages and data sheets for conductors and cables, including detailed information on materials, construction, ratings, listings, and available sizes, configurations, and stranding.
- C. Manufacturer's Installation Instructions: Indicate application conditions and limitations of use stipulated by product testing agency. Include instructions for storage, handling, protection, examination, preparation, and installation of product.

1.6 QUALITY ASSURANCE

- A. Conform to requirements of NFPA 70.
- B. Manufacturer Qualifications: Company specializing in manufacturing the products specified in this section with minimum three years documented experience.
- C. Product Listing Organization Qualifications: An organization recognized by OSHA as a Nationally Recognized Testing Laboratory (NRTL) and acceptable to authorities having jurisdiction.

1.7 DELIVERY, STORAGE, AND HANDLING

- A. Receive, inspect, handle, and store conductors and cables in accordance with manufacturer's instructions.

1.8 FIELD CONDITIONS

- A. Do not install or otherwise handle thermoplastic-insulated conductors at temperatures lower than 14 degrees F, unless otherwise permitted by manufacturer's instructions. When installation below this temperature is unavoidable, notify Architect and obtain direction before proceeding with work.

PART 2 PRODUCTS

2.1 CONDUCTOR AND CABLE APPLICATIONS

- A. Do not use conductors and cables for applications other than as permitted by NFPA 70 and product listing.
- B. Provide single conductor building wire installed in suitable raceway unless otherwise indicated, permitted, or required.

2.2 CONDUCTOR AND CABLE GENERAL REQUIREMENTS

- A. Provide products that comply with requirements of NFPA 70.
- B. Provide products listed, classified, and labeled as suitable for the purpose intended.
- C. Provide conductors and cables with lead content less than 300 parts per million.
- D. Provide new conductors and cables manufactured not more than one year prior to installation.
- E. Unless specifically indicated to be excluded, provide all required conduit, boxes, wiring, connectors, etc. as required for a complete operating system.
- F. Comply with NEMA WC 70.
- G. Comply with FS A-A-59544 where applicable.
- H. Conductor Material:
 - 1. Copper Conductors: Soft drawn annealed, 98 percent conductivity, uncoated copper conductors complying with ASTM B3, or ASTM B8 unless otherwise indicated.
 - 2. Tinned Copper Conductors: Comply with ASTM B33.
- I. Minimum Conductor Size:
 - 1. Branch Circuits: 12 AWG.
 - a. Exceptions:
 - 1) 20 A, 120 V circuits longer than 75 feet 10 AWG minimum, and sized for voltage drop.
 - 2) 20 A, 120 V circuits longer than 150 feet 8 AWG minimum, and sized for voltage drop.
 - 3) 20 A, 277 V circuits longer than 150 feet: 10 AWG minimum, and sized for voltage drop.
 - 2. Control Circuits: 14 AWG.
- J. Where conductor size is not indicated, size to comply with NFPA 70 but not less than applicable minimum size requirements specified.
- K. Conductor Color Coding:
 - 1. Color code conductors as indicated unless otherwise required by the authority having jurisdiction. Maintain consistent color coding throughout project.
 - 2. Color Coding Method: Integrally colored insulation.
 - a. Conductors size 4 AWG and larger may have black insulation color coded using vinyl color coding electrical tape.
 - 3. Color Code:
 - a. 480Y/277 V, 3 Phase, 4 Wire System:
 - 1) Phase A: Brown.
 - 2) Phase B: Orange.
 - 3) Phase C: Yellow.
 - 4) Neutral/Grounded: Gray.
 - b. 208Y/120 V, 3 Phase, 4 Wire System:
 - 1) Phase A: Black.
 - 2) Phase B: Red.
 - 3) Phase C: Blue.
 - 4) Neutral/Grounded: White.

- c. 240/120 V, 1 Phase, 3 Wire System:
 - 1) Phase A: Black.
 - 2) Phase B: Red.
 - 3) Neutral/Grounded: White.
- d. Equipment Ground, All Systems: Green.
- e. Isolated Ground, All Systems: Green with yellow stripe.
- f. Travelers for 3-Way and 4-Way Switching: Pink.
- g. For modifications or additions to existing wiring systems, comply with existing color code when existing code complies with NFPA 70 and is approved by the authority having jurisdiction.
- h. For control circuits, comply with manufacturer's recommended color code.

2.3 SINGLE CONDUCTOR BUILDING WIRE

- A. Manufacturers:
 - 1. Copper Building Wire:
 - a. Cerro Wire LLC.
 - b. Southwire Company
 - c. General Cable Technologies
 - d. Substitutions: See Section 01 - Product Requirements.
 - 2. Aluminum Building Wire (only where specifically indicated):
 - a. Encore Wire Corporation
 - b. Southwire Company
 - c. Stabiloy, a brand of General Cable Technologies Corporation
 - d. Substitutions: See Section 01 - Product Requirements.
- B. Description: Single conductor insulated wire.
- C. Conductor Stranding:
 - 1. Feeders and Branch Circuits:
 - a. Size 10 AWG and Smaller: Solid.
 - b. Size 8 AWG and Larger: Stranded.
 - 2. Control Circuits: Stranded.
- D. Insulation Voltage Rating: 600 V.
- E. Insulation:
 - 1. Copper Building Wire: Type THHN/THWN or THHN/THWN-2, except as indicated below.
 - a. Installed Underground: Type XHHW-2.
 - 2. Aluminum Building Wire (only where specifically indicated): Type XHHW-2.

2.4 WIRING CONNECTORS

- A. Description: Wiring connectors appropriate for the application, suitable for use with the conductors to be connected, and listed as complying with UL 486A-486B or UL 486C as applicable.
- B. Connectors for Grounding and Bonding: Comply with Section 26 0526.
- C. Wiring Connectors for Splices and Taps:
 - 1. Copper conductors 10 AWG and smaller: Install insulated spring wire connectors with plastic caps

2. Copper Conductors Size 8 AWG: Install solderless pressure connectors with insulating covers
3. Copper Conductors Size 6 AWG and larger: Install pressure connectors or split bolt connectors.
4. Connectors for Aluminum Conductors: Use compression connectors.

D. Wiring Connectors for Terminations:

1. Provide terminal lugs for connecting conductors to equipment furnished with terminations designed for terminal lugs.
2. Provide compression adapters for connecting conductors to equipment furnished with mechanical lugs when only compression connectors are specified.
3. Where over-sized conductors are larger than the equipment terminations can accommodate, provide connectors suitable for reducing to appropriate size, but not less than required for the rating of the overcurrent protective device.
4. Provide motor pigtail connectors for connecting motor leads in order to facilitate disconnection.
5. Copper Conductors Size 8 AWG and Larger: Use mechanical connectors or compression connectors where connectors are required.
6. Aluminum Conductors: Use compression connectors for all connections.
7. Stranded Conductors Size 10 AWG and Smaller: Use crimped terminals for connections to terminal screws.
8. Conductors for Control Circuits: Use crimped terminals for all connections.

E. Do not use insulation-piercing or insulation-displacement connectors designed for use with conductors without stripping insulation.

F. Do not use push-in wire connectors as a substitute for twist-on insulated spring connectors.

G. Twist-on Insulated Spring Connectors: Rated 600 V, 221 degrees F for standard applications and 302 degrees F for high temperature applications; pre-filled with sealant and listed as complying with UL 486D for damp and wet locations.

1. Manufacturers:
 - a. 3M
 - b. Ideal Industries, Inc.
 - c. NSI Industries LLC.
 - d. Ilasco
 - e. Erico
 - f. Substitutions: See Division 01 – General Requirements.

H. Mechanical Connectors: Provide bolted type or set-screw type.

1. Manufacturers:
 - a. Burndy LLC.
 - b. Ilasco
 - c. Thomas & Betts Corporation
 - d. Substitutions: See Division 01 – General Requirements.

I. Compression Connectors: Provide circumferential type or hex type crimp configuration.

1. Manufacturers:
 - a. Burndy LLC.
 - b. Ilasco
 - c. Thomas & Betts Corporation
 - d. Erico
 - e. Substitutions: See Division 01 – General Requirements.

J. Crimped Terminals: Nylon-insulated, with insulation grip and terminal configuration suitable for connection to be made.

1. Manufacturers:
 - a. Burndy LLC.
 - b. IlSCO
 - c. Thomas & Betts Corporation
 - d. Substitutions: See Division 01 – General Requirements.

2.5 WIRING ACCESSORIES

A. Electrical Tape:

1. Manufacturers:
 - a. 3M
 - b. Plymouth Rubber Europa
 - c. Substitutions: See Division 01 – General Requirements.
2. Vinyl Color Coding Electrical Tape: Integrally colored to match color code indicated; listed as complying with UL 510; minimum thickness of 7 mil; resistant to abrasion, corrosion, and sunlight; suitable for continuous temperature environment up to 221 degrees F.
3. Vinyl Insulating Electrical Tape: Complying with ASTM D3005 and listed as complying with UL 510; minimum thickness of 7 mil; resistant to abrasion, corrosion, and sunlight; conformable for application down to 0 degrees F and suitable for continuous temperature environment up to 221 degrees F.
4. Rubber Splicing Electrical Tape: Ethylene Propylene Rubber (EPR) tape, complying with ASTM D4388; minimum thickness of 30 mil; suitable for continuous temperature environment up to 194 degrees F and short-term 266 degrees F overload service.

B. Heat Shrink Tubing: Heavy-wall, split-resistant, with factory-applied adhesive; rated 600 V; suitable for direct burial applications; listed as complying with UL 486D.

1. Manufacturers:
 - a. 3M
 - b. Burndy LLC.
 - c. Thomas & Betts Corporation
 - d. Substitutions: See Division 01 – General Requirements.

C. Oxide Inhibiting Compound: Listed; suitable for use with the conductors or cables to be installed.

1. Manufacturers:
 - a. Burndy LLC.
 - b. Ideal Industries, Inc.
 - c. IlSCO
 - d. Substitutions: See Division 01 – General Requirements.

D. Wire Pulling Lubricant: Listed; suitable for use with the conductors or cables to be installed and suitable for use at the installation temperature.

1. Manufacturers:
 - a. 3M
 - b. American Polywater Corporation
 - c. Ideal Industries, Inc.
 - d. Substitutions: See Division 01 – General Requirements.

E. Cable Ties: Material and tensile strength rating suitable for application.

1. Manufacturers:
 - a. Burndy LLC.
 - b. Substitutions: See Section 01 - Product Requirements.

2. Provide plenum rated cable ties.

PART 3 EXECUTION

3.1 EXISTING WORK

- A. Remove exposed abandoned wire and cable, including abandoned wire and cable above accessible ceiling finishes. Patch surfaces where removed cables pass through building finishes.
- B. Disconnect abandoned circuits and remove circuit wire and cable. Remove abandoned boxes when wire and cable servicing boxes is abandoned and removed. Install blank cover for abandoned boxes not removed.
- C. Provide access to existing wiring connections remaining active and requiring access. Modify installation or install access panel.
- D. Extend existing circuits using materials and methods compatible with existing electrical installations, or as specified.
- E. Clean and repair existing wire and cable remaining or wire and cable to be reinstalled.

3.2 EXAMINATION

- A. Verify that interior of building has been protected from weather.
- B. Verify that work likely to damage wire and cable has been completed.
- C. Verify that raceways, boxes, and equipment enclosures are installed and are properly sized to accommodate conductors and cables in accordance with NFPA 70.
- D. Verify that conditions are satisfactory for installation prior to starting work.

3.3 PREPARATION

- A. Clean raceways thoroughly to remove foreign materials before installing conductors and cables.

3.4 INSTALLATION

- A. Install products in accordance with manufacturer's instructions.
- B. Perform work in accordance with NECA 1 (general workmanship).
- C. Installation in Raceway:
 1. Tape ends of conductors and cables to prevent infiltration of moisture and other contaminants.
 2. Pull all conductors and cables together into raceway at same time.
 3. Do not damage conductors and cables or exceed manufacturer's recommended maximum pulling tension and sidewall pressure.
 4. Use suitable wire pulling lubricant where necessary, except when lubricant is not recommended by the manufacturer.

- D. Paralleled Conductors: Install conductors of the same length and terminate in the same manner.
- E. Secure and support conductors and cables in accordance with NFPA 70 using suitable supports and methods approved by the authority having jurisdiction. Provide independent support from building structure. Do not provide support from raceways, piping, ductwork, or other systems.
 - 1. Installation Above Suspended Ceilings: Do not provide support from ceiling support system. Do not provide support from ceiling grid or allow conductors and cables to lay on ceiling tiles.
 - 2. Installation in Vertical Raceways: Provide supports where vertical rise exceeds permissible limits.
- F. Install conductors with a minimum of 12 inches of slack at each outlet.
- G. Neatly train and bundle conductors inside boxes, wireways, panelboards and other equipment enclosures.
- H. Make wiring connections using specified wiring connectors.
 - 1. Make splices and taps only in accessible boxes. Do not pull splices into raceways or make splices in conduit bodies or wiring gutters.
 - 2. Do not remove conductor strands to facilitate insertion into connector.
 - 3. Clean contact surfaces on conductors and connectors to suitable remove corrosion, oxides, and other contaminates. Do not use wire brush on plated connector surfaces.
 - 4. Connections for Aluminum Conductors: Fill connectors with oxide inhibiting compound where not pre-filled by manufacturer.
 - 5. Mechanical Connectors: Secure connections according to manufacturer's recommended torque settings.
 - 6. Compression Connectors: Secure connections using manufacturer's recommended tools and dies.
- I. Insulate splices and taps that are made with uninsulated connectors using methods suitable for the application, with insulation and mechanical strength at least equivalent to unspliced conductors.
 - 1. Dry Locations: Use insulating covers specifically designed for the connectors, electrical tape, or heat shrink tubing.
 - a. For taped connections, first apply adequate amount of rubber splicing electrical tape or electrical filler tape, followed by outer covering of vinyl insulating electrical tape.
 - b. For taped connections likely to require re-entering, including motor leads, first apply varnished cambric electrical tape, followed by adequate amount of rubber splicing electrical tape, followed by outer covering of vinyl insulating electrical tape.
 - 2. Damp Locations: Use insulating covers specifically designed for the connectors, electrical tape, or heat shrink tubing.
 - a. For connections with insulating covers, apply outer covering of moisture sealing electrical tape.
 - b. For taped connections, follow same procedure as for dry locations but apply outer covering of moisture sealing electrical tape.
 - 3. Wet Locations: Use heat shrink tubing.
- J. Insulate ends of spare conductors using vinyl insulating electrical tape.
- K. Field-Applied Color Coding: Where vinyl color coding electrical tape is used in lieu of integrally colored insulation as permitted in Part 2 under "Color Coding", apply half

overlapping turns of tape at each termination and at each location conductors are accessible.

- L. Identify conductors and cables in accordance with Section 26 05 53.
- M. Install firestopping to preserve fire resistance rating of partitions and other elements, using materials and methods specified in Section 07.
- N. Unless specifically indicated to be excluded, provide final connections to all equipment and devices, including those furnished by others, as required for a complete operating system.

3.5 FIELD QUALITY CONTROL

- A. See Division 01 – General Requirements.
- B. Inspect and test in accordance with NETA ATS, except Section 4.
- C. Perform inspections and tests listed in NETA ATS, Section 7.3.2. The insulation resistance test is required for all conductors. The resistance test for parallel conductors listed as optional is not required.
 - 1. Disconnect surge protective devices (SPDs) prior to performing any high potential testing. Replace SPDs damaged by performing high potential testing with SPDs connected.
- D. Correct deficiencies and replace damaged or defective conductors and cables.

END OF SECTION